Architectural Hardware and Motorized Window Solution

LGFSYSMAC INDIA PVT. LTD.
402-403,Tower C,NDM-2
Netaji Subhash Place, New Delhi 110034

Specification File Number:	**1593.02.00_Lgf_Tech Support_20-21_CRN_Skylight**
Client Name and Location :	**-**
Developer Name and Location :	**N/A**
Consultant Name and Location :	**N/A**
Project Name and Location :	**-**
Date:	**22.03.2021**
Prepared By:	**VRZ**

Type:	Skylight-Parallel	**Skylight**	Glass:	10mm + 1.52mm PVB. +8mm	
Typology:	Single Shutter	**Motorized (Option-03)**	Material:	Aluminium	
Level:	-		**Testing Status**	**NA**	
Location:	-		Wind Load	1.5	Kpa
Code:	-		Proof Load	2.25	Kpa
Sliding Sash size:	1500mm (W) x 1200MM (H)		Sash Weight:	92	Kgs

Manufacturer	Product code	Description	units	Quantity per typology	No. Of Window	Total Qty.
UCS	41750O	SYNCHRO T-Rack 24Vdc - 1000N - 350mm	pc	4	1	4
UCS	41761Z	Sliding bracket T-Rack	pc	4	1	4
UCS	40490Y	Weather Control Unit for 230 Vac actuators (rain and wind sensors included)	pc	1	1	1
UCS	40893D	Switching Power Supply - 8,4 A	pc	1	1	1
UCS	40995J	Relais box RB24	pc	1	1	1
UCS	41734Y	Radio receiver for 24Vdc actuators	pc	1	1	1
UCS	41729T	Radio transmitter 6 ch	pc	1	1	1
Securistyle	PX0670L	Frictional Hinge @ Left-Parallel	pc	1	1	1
Securistyle	PX0670R	Frictional Hinge@ Right-Parallel	pc	1	1	1
Securistyle	C8688	Stops at Left and Right	pc	2	1	2
Securistyle	PX0950R	Control stays @ Top-Parallel	Pair	1	1	1
Securistyle	CPB2	Pull in Blocks	sets	2	1	2

Note:
A1) We have assumend that the profiles will be suitable for the fitment of the heavy duty Hinges.
A2) All hardware are subject to physical sampling.
A3) The above specification for the hinges and locking is subject to practical test performed by the window fabricator to determine the final results.

NOTE:
1. All hardware compatibility to be confirmed practically.
2. In case of hardware specification for UCS product line, the same will be treated as a prelim enquiry in case floor plans (schedule) are not provided with the
3. In case of specification for estimation purposes; we may not have considered the drawings provided with the enquiry.
4. At the time of specification; consideration is given only to wind pressure provided and does not cover test / lab / proof load requirements, which may vary case

SUMMARY **Motorized (Paralle POP out)**

Manufacturer		Product Code		Description		Total Quantity
UCS		41750O		SYNCHRO T-Rack 24Vdc - 1000N - 350mm	pc	4
UCS		41761Z		Sliding bracket T-Rack	pc	4
UCS		40490Y		Weather Control Unit for 230 Vac actuators (rain and wind sensors included)	pc	1
UCS		40893D		Switching Power Supply - 8,4 A	pc	1
UCS		40995J		Relais box RB24	pc	1
UCS		41734Y		Radio receiver for 24Vdc actuators	pc	1
UCS		41729T		Radio transmitter 6 ch	pc	1
Securistyle		PX0670L		Frictional Hinge @ Left-Parallel	pc	1
Securistyle		PX0670R		Frictional Hinge@ Right-Parallel	pc	1
Securistyle		C8688		Stops at Left and Right	pc	2
Securistyle		PX0950R		Control stays @ Top-Parallel	Pair	1
Securistyle		CPB2		Pull in Blocks	sets	2