KANSAI NEROLAC

ISO 9001 CERTIFIED

KANSAI NEROLAC PAINTS LIMITED

F-2,F-3,MIDC,Lote Parshuram Industrial Area, Tal,Khed,Dist.Ratnagiri-415722
Tel : (02356) 272122,272133,Fax: (02356) 272135 email: ppilote@nerolac.com

TEST CERTIFICATE

Product :-	Epoxy Polyester powder coating
Description :-	EPP GLOSSY RAL 9001(MF)_20K
Ref.No. :-	9006600
B No. :-	3575995
Mfg Date :-	JAN-24

S.No.	PARTICULARS	SPECIFICATION	RESULTS
1	Shade	As per STD.	As per STD.
2	Baking Schedule(Obj.Temp)	180°C/10'	180°C/10'
3	Dry Film Thickness(Microns)	50 - 60	55 - 60
4	Flexibility	3.25 mm	Passes
5	Erichsen Cupping Value	9.0 mm	Passes
6	Gloss @ 60°	90 - 100 %	97-98%
7	Cross Hatch Adhesion	GT '0'	Passes
8	Impact(KgCm)	150	Passes
9	Scratch Hardness(Gms)	3000	Passes
10	Pencil Hardness	2 H	Passes
11	Specific Gravity	1.55 to 1.65	1.59
12	Particle Size Distribution		
	Under 63 Microns	89 - 95 %	91.40%
	Under 90 Microns	95 - 100 %	98.80%
	Under 125 Microns	98 - 100 %	100.00%

(Above tests are carried out on 0.6 mm thick M.S. Panels degreased, scuffed with 240 no. emery paper & cleaned with solvent)Material is to be stored dry place & at temp.below 30°C in an unopen & undamaged condition self life of material,if stored as per above condition,is 6 months after 6 months revalidation is recommended before it is used

This is computer generated TC does not required signature.

NIHVA TECHNOLOGIES PVT. LTD. PUNE