AUFTRAGSBESTÄTIGUNG/
ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No** 30644613 **Datum/Date** 2017-11-09 **Referenz/Reference** Mr. Dange **Verkäufer/Salesman**

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Tatjana Rerich 02941/766-748	Sea freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA- 335	FCA / Lippstadt / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 60

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Versanddatum** **Ship date**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
10	**AD_RR300_PLUSAlbany RR300_plus**		**2017-12-04**	**1.000**	**ST**	**4,083.00**	**4,083.00**

Serien-Nr. 1300009933

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

20 AD_RR300_PLUSAlbany RR300_plus 2017-12-04 1.000 ST 4,090.00 4,090.00

Serien-Nr. 1300009934

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

30 AD_RR300_PLUSAlbany RR300_plus 2017-12-05 1.000 ST 4,090.00 4,090.00

Serien-Nr. 1300009935

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Dimension packing 2 LxWxH 800X600X580

40 AD_RR300_PLUSAlbany RR300_plus 2017-12-05 1.000 ST 4,021.00 4,021.00

Serien-Nr. 1300009936

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	3.000 mm
Daylight height	3.000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	3.000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

50 AD_RR300_PLUSAlbany RR300_plus 2017-12-05 1.000 ST 3,810.00 3,810.00

Serien-Nr. 1300009937

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2.000 mm
Daylight height	3.000 mm
Door control system	MCC VectorControl - frequency converter control system for a

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

	dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	3.000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3500X480X400
Dimension packing 2 LxWxH	800X600X580

60 AD_RR300_PLUSAlbany RR300_plus 2017-12-05 1.000 ST 3,977.00 3,977.00

Serien-Nr. 1300009938

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2.450 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos.	Produkt	Beschreibung	Versanddatum	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	Ship date	QTY	Unit	Price/Unit	Price

Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

70 AD_RR300_PLUSAlbany RR300_plus 2017-12-06 1.000 ST 3,977.00 3,977.00

Serien-Nr. 1300009939

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	2.500 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

	open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Red, similar to RAL 3002
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4000X480X400
Dimension packing 2 LxWxH	800X600X580

80 AD_RR5000 Albany RR3000 ISO 2017-12-04 1.000 ST 8,726.00 8,726.00

Serien-Nr. 2701001511

Door type	RapidRoll 3000 ISO_
Daylight width	3.000 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type Al
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	4
Window level	1.335 mm
CE - Sign	Yes
Packing	Heat treated pallet

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Warranty	1 Year
Dimension packing 1 LxWxH	3880X800X1150
Dimension packing 2 LxWxH	4500X800X600

90 AD_RR5000 Albany RR3000 ISO 2017-12-04 1.000 ST 8,726.00 8,726.00

Serien-Nr. 2701001512

Door type	RapidRoll 3000 ISO_
Daylight width	3.000 mm
Daylight height	3.500 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,1 m/s
Max. Closing Speed	0,7 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	3
Side frame version	Galvanised steel
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Top roll material	Top roll made of steel
Door curtain	Lamella type AI
MCC type	Standard version
MCC-display position	Mounted on the side frame, drive side
MCC display type	Standard display with push buttons
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	4.500 mm
Light curtain	With light curtain integrated in the side frames
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
Qty. window lamella	4
Window level	1.335 mm
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3880X800X1150
Dimension packing 2 LxWxH	4500X800X600

Warenwert/Value of goods		**45,500.00**
Export packing		**463.00**
Summe/Total	**EUR**	**45,963.00**

Wir danken für Ihren Auftrag Thank you for the order

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson

Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Juan Vargues
Per Hansson