NIHVA Technologies Pvt. Ltd.

Technical Specifications
Secondary Packeging System

Customer: ITC Ltd, Spice Division, Guntur	Supplier: NIHVA Technologies Pune Maharashtra, India
contact: Mr. C N Kiran	Contact: Mr. Mayur Derle

Scope of Supply & Scope of work

S.No	Description	Quantity/ Remarks	Scope
A	Scope of Supply		
1	Take-Up Conveyor	2	NIHVA Technologies
2	Diverters	2	NIHVA Technologies
3	Online Pouch Check Weigher	1	Sartorius Mechatronics India Pvt Ltd
4	Automatic Stacker Unit	1	NIHVA Technologies
5	Carton Errector	1	NIHVA Technologies
6	Stack pusher & Collecting Arm	1	NIHVA Technologies
7	Workstation-Manual Lid Closing	1	NIHVA Technologies
8	Carton Sealer	1	NIHVA Technologies
9	Control Panel	1	NIHVA Technologies
B	Scope of work		
1	Design, Engineering, Manufacturing and supply of Box Packaging Line		NIHVA Technologies
2	Installation of the machine		NIHVA Technologies
3	Commissioning of the machine		NIHVA Technologies
4	Operation and maintenance manual Contents 1. Assembly Drawings 2. Electrical Drawings 3. Pneumatic Drawings		NIHVA Technologies
5	Training to Engineers and Supervisor for operation and maintenance of machine		NIHVA Technologies

c	**Exclusion**		
	Civil Work		Customer
	Mains Power Cable		Customer
	Pneumatic Air Supply of 6 Bar		Customer
	Electrical Work outside Battery Limit		Customer
	Mechanical Fabrication Work at Site		Customer

TECHNICAL SPECIFICATIONS SHEET FOR AUTOMATIC SECONDARY PACKEGING SYSTEM		
Sr. No	Packaging Material Data	
1	Weight of Filled Pouch (Type)	100-1000G
2	Size of the Filled Pouch	200X255X115.5 - 340X445X210
3	Pouch Speed	100-30 PPM
4	No of pouches in 1 Box	20-6 /BOX
5	Weight of the filled Box	1.5-6 Kgs
6	Size of the Box	as per Annexture
7	Type of Box	Printed Half regular slotted type Kraft Paper Box
Secoundary Packing Line Specifications and Utility Data		
1	Machine Speed	120PPM
2	Machine Overall Area	Refer Diagram
3	Machine Power Consumption	4-5 KW
4	Compressed Air Requirement	6 Bar Line
5	Air Consumption	1.2 CFM
A	**Take-Up Conveyor**	
1	Speed of Conveyor	minimum 35 m/min
2	Length (Center to Center)	2m
3	Belt Width	300 mm
4	Material of belt	food grade belt
5	Motor	Geared Motor
6	Sensor for pouch count at feed conveyor	Sick Make
B	**Divertor**	
1	Speed of operations	120 rotations/min
2	Material	SS Plate
2	Control Action	Control with rotary cylinder
3	Size	250mm
C	**Check Weigher**	
1	Minimum Weight	100 gms
2	Maximum weight	1200 gms
3	Weighing range	2-3000 gms
4	Accuracy	is + /-0.6 gms
5	Belt Width	300
6	Belt speed	120 m/min
7	Length	1200mm overall
8	Material of construction	MS Powder Coated
9	Type of Rejecter	Pneumatic Pusher Type
10	Power Consumption	approx. 350 VA
D	**Automatic Stacker Unit**	
1	Pneumatics	
1.1	Make of Piston	Festo Make
1.2	Cylinder dia	20mm
1.3	Stroke length	250mm
1.4	Operating Pressure	4-6 bar
2.0	Body Material	SS304
3.0	structre	Adjustable SS structre
4.0	LM Guides	Hiwin
5.0	Vibrator	Yes
6.0	Tapper	Yes 1 Nos

E	**Carton Errector**	
1	Carton Errection speed	
2	Body material	Mild Steel Powder Coated
3	Maximum Size	1500mm
4	Sealing Mechanism	Pre Glued Boxed
5	Pressing Mechanism	one nos of mechanism
6	Suction Mechanism	two mechanisms
F	**Manual Lid Closing Workstation**	
1	Conveyor Length	1.5m
2	Width	500
3	Mechanism	Spring stopper Mechanism
4	Seam	Double Thread Chain Stitch
G	**Sealer**	
1	Type	Powerised sealer unit
2	Pneumatics	Cylinder Both side sealer
3	Mechanism	Holding and Pushing
4	Cylinder Make	Festo

List of Standard Boughout Items		
1	Gear Boxes	Sew/Bonfiglioli
2	Motors	Sew/Bonfiglioli
3	Bearings	SKF/Hiwin
4	Pneumatics	SMC/FESTO
5	PLC	Siemens/Mitsubishi
6	HMI	Mitsubishi
7	LM Guides	HiWin
8	Weighing Scale and Controller	Sartorius
9	Sensors	Sick
10	Control Panel	Nihva

POINTS TO BE NOTED		
Sr No	Description	Remarks
1	Machine FAT	Machine FAT will be carried out at NIHVA Factory in Pune where the pouch samples send by the End user will be tested and certified for satisfactory performance.

NOTE : The Technical Specification may change and will be review after the system design.