| Technical Specifocations | | |
|---|---|---|
| **Sr. No** | **Description** | **Specifications** |
| 1 | **Door Type** | ALU High Speed Roling Shutters |
| 2 | **Size** | 2780(W)x4000(H)mm |
| 3 | **Use** | External Application |
| 4 | **Speed** | Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking |
| 5 | **Opening speed** | upto 2 m/s |
| 6 | **Closing speed** | 0.7 m/s |
| 7 | **Control Panel** | 3 Push Button operated |
| 8 | **Security Features** | EN 13241-1 Standard |
| 9 | **Resistance to wind load** | EN12424 upto class 1 |
| 10 | **Curtain** | 19 mm thk , Polyurethane filled RAL 9006 aluminium lamella |
| 11 | **Guide Material** | Aluminium Anodized , Painting in any RAL9006 lamalla colour |
| 12 | **Hood & Motor Cover** | Anodised Aluminum , Inclusive |
| 13 | **Operator & Control** | German Make Motor |
| 14 | **Connecting Voltage** | 220V , 1Ph , N |
| 15 | **Open-Stop-Close Button** | Standarad |
| 16 | **Protection Category** | IP 54 |
| 17 | **Emergency Off Button** | Standard |
| 18 | **Closing Zone Monitoring** | Optical Safety edge |
| 19 | **Safety Device** | Photocell |
| 20 | **Emergency Opening** | Crank Handle |

