Technical sheet of product used

(Considering trials)

Industrial motors	: - LHP / Crompton & Greaves / SEW
Servomotors	: - Panasonic / SEW
Pneumatic Cylinder	: - SMC
PLC & drives	: - Siemens / Mitsubishi
HMI	: - Mitsubishi
Structure	: - SS304
Sensor	: - SICK

Take-up conveyor

- Take-up conveyor is mainly used to elevate pouches to a desired height to accommodate further process.
- 60 PPM each conveyor output, speed matching of check weighed and FFS VFD is used.
- Divertor for the different line selection. Motor is as above mentioned.
- Conveyor are equipped with castor wheels to aid maintenance, other activities & adjustments
- It consists of food grade belt & VFD drive for speed adjustment.

Divertor:

- Divertor is a simple device which incorporates to maintain balance between flows of two conveyor lines.
- When pouch of 1st line is required at Checkweigher it stops the incoming pouch from 2nd conveyor by reducing speed of other line.
- Obstructing it done by deflector itself.
- It mainly has servo system for the process flow.

Checkweigher: -

- Checkweigher is a state of art device which has three stages of work. 1st one is infeed, second is weight checking and 3rd is out feed.

- 120PPM adjustable speed

- Capacity 100gm to 1200gm
- Rejection & storing capability.
- Accuracy: - +/- 3gm

Stacker : -

- Working speed adjustable as per check weighed speed.
- SS structure is used.
- Vibrator is used to level up the pouches stacked.
- Set filled in the box specified.
- PLC logic are to be used to control actions with servo.
- Tapper is used to help stacking go well.

Carton Erector:

- It is a device used to open boxes from its packaged state to the open state.
- Cartons are coming in a pre-cut and pre-jointed form to be opened in sequence so as to form a box.
- This box is then dropped on the out-feed conveyor.
- It consists of cylinder & sucker assembly to erect the boxes & place it on the conveyor.
- 15-20 boxes per minute output.

Pusher assembly:

- It is a joint-part of Stacker assembly and Collecting Arm.
- Collecting arm is used to push collected stack of pouches when reach to desired count as user specified count matrix.
- It has the cylinder operation to place the stack pouches in the box.
- It has a frame to adjust as per the boxes.

Manual Lid Closing workstation:

- When pouch stack is pushed in to box then that box is move to Lid closing workstation.
- Here manually lids are placed to box.
- 2 worker can work at a time at this station.
- Passed through spring blocker towards the sealer Guides.

Guides:

- Guides are used to help the filling up process at proper orientation.

- It guides the pouches while moving in to the stacker by offering aid to move in to the stacker.
- Similar guide is used in stacker for the proper stacking.
- Guide passes through half conveyor.

Sealing:

- In sealing closed box in moved in through guides by manual push through sealing process is started and seal tape is moved around the box and seal it.
- Sealing is done through both side.
- Up & down process control by servo system.