Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

CE - Sign Yes
Packing Heat treated pallet
Warranty 1 Year
Dimension packing 1 LxWxH 3000X480X400
Dimension packing 2 LxWxH 800X600X370
Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH 3100x530x430
Dimension packing 2 LxWxH 800x600x530
Net Weight 187,000 KG
Gross Weight 207,000 KG

AD_RP300 ASSA ABLOY RP300 1.000 ST 3,376.00 3,376.00
Serien-Nr. 2610017737

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370
Commodity code: 39252000	
Country of origin: CZ	

Dimension packing 1 LxWxH	**3100x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**187,000 KG**
Gross Weight	**207,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**

Serien-Nr. 2610017738

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Dimension packing 2 LxWxH 800X600X370
Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH 3100x620x430
Dimension packing 2 LxWxH 800x600x530
Net Weight 187,000 KG
Gross Weight 207,000 KG

AD_RP300 ASSA ABLOY RP300 1.000 ST 3,376.00 3,376.00
Serien-Nr. 2610017739

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Country of origin: CZ

Dimension packing 1 LxWxH **3100x530x430**
Dimension packing 2 LxWxH **800x600x530**
Net Weight **187,000 KG**
Gross Weight **207,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**
Serien-Nr. 2610017740

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Dimension packing 1 LxWxH **3000x530x430**
Dimension packing 2 LxWxH **800x600x530**
Net Weight **177,000 KG**
Gross Weight **197,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**
Serien-Nr. 2610017741

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH **3000x530x430**
Dimension packing 2 LxWxH **800x600x530**

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Net Weight **177,000 KG**
Gross Weight **197,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**
Serien-Nr. 2610017742

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH **3000x530x430**
Dimension packing 2 LxWxH **800x600x530**
Net Weight **177,000 KG**
Gross Weight **197,000 KG**

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**

Serien-Nr. 2610017743

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3000x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**177,000 KG**
Gross Weight	**197,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Serien-Nr. 2610017744

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3100x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**187,000 KG**
Gross Weight	**207,000 KG**

AD_RP300	**ASSA ABLOY RP300**	**1.000**	**ST**	**3,376.00**	**3,376.00**

Serien-Nr. 2610017745

Door type	High-speed roller door RapidProtect 300

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3100x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**187,000 KG**
Gross Weight	**207,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**

Serien-Nr. 2610017746

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down mounted on the control box
Max. Opening Speed	1,0 m/s
Max. Closing Speed	1,0 m/s
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Original - extremely stiff and tear resistant polyester monofilament fabric
Door curtain colour	Blue, similar to RAL 5002
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1 100 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
Control box material	Painted steel
Power supply	400 V, 3-phase
Frequency	50 Hz
Motor cable length	3 000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	3000X480X400
Dimension packing 2 LxWxH	800X600X370

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**3000x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**177,000 KG**
Gross Weight	**197,000 KG**

AD_RP300 **ASSA ABLOY RP300** **1.000** **ST** **3,376.00** **3,376.00**

Serien-Nr. 2610017747

Door type	High-speed roller door RapidProtect 300
Daylight width	1 500 mm
Daylight height	2 500 mm
Side frame extension X-Level	0 mm
Door control system	ACS50 electronic control system with push buttons up/stop/down

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye