Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door of HS-Series Power Drive

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your ASSA ABLOY High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

HS-Series Power Drive

Product group	Description	100.000 cycles or 2 years	100.000 cycles or 3 years	200.000 cycles or 3 years	300.000 cycles or 3 years	300.000 cycles or 6 years	400.000 cycles
Actuators	Photocell Transmitter/Receiver						●
Counterbalancing	Belts for counterweight				●		
Curtain tension	Springs fixed to C-profile			●			
Curtain	Lateral retaining straps with teeth			●			
Top roll	Gear block incl. Plastic gear wheel				●		
	Bearings drum					●	
Bottom profile	Wireless safety edge		●				
Sliding/Guiding	Guides A and B			●			
	Wearing guide 150 mm	●					
	Inner guide methylene			●			
	Reintroduction block				●		
Drive unit	Gear unit				●		
	Motor						●
Encoder	Encoder						●

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

© ASSA ABLOY Entrance Systems AB PL.MAN/Power Drive/DEU.EN-1.1/1711 / 64 100 762 Technical data subject to change without notice

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization