**Technical Specification of NIHVA Dock Leveller**

**Client: Ducon Consultants**

**Project: Ahmedabad**

**Date: 26.04.2019**

| Sr. No. | Description | Specifications |
|---|---|---|
| 1 | Capacity | 2 Ton |
| 2 | **Platform Size (W x L)** | **2030 mm x 2720 mm** |
| 3 | **Quantity** | **1 No.** |
| 4 | Dock operation mode | AC power pack hydraulically operated |
| 5 | Lip operation mode | Hydraulic |
| 6 | Operation control | Through panel |
| 7 | Loading platform height from road | 1200 mm (Min) |
| 8 | Travel above & below dock level | (+) 300 / (-) 200 mm |
| 9 | Lip size (W x L ) | 2030 x 400 mm |
| 10 | Shut Height | 550 mm |
| 11 | Working length | 3120 mm |
| 12 | Overall length | 2030mm x 2720mm + Lip Length (400mm ) |
| 13 | Maximum slope can be achieved | 10% |
| 14 | Clear Pit dimensions (W x L x D) | (W) 2080mm x (L) 2770 mm x (D) 560 mm |
| 15 | Hydraulic power pack | Standard |
| 16 | Driver type | Direct by electric Motor |
| 17 | Motor Ratings | 1 H.P Motor |
| 18 | Pump design flow | 2.5 LPM |
| 19 | Pump pressure | 120 bar Operating 200 bar Max. |
| 20 | Safety valve set pressure | 120 Kg/cm² |
| 21 | Pump Type | Gear |
| 22 | Volume of oil receiver | 7 Lit |
| 23 | No Of Deck cylinder | 2 No |
| 24 | Lip Cylinder | 1 No |
| 25 | Dock Bumper | Included |