NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

GS PEB & Civil Works Pvt. Ltd
Jai Ganesh Vision Complex, B-Wing,
2nd Floor, Office No.264,265,266,
Ganga Nagar, Akurdi, Pimpri-Chinchwad, Maharashtra 411035

Date : 07.04.2020
Quote NO : SQT/19-20/2522
Kind Attn : Mr Prakash Patil
Email Id : prakash.patil@groupsurya.in
Contact No: 7507778262

Subject : Quotation for Sectional Door, Rolling shutter, Edge Dock Leveller, Gate & Boom Barrier (Project Location - Chakan)

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions.
This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2,3
C.	General Conditions	4
D.	Terms & Condtions	4

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Height (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	Motorised Sectional Door	2400	3000	65	2,56,000	1,66,40,000	20,000	13,00,000
2	MS Gear Operated Rolling Shutter	2400	3000	25	65,000	16,25,000	20,000	5,00,000
3	MS Motorized Rolling Shutter	4000	5000	3	1,60,000	4,80,000	20,000	60,000
4	ELECTRO HYDRAULIC Edge Dock Leveller	700	2000	26	1,38,000	35,88,000	12,000	3,12,000
5	Motorized Single Leaf Sliding Gate	6000	3000	4	3,85,000	15,40,000	20,000	80,000
6	Automatic Boom Barrier	6000		4	1,25,000	5,00,000	15,000	60,000
			Total			**2,43,73,000**		**23,12,000**
7	P&F Charges			3%		7,31,190		
	Total Without Taxes					2,51,04,190		23,12,000
	GST Extra @ 18%			18%		45,18,754.20		4,16,160
	Total With Taxes					**2,96,22,944**		**27,28,160**
8	Transportation Charges					Extra at Actual		
9	Unloading Charges @ Site					In Client Scope		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

Technical Specification -Sectional Door

Sr. No	Description	Specification
1	Model No	ASSA ABLOY OH1042P
2	Vision Windows	2 Nos at central panel
3	Opening Direction & Mounting	Standard
4	Opening/Closing Speed	CDM9 0,28 m/s
5	Door Material	GI Steel
6	Panel Thickness	42 mm Square Grid, steel sheet
7	Filling	CFC-free polyurethane
8	Panel colour	RAL 9002 Grey White Powder coated
9	Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
10	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
11	Water Penetration	EN 12425 class 3
12	Air Permealibity	EN12426 class 3
13	Wind Load	EN21424 class 3
14	Thermal Transittance	EN 12428 1.10W /m2K
15	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
16	Door saftey	Doors equiped with spring break device
17	Incase of Power failuer	Doors to be equiped with quick release fuction
18	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
19	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
20	Emergency Operation	by Disengagement rope manual
21	Operating Switch	Up/Down Keypad + stopbutton
22	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
23	Environmental Green Product Declaration Certification	As per ISO 14025 and EN 15804

Technical Specification -Rolling Shutter

Sr .No.	Specification	MS Geared / Motorized Rolling Shutter
1	Description:	Geared / Motorised Rolling Shutter with MS Laths with thickness of 1 mm.
2	Mounting Location area	Inside area / Outside area
3	Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side
4	Curtain Panel	The panel made of 1.0mm thick MS.
5	Curtain panel size	75mm wide
6	Curtain Profile	Curved
7	Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
9	Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	Hood Cover	Made of GI Sheet Thickness 1.2 mm GF mm with 25x25x3mm angle stiffener
12	Surface finish	PU paint or Powder coated
13	Drive Unit & Mounting Type	1) Geared - Gear Assembly 2) Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54

NIHVA TECHNOLOGIES PVT. LTD.

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

Technical Specification - Sliding Gate

SN	Specification	AUTOMATIC SINGLE LEAF SLIDING GATE	
1	**Door type**	**Motorized Sliding Gate**	
2	**Clear Opening gate dimension**	(W) 6000 x (H) 3000…in mm	
3	**Opening Direction**	**Horizontal - from left to right or reverse**	
4	**Mounting Location area**	Inside area	
5	**Design Pattern**	Standard Tubular Design Pattern	
6	**Outer Frame Tube Sizes**	72 x 72 x 3.2mm MS SQ. TUBE	
7	**INNEAR TUBE**	38x38x2.6mm/40x40x2.6 MS SQ. TUBE	
8	**Gap Between Tubes**	125mm	
9	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams	
10	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)	
11	**Guide Rollers supporter during Gate movement**	Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate	
12	**Painting**	2 Coats of EPOXY polyamide based enamel finish of approved colour	
13	**El motor make**	BFT – Italy (100% imported)	
14	**Emergency Operation**	Manual after turn the switch	
15	**Operating Switch**	Push Button from inside	
16	**Safety**	Photocells, Flashing Light	
17	**Metal Rack**	zinc plated metal rack	

Boom Barrier

Sr. No.	Description	Specifications
1	Size	6 Mtr
2	Model No	Michealangelo 60
3	MICHELANGELO BT A Barrier	Opening Time- 4S
4	Motor Power Supply	24V
5	Type of limit Switch	Electronic
6	Frequency of Use	Continous Use
7	Protection Rating	IP24
8	Operated	Push Button Pedant

Electro Hydraulic Edge Dock leveler

Sr. No.	Description	Specifications
1	LIP SIZE	400W X 2000L
2	LIFT ABOVE	100 MM
3	LIFT BELOW	100 MM
4	OPERATION	4 PUSH BUTTOM WITH INCHING MODE
5	POWER PACK	1HP, 415 VOLT 3Phase

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description	Remark
1	Secured and fully covered Store area to keep the material	In Client Scope
2	Scaffolding/Hydra/Crane/Forklift Etc - Required for Installation at Site	In Client Scope
3	Electrical Supply on the site single phase/three phase points at different places.	In Client Scope
4	Any civil / masonry/structural work required	In Client Scope
5	All structure support required	In Client Scope
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	In Client Scope
7	Conduits, Cables required	In Client Scope

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 6 - 7 weeks for Rolling Shutter, Sliding Gate, Dock Leveller and Boom Barrier and 14-16 weeks for Sectional Door from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

Please feel free to Contact **Mr. Ravindra Kharat on 7410169333** For any further Clarification /Information in this Concern.

With Best Regards
Varsha
8551091333
For NIHVA Technologies Pvt Ltd