TECHNICAL SPECIFICATION

A. Supply of Electrical Operated Hydraulic Rise Scissor as per following specification :

Item Number	Item Title	Item Description	Unit of Measure
1	Electrical Operated Hydraulic Rise Scissor	Electrical Operated Hydraulic Rise Scissor Lift of 500 kg capacity with manual towable arrangement.	Pieces

B. Technical Specification

Electrical Operated Hydraulic Rise Scissor Lift with Manual Toeing

1. Capacity : 500 Kgs
2. Maximum Platform Lift Height From Ground (mm) : 5000
3. Minimum Platform Size (mm) : 1000 (Width) X 1800 (Length)
4. Lifting Power (Electrical) : 3 phase 415 VAC
5. Lifting Time : Specified by Manufacturer
6. Total Weight : Specified by Manufacturer
7. Railing Height (mm) : 1000
8. Toe guard Height (mm) : 150
9. Maximum Wheel width (mm) : 60
10. Power supply cable length (meter) : 15

Specification of hydraulic oil : VG-68

Features :

1. Manual Toeing Handle system.
2. Four numbers of Solid rubber wheels with 2 fixed and 2 swivel castors.
3. Anti skid floor on platform.
4. The control panels must available on the scissor lift body.
5. Push button pendent control for up and down movement on the platform.
6. Removable guardrails.
7. Limit switch for auto shut off.
8. Mechanical stoppers.
9. Hose burst safety valve to prevent equipment to come down abruptly in case of hose failure.
10. Manual solenoid release at the bottom to release hydraulic pressure and bring platform to home position in case of power failure.
11. Ladder requirement to reach platform.
12. Greasing Points to be provided at all pivot points with grease nipples.