High Speed Rolling Shutter - (ALU Speed Door)

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super-fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spare parts, minimum cost
- Patented rubber drive method

Sr. No	Description	Specifications
1	Use	Internal / External Door
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of
3	Opening speed	upto 1.5 m/s
4	Closing speed	0.7 m/s
5	Security Features	EN 13241-1 Standard
6	Resistance to wind	class 4
7	Curtain	Aluminum 19.0 mm
8	Door Leaf Material /	Polyurethane filled RAL 9006 aluminum lamella
9	Hood Cover	Included
10	Motor Cover	Included
11	Guide Material /	Aluminum Anodized, Painting in any RAL9006 lamella color
12	Operator & Control	Brakelli
13	Connecting Voltage	220V, 1Ph, N
14	Open-Stop-Close	Standard
15	Protection Category	IP 54
16	Power Consumption	1.5 kw Motor
17	Emergency Off Button	Standard
18	Closing Zone	Optical Safety edge, bottom edge sensor
19	External Route	Photocell
20	Emergency Opening	Crank Handle
21	Door Area Monitoring	Radar and Loop detector on both side
22	Window	one row of window