

Abbrevation's:
WOW-Wall Opening Width
WOH-Wall Opening Height
UC-Under Cut
FFL-Finished Floor Level

ASSESORIES DETALES

(a) HINGES: Stanley


(b) LOCK : 1. Size1113x2380mm- Panic Bar - Briton
External trim - Dorma
2. Size1113x2415mm - Panic Bar - Stanley
External trim - Stanley

(c) DOOR CLOSER - RYOBI


(d) GLASS : 1No. Clear fire Vision Glass size 200x300mm.
Glass Thickness - 5mm

Color : Soft Gray
Shutter thickness : 47 mm
Frame Sheet thick : 1.20mm
Shutter sheet thick : 0.80mm
Fixing : On Soliid Brick plasterd wall with Anchors


NOTE:- *All Dimensions are in mm.
*Tolerance:-All Linear Dimensions ±3mm,Others ±0.5mm.
*The Drawing Is For Location of Hardware only. Drawing Does Not Represent The Hardware For More Clarity, Please Go Through Hardware Broucher.



Inside Elevation



Top View



Detail view of Section A

FIRE DOOR SIZES		
WOW	WOH	QUANTITY
1113	2380	4
1113	2415	4

This drawing & designing is the property of NIHVA TECHNOLOGIES. Not be sold or copy to any other concern.

Fire Door

CLIENT APPROVAL

ALL DIMENSION ARE IN mm

	NAME	DATE	SIGN.
DRAWN	ANIL KHOT	07/03/16	
CHECK	ANIL	07/03/16	
REV.	00		
APPRD.			
MFG			

NIHVA TECHNOLOGIES PVT. LTD.

NIHVA TECHNOLOGY PVT. LTD. PUNE
Tel : 020 66304033
Email:- info@nihva.com
Website:-www.nihva.com

CLIENT - INDOSPACE
PROJECT - APM BUILDING
SITE - CHAKAN
DWG. NO. - NIHVA/15-16/237
SCALE: 01 | WT: | SHEET: 01 OF 01
If any queries contact : projects@nihva.com