Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

Enhance the durability of your High Performance Door Albany RR392

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR392

Product group	Description	50.000 cycles	150.000 cycles	250.000 cycles	300.000 cycles	500.000 cycles	1.000.000 cycles	5 years	10 years	wear / tear related
Actuators	Photocell transm./rec. with bracket								●	
Cable chain	Cable chain, complete with cable and bracket					●				
Counterbalancing	Rope for counter balance, contactor control	●								
	Rope pulley, contactor control	●								
	Rope for counter balance, frequency converter		●							
	Rope pulley, frequency converter		●							
Curtain tension	Deflection spring			●						
	Rope for curtain tension			●						
	Rope pulley			●						
	Spring d=5mm			●						
Curtain	Curtain									●
	Set of wind tabs					●				
	Curtain including top roll									●
Top roll	Flange bearing					●				
	Top roll					●				
Bottom profile	Rubber profile with contact strip							●		
	Spiral cable with cable gland				●					
Crash	Proximity switch								●	
	Sliding part outside for crash-version									●
Drive unit	Drive unit - contactor control					●				
	Drive unit - frequency converter						●			
	Limit switch								●	
	Microswitch							●		
Chain drive	Chain wheel - contactor control					●				
	Chain wheel - frequency converter						●			
	Roller chain complete					●				
	Shaft with drive pinion					●				
Brake	Brake - contactor control					●				
	Brake - frequency converter						●			
Encoder	Double Proximity switch								●	
	Encoder 50 pulses, only electronic part								●	
Damper	Vibration absorber					●				

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year

Technical data subject to change without notice

© ASSA ABLOY Entrance Systems AB PL.MAN/RR392/DEU.EN-1.1/1504 / 64 100 481

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization