NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

Project Name: CN IFFCO Ludhiana


Technical Specifications

Sr. No	Product Name	Model No	Make	Pages
1	Sectional Door	OH1082P	ASSA ABLOY	1
2	Sectional Door	OH1042P	ASSA ABLOY	2
3	High Speed Door Internal Application	RR300+ Alu	ASSA ABLOY	3
4	High Speed Door External Application	HS8010P	ASSA ABLOY	4
5	Motorised Rolling Shutter	-	NIHVA	5
6	Sliding Doors		ASSA ABLOY	5

1) Sectional Door



OH1082P




Vertical Lift
(head room > 2 x height)

Sr. No	Description	Specification
1	Vision Windows	2 Nos at central panel
2	Opening Direction & Mounting	Vertical
3	Opening/Closing Speed	CDM9 0,28 m/s
4	Door Material	GI Steel
5	Panel Thickness	82 mm thick Diamond grid
6	Filling	PIR, flame retardant
7	Panel colour	RAL 9002 Grey White Powder coated
8	Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
9	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
10	Water Penetration	EN 12425 class 3
11	Air Permealibity	EN12426 class 3
12	Wind Load	EN21424 class 3
13	Thermal Transittance	EN 12428 1.10W /m2K
14	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
15	Door saftey	Doors equiped with spring break device
16	Incase of Power failuer	Doors to be equiped with quick release fuction
17	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
18	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
19	Emergency Operation	by Disengagement rope manual
20	Operating Switch	Up/Down Keypad + stopbutton
21	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.



OH1042P



Vertical Lift
(head room > 2 x height)

Sr. No	Description	Specification
1	Vision Windows	2 Nos at central panel
2	Opening Direction & Mounting	Vertical
3	Opening/Closing Speed	CDM9 0,28 m/s
4	Door Material	GI Steel
5	Panel Thickness	42 mm Square Grid, steel sheet
6	Filling	CFC-free polyurethane
7	Panel colour	RAL 9002 Grey White Powder coated
8	Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
9	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
10	Water Penetration	EN 12425 class 3
11	Air Permealibity	EN12426 class 3
12	Wind Load	EN21424 class 3
13	Thermal Transittance	EN 12428 1.10W /m2K
14	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
15	Door saftey	Doors equiped with spring break device
16	Incase of Power failuer	Doors to be equiped with quick release fuction
17	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
18	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
19	Emergency Operation	by Disengagement rope manual
20	Operating Switch	Up/Down Keypad + stopbutton
21	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
22	Environmental Green Product Declaration Certification	As per ISO 14025 and EN 15804

A) High Speed Door **Internal Application**





Sr. No	Description	Specifications
1	Description	Flexible High Performance Door, opening in vertical direction for interior use in wind-protected areas
2	Side frames	Made of aluminum
3	Wind resistance	Class 1 (EN 12424)
4	Bottom profile	Anodized aluminum
5	Drive unit	Hollow shaft gear motor with operating current brake
6	Protection	IP 55
7	Control system	MCC Vector Control - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit. Max. Opening Speed 2.2m/s Max. Closing Speed 0.9 m/s
8	Supply voltage	3L(N)PE/380/400/415/440/480V;50/60Hz
9	Safety devices	• Electrical safety contact edge • Evaluation via integrated cable chain • Door line photocell in the side frames • Drop down protection by integrated balancing system
10	Manual activation	By releasing the brake at ground level. Depending on width/height ratio the door opens up to max. 2.0 m

Optional Accessories

Sr. No	Description	Specifications
1	Radar Sensor 	An infrared sensor above the door detects an object (person, vehicle) within a specified distance from the door and opens the door automatically. This is an ideal solution for frequent vehicle or personal traffic.
2	External push button box 	Used for opening & closing of door. Installed on the inside or outside wall beside the door
3	Pull-rope switch 	Pulling the rope opens the door. Installed on the inside construction above the door A pull-rope switch above the door opening can be operated from e.g. a forklift truck.

A) High Speed Door **External Application**



Sr. No	Description	Specifications
1	Door curtain	The HS8010P is designed for exterior openings in medium-sized heavy-duty operations.
2	Self-supporting side frames	Made of galvanized steel
3	Wind resistance	class 4 (300 Pa (N/m2))
6	Water penetration	class 2 (50 Pa (N/m2))
7	Air Permeability	class 1 (24 m3/m2/h at 50 Pa)
9	Temperature Working Range	-20 to +40 Degree
10	Bottom profile	Flexible Bottom Edge including wireless edge activator
11	Degree of Protection	Operator IP 65 & Control Unit IP54
12	Safety devices	• Photocell in Side Columns • Break away and self-repair function
14	Opening and Closing Speed	(open/close) up to max. 2.4/1.2 m/s
15	Supply voltage	400V 3-phase 1,5 kW 3 x 16A

Optional Accessories

Sr. No	Description	Specifications
1	Radar Sensor 	An infrared sensor above the door detects an object (person, vehicle) within a specified distance from the door and opens the door automatically. This is an ideal solution for frequent vehicle or personal traffic.
2	External push button box 	Used for opening & closing of door. Installed on the inside or outside wall beside the door
3	Pull-rope switch 	Pulling the rope opens the door. Installed on the inside construction above the door A pull-rope switch above the door opening can be operated from e.g. a forklift truck.

G) Motorised Rolling Shutter





Sr. No	Description	Specification
1	Rolling Shutter	Motorised Rolling Shutter with Galvanised Steel Laths with thickness of 1 mm.
2	Mounting Location area	Inside area / Outside area
3	Curtain Panel	The panel made of 1.0mm thick GI steel
4	Curtain panel size	75mm wide
5	Curtain Profile	Curved
6	Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
7	Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
8	Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	Hood Cover	Made of GI Sheet Thickness 0.9 mm GI mm with 25x25x3mm angle stiffener
11	Surface finish	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer
12	Drive Unit & Mounting Type	Indirect Drive - Motor

I) Sliding Glass Doors



Sr. No	Description	Specification
1	Power Supply	100-240 VAC/50/60Hz
2	Power Consumption	Max. 250W
3	Opening / Closing – Speed	1.7 m/s
4	Hold Open time	0 – 60sec
5	Ambient Temperature	-20 Degree to +50 Degree
6	Opening time	0.2 Seconds
7	Passage Speed	30 peoples/minute
8	Glass	12 mm thick Toughened Glass
10	Sensor	Motion Sensor for Auto Open and Close