	Nihva	AU REMARK
Description	**DESCRIPTION**	
Size of rolling shutter	Clear opening width X Clear opening Height 4000 x 4000, 3000 x 2450, 2450 X 3000, 2450 X 2450	ok. RS3 & RS2a are internal shutters. Rs5-1 no is also internal shutters. If required these can be designed as internal shutter for better pricing.
Shutter description	M.S./ GI slat motorised rolling shutter	ok
Total moving weight of shutter	17 to 20 kg/m^2	
Mounting Location area	can be mounted inside / outside as per client requirement	Check missing details from
Mounting Surface	can be mounted on brick wall , concrete or metal frame	ok
Curtain profile	Curved slat	ok
Curtain panel size & thickness	75mm wide , CRC M.S/ G.I Steel Slats available in 1.0 mm & 1.2 mm thickness	ok
Curtain Panel Material	M.S. / GI	ok
Bottom profile size, thickness & material	Mild Steel Bottom Plate with Angle Stiffener Rubber bottom seal as optional	ok , part of standard Design
Side guide profile- dimention & thickness	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick as per size of rolling shutter	**Need confirmation whether Wind load (50m/Sec) is considered for all external shutters ? If not , need to consider same.**
Roller Shaft- diameter & thickness	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per size of rolling shutter	Shaft Diameter by Gatemann seems too small.
Opening & closing speed	0.05 to 1 metre/sec	Nihva are providing better speeds, mean better motor capacity.
Hood Cover- material & thickness	Made of GI Sheet 0.9 mm thickness	ok
Motor cover-material & thickness	Made of GI Sheet 0.9 mm thickness	ok
Surface finish	Painting /Powder coated as per approved RAL shade	PU painted Shutters will be preffered.
Drive Unit & Mounting Type	Imported make Indirect /Direct Connecting Drive selection made depending on the space opening availability, no of operations subjected etc. Drive with integral breaking system with Long life expectancy	ok. Direct / Indirect type selection is driven by No of Operations.
Motar DETAILS/capacity	depends as per size of rolling shutter	ok
Safety device	Optional Safety Photocell Optional safety catch motor	Both side Photocell for each shutter is prefereable. To be checked with Gurit requirement.
Control type	Opearted by push buttons	Key type locking system , with Three station push button with deadman control which allows allows a shutter to move as long as the operating button is being pressed is preffered.
Push Button	for up / down operation & stop operation	
Emergency Operation	Manual operation by Hand chain or hand crank	ok
No of operations per day	depends upon drive selection	Check Operational Frequency with Gurit. However, for docking shutters, operations less than 15 is not advisable.
Locking arrangement	Bottom profile provided with locking plate arrangement	Genrally locking is done through key mechanisam so this will not be decisive critera.