ASSA ABLOY

RECHNUNG/INVOICE

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**ASSA ABLOY, Rechnung/Invoice** 90759062 **Datum/Date** 2019-01-30 **Lieferschein-Nr./delivery note** 80401116 **Auftrags-Nr./Order No.** 30719988 **Referenz/Reference** Mr. Patil

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**	
1059669	Nadine Gundelach	Forwarder (W)	Sea freight
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**	**Lieferdatum/Delivery date**
	NVA-411	FCA Hemau, Germany	2019-01-30

Lieferadresse/Delivery address	**Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**	**Fälligkeit/Due date**
NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	1059669	Due Net 90	2019-04-30

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
	AD_RR300_PLUS	**ASSA ABLOY RR300 Plus**	**1.000**	**ST**	**3,650.00**	**3,650.00**

Serien-Nr. 1300011061

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	QTY	Unit	Price/Unit	Price

Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580
Commodity code: 39252000	
Country of origin: CZ	

Dimension packing 1 LxWxH	**4500x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**210,000 KG**
Gross Weight	**230,000 KG**

AD_RR300_PLUS ASSA ABLOY RR300 Plus 1.000 ST 3,650.00 3,650.00

Serien-Nr. 1300011062

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	QTY	Unit	Price/Unit	Price

Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4500x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**210,000 KG**
Gross Weight	**230,000 KG**

AD_RR300_PLUS ASSA ABLOY RR300 Plus 1.000 ST 3,650.00 3,650.00

Serien-Nr. 1300011063

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos. item	Produkt Product	Beschreibung Description	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

	open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4500x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**210,000 KG**
Gross Weight	**230,000 KG**

AD_RR300_PLUS ASSA ABLOY RR300 Plus 1.000 ST 3,650.00 3,650.00

Serien-Nr. 1300011064

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up to

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	QTY	Unit	Price/Unit	Price

	75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4500x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**210,000 KG**
Gross Weight	**230,000 KG**

AD_RR300_PLUS ASSA ABLOY RR300 Plus 1.000 ST 3,650.00 3,650.00

Serien-Nr. 1300011065

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.
Egress height	When the brake is released doors up to daylight height of 2300mm open up

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	QTY	Unit	Price/Unit	Price

	to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4500x480x400**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**226,000 KG**
Gross Weight	**246,000 KG**

AD_RR300_PLUS **ASSA ABLOY RR300 Plus** **1.000** **ST** **3,900.00** **3,900.00**

Serien-Nr. 1300011066

Door type	High speed roller door RapidRoll 300 Plus
Daylight width	4 000 mm
Daylight height	4 000 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,2 m/s
Max. Closing Speed	0,9 m/s
Control box position	Mounted next to the drive unit
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Bottom plates included
Bottom profile	Aluminium
Safety contact edge	Electrical safety edge at the bottom profile
Connection for safety edge	With cable chain, integrated in side frame
Photocell	With photocell
Manual egress (brake release)	Release handle with encapsulated cable on the front side
Brake type	Door equipped with fail safe brake. When the brake is released by the door opens partially supported by the balancing system.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

Pos.	Produkt	Beschreibung	Anzahl	Einheit	Preis/Einh.	Preis
item	Product	Description	QTY	Unit	Price/Unit	Price

Egress height	When the brake is released doors up to daylight height of 2300mm open up to 75% of the daylight height. Doors with daylight height > 2300mm open approx. 2m
Top roll material	Aluminum
Door curtain	PVC material - transparent with vertical coloured stripes
Door curtain colour	Blue, similar to RAL 5002
Curtain tensioning system	With curtain tensioning system
MCC type	Standard version
MCC-display position	Wall mounted
MCC display type	Combibox with display and mainswitch
Material combibox	Plastic
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Mains connection cable length	7 000 mm
Combibox cable length	7 000 mm
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Heat treated pallet
Warranty	1 Year
Dimension packing 1 LxWxH	4500X480X400
Dimension packing 2 LxWxH	800X600X580

Commodity code: 39252000
Country of origin: CZ

Dimension packing 1 LxWxH	**4500x530x430**
Dimension packing 2 LxWxH	**800x600x530**
Net Weight	**230,000 KG**
Gross Weight	**250,000 KG**

Warenwert/Value of goods		**22,150.00**
Mwst/VAT	**0.00 %**	**0.00**
Summe/Total	**EUR**	**22,150.00**

Goods delivered outside the European Community are tax free according to § 4 No. 1a UStG

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye

ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: DE 813 313 618
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Register court Paderborn: HR B 61 06

Management:
Mogens Jensen
Per Hansson
Christopher Norbye