NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Shapoorji Pallonji & Company Pvt Ltd
Bengaluru

Date : 17.10.2019
Quote NO : SQT/19-20/2196R
Kind Attn : Mr. M.S.Gururaj,
Email Id : GURURAJ.RAO@shapoorji.com
Contact No: 9632184618

Subject : Quotation forRolling Shutters, High Speed Rollup Doors, OH Sectional Door and Gates. (Project - Biocon's Bulk Drug Manufacturing Facility at Vishakapatnam)

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions.
This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2
C.	General Conditions	3
D.	Terms & Condtions	4

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Height (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	MS Motorized Rolling Shutter	3000	4200	1	1,10,000	1,10,000	20,000	20,000
2	MS Motorized Rolling Shutter	3000	3500	1	96,000	96,000	20,000	20,000
3	MS Motorized Rolling Shutter	2500	3000	10	79,000	7,90,000	20,000	2,00,000
4	MS Motorized Rolling Shutter	3000	3500	1	96,000	96,000	20,000	20,000
5	MS Motorized Rolling Shutter	3000	3000	1	89,000	89,000	20,000	20,000
6	MS Motorized Rolling Shutter	2700	4200	3	1,00,000	3,00,000	20,000	60,000
7	MS Motorized Rolling Shutter	2000	4200	1	65,000	65,000	20,000	20,000
8	Fire Rated Rolling Shutter	3000	4200	1	2,46,000	2,46,000	20,000	20,000
9	Fire Rated Rolling Shutter	2000	3500	1	2,12,000	2,12,000	20,000	20,000
10	Fire Rated Rolling Shutter	2000	4200	1	1,82,000	1,82,000	20,000	20,000
11	Fire Rated Rolling Shutter	2700	4200	1	2,13,000	2,13,000	20,000	20,000
12	Gear Operated Rolling Shutter	3000	3500	3	69,000	2,07,000	20,000	60,000
13	Gear Operated Rolling Shutter	2500	3000	2	56,000	1,12,000	20,000	40,000
14	Gear Operated Rolling Shutter	3000	3000	2	64,000	1,28,000	20,000	40,000
15	Gear Operated Rolling Shutter	3000	4000	7	79,000	5,53,000	20,000	1,40,000
16	Gear Operated Rolling Shutter	3500	4000	4	89,000	3,56,000	20,000	80,000
17	Gear Operated Rolling Shutter	4000	4000	8	99,000	7,92,000	20,000	1,60,000
18	Gear Operated Rolling Shutter	4000	5000	1	1,19,000	1,19,000	20,000	20,000
19	Gear Operated Rolling Shutter	5000	5000	1	1,44,000	1,44,000	20,000	20,000
20	High Speed Door HS9020G	2500	3000	2	5,17,000	10,34,000	20,000	40,000
21	High Speed Door HS9020G	2500	4000	1	5,82,000	5,82,000	20,000	20,000
22	High Speed Door HS9020G	3000	3000	1	5,62,000	5,62,000	20,000	20,000
23	High Speed Door HS9020G	3000	4000	1	6,39,000	6,39,000	20,000	20,000
24	Retractable Dock Shelter	2500	3000	1	1,50,000	1,50,000	20,000	20,000
25	Sectional Door	2500	3200	1	2,40,000	2,40,000	20,000	20,000
26	Wicket Gate	1200	1500	1	50,000	50,000	20,000	20,000
27	Wicket Gate	1000	1500	1	45,000	45,000	20,000	20,000
28	Telescopic Sliding Gate (Motorised)	16000	1500	1	8,26,000	8,26,000	20,000	20,000
29	Telescopic Sliding Gate (Motorised)	9000	1500	1	5,38,000	5,38,000	20,000	20,000
30	Sliding Gate (Motorised)	3100	1500	1	1,74,000	1,74,000	20,000	20,000
				Total		**96,50,000**		**4,40,000**
31	P&F Charges			3%		2,89,500		
	Total Without Taxes					99,39,500		4,40,000
	GST Extra @ 18%			18%		17,89,110.00		79,200
	Total With Taxes					**1,17,28,610**		**5,19,200**
32	Transportation Charges					In Client Scope		
33	Unloading Charges @ Site					In Client Scope		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Sr .No.	Specification	Sectional Door -Crawford - NIHVA Assaabloy	
1	Door type	1042P	
2	Clear Opening dimension	(W)2500 x (H) 3200 mm	
3	Opening Direction	90 Degree	
4	Type of Mounting	High Lift	
5	Door produced Based on which certificatio	Doors produced according to ISO 9000 or ISO 14000 certified	
6	Opening/Closing Speed	0.25 m/s	
7	**Door Material**	GI Steel with PUF inside	
8	Panel Thickness	42mm	
9	Panel colour	RAL 9002 Powder coated	
10	External surface of the panel	diamond grid design with a glossy finish at the section joints.	
11	inside surface of the panel	Monolithic surface on the inside of the door	
12	Broken cold bridge	Section joints with broken cold bridges	
13	Door sealent	All door sealants made of EPDM rubber.	
14	All Panel height	All panels should be 545mm high	
15	Panel Inside insulation metrial	Insulation material to be CFC free polyuretane foam.	
16	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.	
17	Steel component Material	All steel components to be electro galvanized	
18	Hinge Material	Glass fibre reinforced Polyamide	
19	Panel Thickness	42 mm	
20	Spring Material surface finish	Powder coated	
21	Water Penetration	EN 12425	class 3
22	Air Permealibity	EN12426	class 2
23	Wind Load	EN21424	class 3
24	Thermal Transittance	EN 12428 1.10W /m2K	
25	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber	
26	Door saftey device 1	Doors equiped with spring break device	
27	Door saftey device 2	Door equiped with pneumatic safety edge	
28	Door saftey 3	Having hinges flush with the inside door surface is a safety feature that eliminates the risk of things or people getting caught by parts protuding from a moving door	
29	Incase of Power failuer	One can operate the Door manually	
30	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W	
31	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft	
32	Emergency Operation	by Disengagement rope manual	
33	Operating Switch	Up/Down Keypad + stopbutton	
34	Environmental Green Product Declaration Certification	as per ISO 14025 and EN 15804	

Sr .No.	Specification	MS Motorized Rolling Shutter
1	**Description:**	Motorised Rolling Shutter with MS Laths with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete /Steel & Side
4	**Curtain Panel**	The panel made of 1.0mm thick MS.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 1.2 mm GF mm with 25x25x3mm angle stiffener
12	**Surface finish**	PU paint or Powder coated
13	**Drive Unit & Mounting Type**	Electric Motor -Indirect Mounting - Sprocket chain arrangement – IP54 Protection

Sr .No.	Specification	MS Gear Operated Rolling Shutter
1	**Description:**	Gear Operated Rolling Shutter with MS Laths with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete
4	**Curtain Panel**	The panel made of 1.0mm thick MS.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
10	**Hood Cover**	Made of GI Sheet Thickness 1.2 mm GF mm with 25x25x3mm angle stiffener
11	**Surface finish**	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide-based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer
12	**Operation**	Gear Assembly.

Sr. No	Specification	High Speed Door ASSAABLOY (Albany) HS9020G (100% Imported products from Europe)
1	**Operating speed:**	Opening: up to 2 m/s , closing: 0,5 m/s .The fast opening and closing speed improves your traffic flow, provides employee comfort, and saves energy.
2	**Wind load resistance**	Class 1 (300 N/m2), maximum wind load while closing 50 N/m2.
3	**Techncial details :**	a. The soft bottom edge has no rigid parts, it moulds around any obstruction to prevent injury or damage.
		b. When an object hits the door, the fabric curtain absorbs the impact and releases itself from its side guides without causing damage or being damaged itself.
		c. Vision Window - One row of 400 mm height.

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description	Remark
1	Secured and fully covered Store area to keep the material	In Client Scope
2	Scaffolding/Hydra/Crane/Forklift Etc - Required for Installation at Site	In Client Scope
3	Electrical Supply on the site single phase/three phase points at different places.	In Client Scope
4	Any civil / masonry/structural work required	In Client Scope
5	All structure support required	In Client Scope
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	In Client Scope
7	Conduits, Cables required	In Client Scope

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 9 - 10 weeks for High Speed Door, Sectional Door and Fire rated Rolling Shutter and 4-5 weeks for Rolling Shutter and Sliding Gates from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% Advance along with Confirmed Purchase Order & Balance before dispatch.

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

Please feel free to Contact **Mr. Swapnil Kulat on 7219207333** For any further Clarification /Information in this Concern.

With Best Regards
Ulka Auti
7219206333
For NIHVA Technologies Pvt Ltd