NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC,
Chinchwad.
Pune – 411019

An ISO 9001:2008 Certified Company

GST Pune : 27AAECN0437H1ZM

F) Single Skinned Motorised Rolling Shutter



Sr. No	Description	Specification
1	Size	(W) 2500 mm x (H) 4000 mm Qty: 4 (W) 4000 mm x (H) 4000 mm Qty: 8 (perforated 600 mm)
2	Roller shutter curtain profile type	Flat Profile Galvalume
3	Mounting Location area	Inside area / Outside area
4	Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side
5	Curtain Panel	The panel made of 1.0mm thick Galvalume
6	Curtain panel size	75mm wide
7	Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
9	Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	Hood Cover	Made of GI Sheet Thickness 0.9 mm
12	Surface finish	without paint
13	**Motor**	Direct Drive German Make