Scissor Lift

Sr. No	Description	Specifications
1	**Type**	Movable/Pit Mounted/Floor Mounted
2	**Capacity in Kg**	Customized
3	**Platform size in mm**	Customized
4	**Shut ht**	Customized
5	**Max ht**	Customized
6	**Lift ht**	Customized
7	**Safety Railing**	both length side only (900 mm height)
8	**Color**	as per req. RAL shade.
9	**Lip**	Manual Lip on one side
10	**Hyd Cylider - Seal kit (Rod end, Head end & Piston)**	Parker
	Hydraulic power pack	3HP, 3 Phase
1	**Gear Pump**	Make Rexroth
2	**ele. Motor**	Siemens/ ABB
3	**Valves**	Rexoth / Yuken
4	**Saftey**	special pilot op check valve
		Manual stand used during Maintainence purpose
		adjustable Limit Switches
5	**Hose**	Make - Parker
6	**Controls**	UP, DOWN and Emergency stop controlled through push buttons provided outside the platform. The lift shall stop automatically , when the platform reaching the desired floor level by actuation of pre adjusted levelling limit switches.
7	**Electrical System**	The continuous running powe pack unit with specified motor starter with suitable length cables. The cylinder unit shall be provided with limit switch and push button control with panel board. The electric panel will have starter contactors, MCB's, push buttons, limit switches and terminal strip. The control panel/cabinet have a seprate stand.