DESG.	NO.S	MASONRY OPNG.		REMARKS
		WIDTH	HEIGHT	
RS1	12	4000	6000	INDUSTRIAL SECTIONAL DOORS
RS2	2	5500	6500	
RS3	1	5000	6000	
RS4	1	2500	3000	ROLLING SHUTTER FIRE RESISTANT (2 HRS RATING)
D	13	1200	2100	GALVANIZED STEEL FIRE RESISTANT DOOR (2 HRS RATING) FIXING OF PANIC BAR SYSTEM LINKED TO ALARM SYSTEM, VISION GLASS OF 300x450MM SIZE.
D1	2	1200	2100	GALVANIZED STEEL FLUSH DOOR CONFIRMING TO IS 277 WITH VISION GLASS SIZE OF 600MMx600MM
D2	6	1200	2100	POWDER COATED ALUMINUM FRAMES AND DOOR FULLY GLAZED SWING DOOR WITH FLOOR MOUNTED SPRING
W	31	2400	1500	MS PROFILED FULLY OPENABLE WINDOWS WITH 6MM GLASS SHUTTERS
W1	10	2400	1500	MS PROFILED FULLY FIXED WINDOWS WITH 6MM GLASS SHUTTERS
W2	2	1500	1200	MS PROFILED FULLY OPENABLE WINDOWS WITH 6MM GLASS SHUTTERS
V	6	900	600	ALUMINIUM POWDER COATED LOUVERED VENTILATOR.