1 mm Galvalume Motorised Rolling Shutter-Indirect Drive		
Sr .No.	**Specification**	**1 mm Galvalume Motorised Rolling Shutter-Indirect Drive**
1	**Description:**	Motorised Rolling Shutter with Galvalume Slats with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete /Steel & Side
4	**Opening/Closing Speed**	0.1 m/sec
5	**Curtain Panel**	The panel made of 1.0mm thick Galvalume.
6	**Curtain panel size**	75mm wide
7	**Curtain Profile**	Curved
8	**Bottom Profile**	Aluminium bottom rail with rubber seal.
9	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
10	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
11	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
12	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
13	**Surface finish**	Powder coated
14	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting