Shlara Automation Pvt. Ltd.
Block-19, Apt. 408, "Bollineni Hillside" Perumbakkam, Chennai-600126. India. Mobile: +919840294082
Phone: +914449526386 Email: Ravi@ShlaraAutomation.com Web: **www.shlaraautomation.com**

PERCo








RTD-03S Waist-high Rotor Turnstile with RB-03TP guide barrier set for indoor application

24 V	60 W	2	23
operating voltage	power consumption	passage directions	persons/min

+50 +1	IP41		M
temperature range	protection rating	mechanical unlocking	motor drive

scheme 3D-presentation video

The RTD-03S waist-high rotor turnstile with wooden handrails is designed for controlling access to facilities with high style and comfort requirements.





Delivery set

- turnstile housing
- guide barrier set
- remote control unit with power supply and battery
- remote control panel

The elegant winged design of this PERCo turnstile meets both comfort and aesthetic requirements for a smart entrance point.

- 90° rotor configuration
- LED directional indicators

The RTD-03S waist-high rotor turnstile comes with a guide barrier set as standard.

The RB-03TP guide barrier set consist of posts made of polished stainless steel tube O50 mm, filler panels of tinted polycarbonate sheets and wooden handrails with built-in LED directional indicators.

High durability and injury-free operation make the use of the RTD-03S long-lived and safe. The electric drive provides smooth, noiseless and inertia-free rotation.

Key override control enables mechanical unblocking of the turnstile for free rotation in both directions.

If required, the turnstiles can be completed with matching railings.



LED indicators at wooden rails of RTD-03S turnstiles



Control panel for remote management



RTD-03S half height turnstiles have mechanical over blocking function

Operating voltage	24 V DC
Power consumption	60 W
Number of passage directions	2
Throughput rate (in the single passage mode)	23 persons/min
Dimensions (length×width×height), without a guide barrier set	1202×1202×1013 mm
Dimensions (length×width×height), with a guide barrier set	1531×1345×1071 mm
Passageway width	600 mm
Operating temperature range	from +1 °C to +50 °C
IP Code	IP41

Frame, guide barrier set – stainless steel.

stainless steel

Filler panels – polycarbonate sheets.

Handrails – solid ashwood / beechwood.

The warranty period is 5 (five) years from the date of sale of the product.