Double Wall Motorized Rolling Shutter

Door type	Double wall / Slat Rolling Shutter
Clear Opening dimension (w) -- x (h) --	(W) 3000 x (H) 3000 mm
Opening Direction	Vertical - from bottom to Top
Mounting Location area	Only Inside area
Mounting Surface	Side Brackets: Optional = On Concrete / Steel & Side Guides : Optional = On Concrete/Steel / Masonry
Opening/Closing Speed	0.1 m/sec
Wind Resistance	100 Km/hr
Slats material	insulated pre coated Galvanized steel (Polyurethane foam)
Slat size	95mm x 19mm with PU filled inside
Curtain Profile	Curved
Bottom Profile	125mm x 15mm with extra angle support. (Optional - Rubber Bottom Seal)
Side Guide Profile	M.S." U" Shaped profile 125 x 40mm x 3 mm thick (as per the opening width dimension)
Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
Side Brackets	MS Plate 3 mm to 10 mm thick , as per the opening dimension
Hood Cover	Made of GI Sheet Thickness 0.9 mm with 25x25x3mm angle stiffener
Surface finish	
Painting	Powder coated – Off white color
Automation	
Drive Unit & Mounting Type	Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement
Emergency Operation	Manual Hand Driven
Operating Mode	Push Button from inside