# Preventive Maintenance Manufacturer's Specification

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in door opening solutions

## Enhance the durability of your High Performance Door Albany RR3000

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



***Instructions for table usage:***

**Qualified person**
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

**Recommendations for exchange**
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

# Preventive Maintenance
# Manufacturer's Specification

ASSA ABLOY

## Albany RR3000

| Product group | Description | 200.000 cycles | 400.000 cycles | 500.000 cycles | 750.000 cycles | 1.000.000 cycles | 1.000.000 cycles or 5 years | 3 years | 5 years | 10 years |
|---|---|---|---|---|---|---|---|---|---|---|
| **Actuators** | Photocell receiver re / tr | | | | | | | | | ● |
| | Safety photocell re / tr | | | | | | | | | ● |
| **Safety** | Cover stat. Photocell | | | | | | | ● | | |
| **Sealing** | Lamella sealing | | | | ● | | | | | |
| | Sealing top lamella | | | | ● | | | | | |
| **Cable chain** | Cable chain, complete with cable and bracket | | | ● | | | | | | |
| **Counterbalancing** | Belt (blue), L=6000, above 4000 mm | ● | | | | | | | | |
| | Belt (blue), L=6000, up to 4000 mm | | ● | | | | | | | |
| | Belt receptacle | | ● | | | | | | | |
| | Flat belt complete | | | ● | | | | | | |
| | Spring suspension top complete | | | | ● | | | | | |
| | Springs above 4 Meters height | ● | | | | | | | | |
| | Springs up to 4,2 Meters height | | ● | | | | | | | |
| | Springs up to 4 Meters height | | ● | | | | | | | |
| **Curtain tension** | Redirection rope with rubber cable | | | ● | | | | | | |
| | Rope for curtain tension, L=8000 | | | ● | | | | | | |
| | Rope pulley | | | ● | | | | | | |
| **Top roll** | Bearing d 35 | | | | | ● | | | | |
| | Dampening profile 2, L=6000 | ● | | | | | | | | |
| | Top roll with lamellas RR3000 complete (*) | | | | | ● | | | | |
| **Lamella** | Edge cover window | | | | ● | | | | | |
| | Lamellas | | | | ● | | | | | |
| | Top lamella | | | | ● | | | | | |
| **Bottom profile** | Rubber profile with / without safety edge | | | | | | | | ● | |
| **Sliding/Guiding** | Adapter with pre running photocell RH / LH | | | | ● | | | | | |
| | Sliding rail | | | ● | | ● | | | | |
| **Switch** | Proximity switch | | | | | | | | | ● |
| **Drive unit** | Brake - frequency converter | | | | | ● | | | | |
| | Drive unit - frequency converter | | | | | ● | | | | |
| | Junction box | | | | | | | | | ● |
| | Microswitch | | | | | | ● | | | |
| **Chain drive** | Drive shaft with pinion | | | ● | | | | | | |
| | Locking element | | | | | ● | | | | |
| | Pinion chain drive barrel | | | ● | | | | | | |
| | Roller chain | | | ● | | | | | | |
| **Encoder** | Encoder 50 pulses, only electronic part | | | | | | | | | ● |
| **Damper** | Vibration absorber | | | ● | | | | | | |

≤150.000 cycles: ±10.000 cycles; >150.000 cycles: ±20.000 cycles
≤5 years: ±6 months; >5 years: ±1 year



© ASSA ABLOY Entrance Systems AB PL.MAN/RR3000/DEU.EN-1.1/1504 / 64 100 478 Technical data subject to change without notice

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization