DATASHEET

KENT VWG690 FABRIC

Kent
Smoke and Fire Curtains

DESCRIPTION

VWG690 is a specially formulated heavyweight fibreglass fabric, reinforced with stainless steel wire and coated with fire retardant aluminum pigmented polyurethane on both sides of the fabric. It is tested to BS 476 Pt 6 (fire propaga tion) and Pt 7 (surface spread of flame) and has achieved the best result of Class 0 for both.

When tested to EN 1634-1 as the full Kent Automatic Fire Curtain Assembly, the fabric achieved a fire resistance of 180 minutes. The finished curtain fabric is carefully sewn with stainless steel thread to achieve a factory produced hems at the top and the sides.



Specifications	Data	Tolerance	Test Method
Thickness	.71mm	± 10 %	DIN ISO 4603/E
Base Fabric Weight	640g/m2	± 5 %	DIN EN 12127
Coated fabric weight	690g/m2	± 10 %	DIN EN 12127
Base Fabric Yarn (Warp)	EC9-136 EC9 68x2 ÷ IV1		DIN EN 12654
Base Fabric Yarn (Weft)	EC9-136 EC9 68x2 ÷ IV1		DIN EN 12654
Thread Count (Wrap)	16 per 1cm	± 5 %	DIN EN 1049
Thread Count (Weft)	15.3 per 1 cm	± 5 %	DIN EN 1049
Coated Side	Both Sides		
Thread	Stainless Steel		
Standard Color	Grey		
Coated Fabric Tensile Strength (Wrap)	500 N/cm		
Coated Fabric Tensile Strength (Weft)	450 N/cm		
Weave	8 Shaft Satin		
BS 476 Pt 6 & Pt 7	Class 0		
EN 13501-1	A2.s1.d0 & BG Nr. 119.112		

Unit 10, 7 Street, Al Qusais Industrial Area 2,
Dubai, PO Box 233962, UAE
www.kentsmokeandfirecurtains.com

Tel-+971 (04) 288 2575
Fax- +971 (04) 288 2576
info@kentsmokeandfirecurtains.com