Motorized Rolling Sutter

Door type	NIHVA Specs	L&T Specs
Clear Opening dimension (w) -- x (h) --	(W) 5000 mm x (H) 5000 mm	(W) 5000 mm x (H) 5000 mm
	(W) 3600 mm x (H) 5000 mm	(W) 3600 mm x (H) 5000 mm
	(W) 3600 mm X (H) 4500 mm	(W) 3600 mm X (H) 4500 mm
	(W) 2400 mm X (H) 3000 mm	(W) 2400 mm X (H) 3000 mm
Mounting Location area	Inside area / Outside area	Inside area / Outside area
Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side	Not Given
	Guides: Not required for height below 3000mm	
Door Material		
Curtain material	MS	MS
Curtain panel size	75mm wide	Not Given
Curtain Profile	Curved	Not Given
Slat Thickness	1 mm	1.5mm
Bottom Profile	2.5 mm	3.15 mm
Side Guide Profile	100mm x 3mm	165mm x 5mm
Roller Shaft	100mm - 300mm	165 mm
Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension	Not Given
Hood Cover	Made of GI Sheet Thickness 0.8 mm with 25x25x3mm angle stiffener	Not Given
Surface finish		
Painting	2 Coats (each coat of 35 microns DFT) of EPOXY polyamide-based enamel finish of approved color and make over a Coat (each one coat 25 microns DFT) of EPOXY polyamide based red oxide zinc phosphate primer	Not Given
Automation		
Drive Unit & Mounting Type	Electric Motor (Imported China make) (single phase / three phase) - Indirect Mounting - Sprocket chain arrangement	Compact gear motor
Emergency Operation	Manual Hand Driven	Chain