NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Hinged Door Chiller / Freezer

TECHNICAL DESCRIPTION:

Door Type:	-	**Hinged Door (Chiller and Freezer application)**
Door Blade:	-	0.6 mm galvanized steel – PVC-coated. Available in the following surfaces: (Other qualities and colors are available)
Thickness:	-	60 mm, 80 mm, 100mm, 120mm and 150 mm
Insulation:	-	High-insulating, CFC-free foam
Frame:	-	2 mm salt water resistant anodized aluminum
Insulation	-	The frame is always insulated with mineral wool.
Gaskets	-	Made of rubber approved for use in the food industry.
Hinges	-	Supplied with stainless steel hinges – Raising
Handle:	-	Special lever handle. Locking box wit face plate prepared for cylinder. Available with full key plate or key plate with hole (prepared for cylinder lock)
	-	door handle of stainless steel. The handle is lockable with emergency opening device.
	-	door stainless steel handle type 2. The handle is lockable

NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Min/ Max size 1 leaf : W x H: 800 x 2000 / 1400 x 2500
2 leaf : W x H: 1400 x 2000 / 2800 x 2500

FOR FREEZER ROOM DOORS :

Heating Arrangement: - Supplied with heating cable in frame and threshold. This threshold, made of salt water resistant anodized aluminum, to be recessed in the floor.

Alternatively, the door can be supplied without threshold, but will then be supplied with extra heating at the bottom of the door blade.

The heating cables are for connection to 230 V / 50 Hz (Also available for other voltage).

Consumption per metre heating cable: Appr. 30 W

Note - Heating in the floor around the door is always recommended.

ADDITIONAL EQUIPMENT:

Canopy: - Recommended for external doors.

Kick Plates: - Door width x height 300 mm (standard)

or

Door width x height 800 mm (max).

Window: - Standard sizes:

- 150 x 300 mm
- 400 x 600 mm
- 500 x 600 mm

Frame: - Salt water resistant anodized aluminum.

Window: - Minimum 2-layer thermo glass.