Product:

NIHVA Sectional Overhead Fully Glazed Doors

Model 1042F

Description:

Overhead sectional door/sectional doors are fully glazed door, designed to be used when there is need for maximum light, exposure, or vision, 44mm thick.

- Up to 3300 mm each Al frame is glazed with one single pane of single or double hardened glass
- Integrated finger pinch protection
- Top, bottom and side seals and seals between door sections
- High Lift/Vertical track system in galvanized steel
- Spring balancing, 20,000 cycles
- Spring break device
- Lock bolt, step-handle

Compliance with all operational and safety instructions in EU Directives and the standards of the European Standardization Committee (CEN)

Operating system: Electric Wind load (EN 12424) - Class 3 (700 N/m²)

Thermal transmittance (EN 12428) – 6 W / (m² K) Water penetration (EN 12425) - Class 3, 70 PA

Air permeability (EN 12426) - Class 3

Surface color:

1. Standard Color is Aluminum Anodized
2. Interior and / or exterior painted in RAL-standard color buyer's choice at extra cost

Hardware: Vertical/High lift

Electronic operator:

Operating voltage: 230 V AC, 50/60 HZ (internal supply 3-phase 230 V AC)

Operating factor: ED = 30%, S3 10 min, non-continuous operation

(Engine operation 3 min, pause 7 min, direct-inverting)

Torque: 15-40 Nm, depending on reel type (value of given door shaft)

Fusing: 10 A

Brake: non-reversible worm gear

Speed monitor: electronic monitoring

Freewheel / clutch: mechanical engagement/disengagement

Limit switch: electronic via torque (setting "Door open" during programming) Setting "Door closed" in processor board

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com

Gears: worm gear 1750 RPM yields approx. 24 rotations door shaft

Shaft: ø35 mm or hexagonal

Direct drive system

No special wall reinforcement necessary

Temperature range: -20°C to 60°C

Soft stop, soft start

Connection using "CEE plug" or lockable mains isolator

Maximum door weight capacity 400 kg

Control units:

a) Loading Area Integrated control unit 950 DLA SD to operate Sectional Door& Dock leveler with automatic return to cross traffic position after operational cycles. Push button control from inside

b) Internal Doors Standard 950 controls equipped with UP DOWN STOP buttons and error displays. Additionally pull switch controller is provided

Output 0.37 kW, input 1 x 230 V. Including control unit with standard actuator UP-STOP-DOWN. The door closes using pulse control incl. self-monitoring safety edge Operating speed 0.25 m/s, safety rating IP 55. If there is a power failure, the disengage device enables manual operation at any time