NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

NIHVA Sales Quotation

Aditya Constructions
Plot NO. 128, Flat No. 3, Usha Apt. ,Nr. Sadhu Vaswani Garden
Pimpri, 411017
Pune, Maharashtra

Date : 23.12.2020
Quote NO : SQT.20.21.2892R
Kind Attn : Mr.Ashok
Email Id : adityaconstructionpune@gmail.com
Contact No: 9011042905

Project Name & Location: Kurkumbh MIDC

Subject : Quotation for Motorised Rolling Shutter, Fire rated Rolling Shutter ,NIHVA make High Speed Door , Sliding Gate ,Retractable Dock Shelter , Boom Barrier , Bollards

Dear Sir,

Thank you for your opportunity and trust shown on "NIHVA" your preferred partner for innovative solutions. This has reference to your above mentioned requirement, please find below our Solutions.

Sr. No	Description	Pages
A.	Commercial Offer	1
B.	Technical Specification	2,3
C.	General Conditions	4
D.	Terms & Condtions	4

A) Commercial Offer

Sr No	Description	Size		Qty	Supply Charges in INR		Installation Charges in INR	
		Clear Width (mm)	Clear Length (mm)	(Nos)	Unit Price	Total Amount	Unit Price	Total Amount
1	GI Motorised Rolling Shutter- Internal	3000	4000	1	141,000	141,000	15,000	15,000
2	GI Motorised Rolling Shutter- Internal	3000	3500	1	134,000	134,000	15,000	15,000
3	GI Motorised Rolling Shutter- Internal	3000	3000	1	127,000	127,000	15,000	15,000
4	GI Motorised Rolling Shutter- Internal	2500	3000	1	120,000	120,000	15,000	15,000
5	GI Motorised Rolling Shutter- Internal	2500	4000	1	131,000	131,000	15,000	15,000
6	GI Motorised Rolling Shutter- Internal	1800	3000	1	109,000	109,000	15,000	15,000
7	GI Motorised Rolling Shutter- External	3000	4000	1	151,000	151,000	15,000	15,000
8	GI Motorised Rolling Shutter- External	3000	3500	1	143,000	143,000	15,000	15,000
9	GI Motorised Rolling Shutter- External	3000	3000	1	136,000	136,000	15,000	15,000
10	GI Motorised Rolling Shutter- External	2500	3000	1	129,000	129,000	15,000	15,000
11	Fire rated Rolling shutter	3000	4000	1	254,000	254,000	15,000	15,000
12	Fire rated Rolling shutter	3000	3500	1	248,000	248,000	15,000	15,000
13	Fire rated Rolling shutter	3000	3000	1	242,000	242,000	15,000	15,000
14	Fire rated Rolling shutter	2500	3000	1	236,000	236,000	15,000	15,000
15	Fire rated Rolling shutter	1800	1800	1	231,000	231,000	15,000	15,000
16	NIHVA Make High Speed Door	3000	4000	1	319,000	319,000	15,000	15,000
17	Single Leaf Motorised Sliding Gate	10000	1500	1	385,000	385,000	15,000	15,000
18	Wicket Gate	1500	1500	1	39,000	39,000	5,000	5,000
19	Retractable Dock Shelter	3400	3500	6	136,000	816,000	15,000	90,000
20	Boom Barrier	6 Mtrs		4	118,000	472,000	15,000	60,000
21	Fix Bollards	Dia 100 mm	1000 Height	30	8,000	240,000	3,000	90,000
22	Additional accessories for High Speed Door	Radar Sensor		1	35,000	35,000		
		Loop Detector		1	35,000	35,000		
		Additional Push Button		1	5,500	5,500		
		Flashing Light		1	7,500	7,500		
		Interlocking Pull Switch		1	20,000	20,000		
		Remote		1	9,500	9,500		
23	Additional accessories for Fire Rated Rolling Shutter	Key Switch		1	5,500	5,500		
		Smoke Detector		1	24,000	24,000		
				Total		**4,945,000**		**500,000**
24			P&F Charges	3%		**148,350**		
			Total Without Taxes			**5,093,350**		**500,000**
			GST Extra @ 18%	18%		916,803		90,000
			Total With Taxes			**6,010,153**		**590,000**
25			Transportation Charges			**Extra at Actual**		
26			Unloading Charges @ Site			**In Client Scope**		

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

B) Technical Specification

Motorized Rolling Shutter





Sr .No.	**Specification**	**GI Motorized Rolling Shutter**
1	**Description:**	Motorised Rolling Shutter with GI Laths with thickness of 1 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	On Concrete /Steel
4	**Curtain Panel**	The panel made of 1.0mm thick GI.
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Dia -100 to 300 mm as per w x h
10	**Side Brackets**	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
12	**Surface finish**	Powder Coating
13	**Drive Unit & Mounting Type**	Electric Motor - Indirect Mounting - Sprocket chain arrangement – IP54 Protection

Fire Rated Rolling Shutter





Sr .No.	**Specification**	**Fire Rated Rolling Shutter**
1	**Shutter Curtain**	Single Skin Design
2	**Guide Rail**	Powder coated
3	**Bottom Bar**	Powder coated
4	**Type of Mounting**	Standard
5	**Motor Drive Unit**	Motorise 230Volt 1P 50Hz with Manual override chain
6	**Standard RAL colors:**	RAL 9002
7	**MAKE & Model**	SKB Make - 2 HRS Fire Rated Shutters BS476
8	**Standard**	BS 476
9	**Fire Rating**	2 Hrs.
10	**Roller Curtain**	Zinc Coated Steel Solid Slats - 1mm thick
11	**Bottom Rail**	Powder coated
12	**Side Guide & Angles**	Galvanise Steel G65, 3mm thick
13	**Shaft/Barrel**	Shaft
14	**Hood & Motor Cover**	0.9mm thick GI
15	**Operation**	Motorise 230Volt 1P 50Hz with Manual override chain
16	**Auto Closing Mechanism**	Fire Shutter will auto close via 71 C degrees Thermal Fusible Link
17	**Power Consumption**	0.75 Kw
18	**Control Switch**	one unit push button switch
19	**Accessories**	Manual override chain
20	**Cable Length**	6 Mtr
21	**Finish/ Colour**	Powder Coated - RAL 9010 (White) or RAL - 7025 - Grey
22	**Protection Category**	BS 476

Retractable Dock Shelter

Sr. No	**Description**	**Specifications**
1	**Size**	(W) 3400 mm x (H) 3500 mm
2	**Top Curtain**	1000 mm
3	**Side Curtain**	600 mm
4	**Curtain colour**	Black
5	**Parking Guides**	White, Yellow
6	**Wall Fixings**	Concrete, Sandwich light Concrete, Load house cavity, insulated panel
7	**Top & Side Curtaiins**	Double Layer High Quality Polyester
8	**Thickness**	3.0 mm
9	**Weight**	Approx 3400 g/m2

NIHVA Make High Speed Door

- Safe & for continous operations
- Self Supporting Construction with anti crash protection system for bottom profile
- Smooth & silent opening & closing
- Can be equipped with full vision PVC curtain
- Modular Interchaegable panels permit to replace worn & damged panels



Sr. No	**Description**	**NIHVA Make High Speed Door**
1	Use	Internal Door
2	Control Panel	4 Push Button operated
3	Security Features	EN 13241-1 Standard
4	Resistance to wind load	EN12424 upto class 1
5	Curtain	Fabric Transparent PVC section
6	Guide Material	Aluminum
7	Hood Cover	GI
8	Motor Cover	GI
9	Operator & Control	German Make Motor
10	Connecting Voltage	220V , 1Ph , N
11	Open-Stop-Close Button	Standard
12	Protection Category	IP 54 / IP 65
13	Power Consumption	0.75 kw Motor
14	Emergency Off Button	Standard
15	Closing Zone Monitoring	Optical Safety edge
16	External Route Monitoring	Photocell
17	Emergency Opening	Crank Handle

NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

Motorised Single Leaf Sliding Gate

Sr .No.	Specification	Motorized Single Leaf Sliding Gate
1	**Door type**	Motorized Single Leaf Sliding Gate
2	**Opening Direction**	Horizontal - from left to right or reverse
3	**Mounting Location area**	Inside area
4	**Design Pattern**	Standard Tubular Design Pattern
5	**Outer Tube**	100 x 100 x 3.6 mm THK SQ. TUBE
6	**For Post**	100 x 100 x 3.6 mm THK SQ. TUBE
7	**Innear Tube**	50 x 50 x 2.6 mm THK SQ. TUBE
8	**Gap Between Tubes**	125mm
9	**Bottom Rail on ground**	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
10	**Bottom Rollers**	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
11	**Guide Rollers supporter during Gate**	Nylon Rollers with Bearings both side mounted on column for support smooth
12	**Painting**	2 Coats of EPOXY polyamide based enamel finish of approved colour
13	**El motor make**	BFT – Italy (100% imported)
14	**Emergency Operation**	Manual after turn the switch
15	**Operating Switch**	Push Button from inside , Remote
16	**Safety**	Photocells, Flashing Light

Boom Barrier






Sr. No.	Description	Specifications
1	Size	6 Mtr
2	Make	Nice/BFT
3	Opening time	Opening Time- 6S
4	Motor Power Supply	24V
5	Type of limit Switch	Electronic
6	Safety	Photocell sensor
7	Operated	Push Button Pedant

Bollards

Sr. No.	Description	Specifications
1	Size	100 mm Dia x 1000 mm Height
2	Make	Nihva
3	Material	MS



NIHVA Technologies Pvt. Ltd.
187, G-Block, 1st Floor, Above Renault Showroom, Thermax chowk, MIDC, Chinchwad.
Pune – 411019

An ISO 9001:2015 Certified Company

GST Pune : 27AAECN0437H1ZM

C) General Conditions

1 Installation will start after receiving of Site Readyness Photographs or written Email communication.

2 We will mobilize the Installation Team in 3 - 4 working days, after reciept of Site Readyness Confirmation

3 For any reason if we need to stop our Installation and demobilize the Team without completing the Work, then extra cost will be applicable for Remobilizing the Team.

4 If Lifting Equipements are in NIHVA Scope, then those will be used for Installation purpose only and not for any other works.

Note: Please find below List which are in Client Scope

Sr. No	Description	
1	Secured and fully covered Store area to keep the material	
2	Scaffolding/Hydra/Crane/Forklift etc - Required for Installation at Site	
3	Electrical Supply on the site single phase/three phase points at different places.	
4	Any civil / masonry/structural work required	
5	All structure support required	
6	In Case of any changes in the layout as per site requirements after the shipment of material , the additional quantities and the wastage.	
7	Conduits, Cables required	

D) Terms & Conditions

Price : Ex Works Pune

Delivery : 9-10 Weeks for High Speed door , Dock shelter,Fire Rated Rolling Shutter & 5-6 weeks for Rolling Shutter , Boom Barrier ,Sliding Gate and Bollards from the date of receipt of confirmed purchase order, Advance Payment & Drawing approval.

Payment : 80% along with confirmed purchase order & Balance before dispatch

Validity : Validity of Offer is 15 days from the date of quotation

Warranty : 12 months from the date of supply.

For any further Clarification /Information in this Concern, Please feel free to Contact **Mr. Shrikant Mirkute on 8551098333**

With Best Regards
Pradeep Shinde
7219206333
For NIHVA Technologies Pvt Ltd