ELECTRO-HYDRAULIC MANUAL TOWING PORTABLE SCISSOR LIFT		
DATE- 24.6.2021	REV-R0	FILLED BY - SIDDHESHWAR SHELAKE

Sr. No.	Description	Specification	NIHVA REMARK
1	Hydraulic Scissor Lift comprising of a platform, Base, Scissor Legs, Hydraulic cylinders, Power and control circuits etc.		OK
2	Capacity	Not Less than 300 Kgs	300KG
3	Platform size (L x W)	2300 mm (Minimum) x 1000 mm (Minimum)	2500LX1500M- PLATFROM RETRACTED 3500LX1500M- PLATFROM EXTENDED
4	Lifting height	Not Less than 8000 mm (from the ground level)	8000 MM
5	Working height	10000 mm (Minimum)	10000 MM
6	Closing height	Equal to (or) less than 1500 mm	1500 MM
7	Plat form extension	1000 mm (Minimum)	1000 MM
8	Plat form extension capacity	100 kg (Minimum)	100 KG
9	To and Fro Movement	Manual towing with ground clearance 200 mm minimum.	MANUAL TOWING WITH GROUND CLEARNACE - 200 MM
10	Up/Down Movement	Electro hydro control - Electrically operated through push buttons and platform is to be lifted by hydraulic cylinders	OPERATED BY PUSH BUTTON PENDANT MOUNTED ON RAILING
11	Power and control	**Shall be furnished**	OPERATED BY 3 PHASE AC 5 HP POWERPACK TANK CAPACITY 40 LITREOPERATION CONTROL BY PUSH BUTTON
12	Control selection	Basket selection	AUTO/MANUAL MODE ON CONTROL PANEL
i)	Control Panel	Electrical/Electronic panel with Up/Down Pendent shall be provided.	CONTROL PANEL MOUNTED ON FRAME NERA POWERPACK
ii)	Additional raising and lowering control with emergency button shall be provided at the base frame of scissor lift.		PUSH BUTTON WILL BE PROVIDED ON CONTROL PANEL FOR OPERATION CONTROL FROM GROUND
13	Guard rail	1100 mm.(Minimum)	1100 MM
14	Stabilizers	Adjustable 4 stabilizing interlocking outriggers	MANUAL TYPE EXTENDING OUT-TRIGGER
15	Tyres	Solid tyre suitable for rough surface	CASTOR WHEEL WITH 2 NOS FIXED & 2 NOS SWIVEL TYPE
16	Lifting time	Shall be furnished	60 SECOND
17	**Safety: The following Safety features shall be provided**		
a)	Max. Height Limit switches to ensure lift does not rise beyond Maximum height		MAXIMUM HEIGHT CUTOFF CONSIDERED
b)	Overload hydraulic valve to ensure equipment will not lift beyond its capacity		PRESSURE RELIEF VALVE WILL BE PROVIDED & SET TO MAXIMUM PRESSURE
c)	Manual valve to lower the scissor platform in case of power failure.		MANUAL VALVE IN CASE OF POWER FAILURE WILL BE PROVIDED
d)	Power operated solenoid valve to ensure lift will not lower down in case of power failure		OK
e)	Hose burst value.		OK
f)	Fuse Protection for main circuit		OK
g)	Lifting hooks.		OK
h)	Safety Belt Hooks.		OK
i)	Mechanical stopper for additional safety		MAINTENANCE STOPPER PROVIDED
j)	Emergency stop button on control panel		OK
18	Power point on the platform shall be provided.		PUSH BUTTON PENDANT WILL BE PROVIDED ON RAILING FOR OPERATION CONTROL POWERPOINT WILL BE ALSO PROVIDED
19	Approach ladder shall be provided to climb on top platform when scissor lift is lowered.		OK
20	Equipment shall work at intermittent height also.		OK, INCHING MODE PROVIDED
21	No of wheel for movement	**Shall be mentioned**	4 NOS
22	Hydraulic cylinder working pressure	**Shall be furnished**	LIFTING CYLINDER -120 BAR PLATFORM EXTENDING CYLINDER 80 BAR
23	No of Hydraulic cylinder	**shall be furnished**	6 NOS OF 40 MM BORE 800 MM STROKE CYLINDER FOR LIFTING PLATFORM 2 NOS OF 25MM BORE 1000MM STROKE CYLINDER FOR PLATFORM EXTENSION
24	The technical catalogue and drawing for the quoted make and Model shall be enclosed		GA DRAWING WILL BE PROVIDED LATER .
25	The equipment shall be supplied with all accessories and consumables like Hydraulic oil etc		OK
26	Original material test certificate shall be furnished laboratories approved by BIS or from the laboratories accredited by NABL.		OK