Gear Operated Rolling Shutter

Sr .No.	Specification	Galvanised Gear Operated Rolling Shutter
1	**Description**	Gear Operated Rolling Shutter with GI slats with thickness of 1.2 mm.
2	**Mounting Location area**	Inside area / Outside area
3	**Mounting Surface**	Side Brackets: Optional = On Concrete
4	**Curtain Panel**	The panel made of 1.2mm thick GI
5	**Curtain panel size**	75mm wide
6	**Curtain Profile**	Curved
7	**Bottom Profile**	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	**Side Guide Profile**	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick.
9	**Roller Shaft**	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día -100 to 300 mm as per w x h
10	**Hood Cover**	Made of GI Sheet Thickness 0.9 mm
11	**Surface finish**	powder Coated
12	**Operation**	Gear Assembly.

Client Requirement

Hot rolled double dipped galvanised steel lath section of 18 SWG (Minimum Galvanised 90 microns or 610gm/Sq.M Conforming to IS: 6248), two top coats of approved synthetic enamel paint etc.