ARIS automation

# TELESCOPIC BELT CONVEYOR

This Conveyor Extends automated loading all the way into the nose of your trailer. It's the perfect choice for high volume shipping /receiving applications.



## Key Features:

- The ramp personnel are able to concentrate on two tasks: Driving the ARIS telescopic belt conveyor in and out to the right position at the touch of a button and placing the packaged goods at the time of loading or unloading. The ergonomic design and the large contingent of safety devices, such as the covers on all moving parts, are important factors for high productivity and safety in the workplace. Everything else takes place through system control, due to full integration into the conveyance technology.

- Flexible, adaptable access systems are the key to success. Efficient, time and energy saving loading processes simplify the material flow. Integrated systems ensure a seamless transition from transport logistics to internal conveyance technology - in each direction.

## Types of Telescopic Conveyor:

- Fixed Type Telescopic Belt Conveyor Without Hydraulic lift
- Fixed Type Telescopic Belt Conveyor With Hydraulic lift
- Mobile Telescopic Conveyor With Hydraulic Lift
- Movable Dockless Telescopic Conveyor With Hydraulic lift

ARIS automation

| ARIS 3 stage Telescopic Belt Conveyor | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Model** | **Fix length (mm)** | **Extension (mm)** | **Total Length ( mm)** | **Minimum Height(mm)** | **Belt Width (mm)** | **Max Load (kg/m)** | **BeltSpeed (m/min)** |
| AR-TBC-3S-4/5.4 | 4000 | 5400 | 9400 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-4.5/6 | 4500 | 6000 | 10500 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-5/6.9 | 5000 | 6900 | 11900 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-5.4/7.3 | 5400 | 7300 | 12700 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-6/8 | 6000 | 8000 | 14000 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-6.5/8.3 | 6500 | 8300 | 15400 | 750 | 600/800 | 50 | 15-30 |
| AR-C-TBC-3S-7/9.6 | 7000 | 9600 | 16600 | 750 | 600/800 | 50 | 15-30 |

| ARIS 4 stage Telescopic Belt Conveyor | | | | | | | |
|---|---|---|---|---|---|---|---|
| **Model** | **Fix length (mm)** | **Extension (mm)** | **Total Length ( mm)** | **Minimum Height(mm)** | **Belt Width (mm)** | **Max Load (kg/m)** | **BeltSpeed (m/min)** |
| AR-TBC-4S-4/7 | 4000 | 7000 | 11000 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-4.5/8.5 | 4500 | 8500 | 13000 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-5/9.5 | 5000 | 9500 | 14500 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-5.4/10.3 | 5400 | 10300 | 15700 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-6/12 | 6000 | 12000 | 18000 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-6.5/12.8 | 6500 | 12800 | 19300 | 800 | 600/800 | 50 | 15-30 |
| AR-C-TBC-4S-7/14 | 7000 | 14000 | 21000 | 800 | 600/800 | 50 | 15-30 |

ARIS automation

## CONTACT US


**ARIS AUTOMATION**

657 MAKARPURA G.I.D.C,

NEAR HIMALYA MACHINERY

VADODARA

M) 9727722740, 9979979755