TECKENTRUP
DOOR SOLUTIONS

Teckentrup GmbH & Co. KG | post box 3113 | 33326 Gütersloh

NIHVA Technologies Pvt Ltd.
8/1 Coomant Housing Society,
411044 PUNE, MAHARASHTRA
INDIA

Teckentrup GmbH & Co. KG
Industriestr. 50
33415 Verl-Sürenheide
info@teckentrup.biz
www.teckentrup.biz

administrator:
Atilla Özel
phone: +495246504182
fax: +495246504177
atilla.oezel@teckentrup.biz

sales representative:
Atilla Özel
phone:
fax: +495246504177
atilla.oezel@teckentrup.biz

offer 2000163286

offer:	2000163286
date:	29-Dec-20
3. amendment dated:	09-Aug-21
customer no.:	122532

building project Requirement of Double Wall Insulated Doors / IN

Dear Sir or Madam,

Thank you very much for your inquiry. Attached you will find our non-binding offer based on our general terms and conditions of trade.

Our offer is based on the tender as well as the door list at hand. Construction drawings have not been taken into consideration.

Delivery occurs free your warehouse, without unloading, without carrying, without mounting and other on-site services.

payment conditions: 50% prepaym.,50% upon collect.
incoterm: EXW Ex Works

Prices net in EURO, plus legal value added tax

delivery period: approx. 5 - 6 weeks after order placement and technical clarification.
The delivery period can be deviating for certain positions, this will be noted accordingly.
The approximate delivery period can differ at the time of placingthe order due to special features and/or increased order volume. by 1 to 2 weeks.
Subject to correct and timely self-delivery.

For this offer a maximum evaluation period of 09.02.2021 applies.
In cases of ordering partial quantities of the offer we reserve the right to renegotiate or recalculate.

We hope our today's offer is meeting your requirements and we are looking forward to receiving your order

With best regards

Teckentrup GmbH & Co. KG

attachments: offer

place of performance and jurisdication for payment and delivery is Gütersloh. Above items remain our property until they are completely paid. Payments towards the representative do not release you from your obligations to us. Delivery in consideration of our terms and conditions of trade.

Sparkasse Gütersloh: IBAN: DE37 4785 0065 0016 0001 01 BIC: WELADED1GTL | Volksbank Gütersloh: IBAN: DE55 4786 0125 0105 3753 00 BIC: GENODEM1GTL
Kreissparkasse Wiedenbrück: IBAN: DE64 4785 3520 0000 0535 61 BIC: WELADED1WDB | Commerzbank Gütersloh: IBAN: DE39 4784 0065 0150 2293 00 BIC: COBADEFF478
Deutsche Bank Gütersloh: IBAN: DE27 4807 0040 0340 6865 00 BIC: DEUTDE3B480

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

TECKENTRUP
DOOR SOLUTIONS

offer 2000163286 / 29-Dec-20 3. amendment dated:09-Aug-21

pos.	material	description	quantity	unit price EUR	total price EUR
001000	**153718**	**roller shutter Thermo Teck (C)**			

double-skinned Teckentrup roller shutter made from PU-foamed steel profiles.
outside of profiles micro-profiled, inner surface "smooth" w groove (curve).
For outer rollers the actual inside is visible on the outside!
Micro-profiling then inside.

net	10.00PC	5,007.39	50,073.86

roller d. curtain profile type	ThermoTeck steel filled with PU-foam
ordering size (b x h)	4.515 mm x 8.200 mm
roller door surface outside	galvanised with protective fil
door color inside / outside	uniformly
roller shutter type	internal roller with storm hooks
buffer drive side min./exist.	325 mm / 325 mm
buffer bear. side min./exist.	200 mm / 200 mm
lintel height min./existing	700 mm / 700 mm
insertion depth	948 mm
building structure	concrete
bottom profile	ET-1 for Teckentrup ThermoTeck
welding shaft	steel tube ø 159mm primed
guide rail	FS 110 steel
underlining size	60 mm
console drive/bearing side	console type 7.5 / console type 7.5
brush sealing type	BH - 50
drive type / -edition	direct mount drive TAR 5.75 KU 400V/3Ph AWG 12 U/min; IP54; 60% ED
drive mounted	inside left, standing
emergency drive operation	emergency hand crank
door operation	normal operation quantity
control unit	CS 310 (pulse) with built-in triple button CEE-plug with wire
control side	same as drive side
safety edge device	opto-sensors
control cable length	9.000 mm
heat transmis. value [W/m2K]	3,34
wind load class	wind load resistance class 3

positions amount		50,073.86
Output Tax	0.00%	0.00
total amount		50,073.86

Please note:
Based on your inquiry the following notes regarding our particular products/positions result:
legal information

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

Teckentrup doors comply with the norm 13241-1.
Included under this is EN 12978 -this applies to the safety devices for power operated doors and gates.

- Doors with pulse control or "push to run" have to be equipped with a secondary safety feature- safety edge or photocells. This is mandatory for automatic closing doors and those using radio control.
  Roller doors and roller grilles less than 2500mm in door height need an additional light barrier as roll-up safety/finger pinch protection to satisfy entrapment regulations.

The maximal wind load is valid for the closed and does not ensure proper door opening.

Teckentrup sectional doors/ roller doors
For roller doors and sectional doors with more than 70 cycles a day or more than 20 cycles per hour we recommend using a motor with 100% rating.

- For doors with more than 10,000 cycles a year we recommend the use of reinforced torsion springs (increased load cycle).
- The lintel seal of sectional doors with low headroom (NSH/NSD) and a lintel of only 250mm may catch on the ceiling and may leave scuff marks.

Teckentrup aluminium roller door 4020
- The smooth version of the roller door 4020 can develop abrasive marks -this is due to technical reasons and will not entitle to warranty or replacement- therefore we recommend the stucco embossed material which conceales any abrasive marks.
- Doors with powder-coated surfaces can cause increased running noises and possibly abrasion marks. This is due to technical reasons and does not constitute grounds for complaint.

Galvanised surface with transparent protective paint
This is manufactured cold formed galvanised sheet, there is no paint coating.

Consider possible environmental influences (such as sea climate, aggressive vapours in the atmosphere, road salt, exposure to abrasive materials, increased wind loads). Where appropriate subsequent protective paints may be required.

To ensure there is sufficient water run-off in front of the door and on the frame parts a minimum fall away of 2-3° is suggested to prevent water standing and puddling (risk of corrosion)

We reserve the right to amend charges if measurements and technical specifications change.,

inspection and maintenance instructions
For power operated doors in a factory or public place the Machinery at Work Act denotes that a maintenance schedule must be in place with yearly safety inspections.

We recommend that Teckentrup industrial doors with more than 50 cycles a day be inspected every 6 months, and doors with more than 100 cycles a day be tested every 3 months.

Non-compliance with the above mentioned tests can cause risk of injuries and danger of property damage and will invalidate warranty rights.

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739

environmental product declaration:
"Teckentrup Türen und Tore" are declared by the ift Rosenheim - EPD (environmental product declaration).
Please find further information on **www.teckentrup.biz/downloadcenter**

legal form: GmbH & Co. KG, commercial register Gütersloh A 4173. Head office Verl, personally liable partner: Teckentrup Metalltüren GmbH. Head office Verl, commercial register Gütersloh B 1628.
managing directors: Kai Teckentrup
value added tax identification no.: DE 209454739