NIHVA
NIHVA TECHNOLOGIES PVT. LTD.



NIHVA Technologies Pvt. Ltd. ***187, G-Block, Thermax Chowk, MIDC*** ***Chinchwad, Pune – 411019*** ***Contact No-8551093333 /8551098333/8551091333*** ***Email Id- sales@nihva.com ; support@nihva.com*** ***Website-www.nihva.com***	***Shubhshree Engineering & Constructions Pvt Ltd.*** ***Aurangabad*** ***Kind Attn- Mr. Manish Sharma*** ***Contact No-9175575106*** ***Email Id- manishsharma@shubhshree.co.in***

Project Name & Location – PH_1 Endress Hauser Flowtech Aurangabad

International Business Partners

ALBANY ASSA ABLOY

MEGADOOR ASSA ABLOY

Crawford ASSA ABLOY

ACO

Teckentrup

NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

1.Company Profile



We Make Possible

"NIHVA Technologies" as one of the Pioneers in offering intelligent, innovative and integrated Automation Solutions.

We would like to work with you on your upcoming project hence request you to give us an opportunity and kindly consider our NIHVA name for Door products and Automation Solutions.

If you need more technical details about our products or any new solutions, kindly revert back to us.

"NIHVA" Business activities:

- **Door Automation**
- **Automation Solutions & Material Handling Equipment's (Customized)**
- **Water Management & Environment Solutions**

"NIHVA" has always been strongly supported by world leaders in automation. Our commitment is to execute projects with highest quality, on time & within the budget,

while adhering to safety, health & environmental standards & thus we are able to serve with the best quality services and products to our customer like you.

NIHVA is the Authorized Business Partner of ***"ASSAABLOY"*** from Germany and Sweden.

International Business Partners

ALBANY ASSA ABLOY

MEGADOOR ASSA ABLOY

Crawford ASSA ABLOY

ACO

Teckentrup

NIHVA
NIHVA TECHNOLOGIES PVT. LTD.

Technical Specification

1) Pit Mounted Scissor Lift





Sr. No	Description	Specifications
1	Capacity	6T
2	Platform size	(W) 2000 mm X (L) 2500 mm
3	Shut ht	1000 mm
4	Max ht	2200 mm
5	Lift ht	1200 mm
6	Power Pack Inside Pit with Buzzer	NIHVA Make
7	Safety Railing	Safety railing M.S SECTION 900 mm ht all side on platform & fixed
8	Manual Lip	3 Piece (240 + 1500 + 240) - 1 Side Only
9	Maintenance Stopper	2 NOS
10	Push Button Pendent	Flexible pendent with 5 Mtr Cable - 1 No
11	Control Panel	Outside pit - 1 No
12	Safety Bellow	All side
13	Hydraulic Cylinder	Two numbers with Bore 150 X stroke 500 mm – NIHVA make
14	Hot Dip Galvanized	As per IS std
15	Hose	Local Make
16	Cable	Polycab cables
17	Hydraulic Oil	Grade 68 - 125 Ltr
18	Paint	Gloosy
19	Fabrication	3500KG

International Business Partners

ALBANY ASSA ABLOY MEGADOOR ASSA ABLOY Crawford ASSA ABLOY ACO Teckentrup

2) Hydraulic Dock Leveler





Sr. No.	Description	Specifications
1	Capacity	6 T (Hot dip Galvanized)
2	Dock operation mode	AC power pack hydraulically operated
3	Lip operation mode	Hydraulic
4	Operation control	Through panel
5	Loading platform height from road	1200mm
6	Travel above & below dock level	(+) 300 / (-) 150 mm
8	Platform Size (W x L)	2000 mm x 3000 mm
9	Lip size (W x L)	2000 x 400 mm
10	Shut Height	480 mm
11	Maximum slope can be achieved	0.1
13	Clear Pit dimensions (W x L x D)	(W) 2050mm x (L)3000 mm x (D)480 mm
14	Hydraulic power pack	Standard
15	Driver type	Direct by electric Motor
16	Motor Ratings	1 H.P
17	Pump design flow	1.5 LPM
18	Pump pressure	120 bar Operating 200 bar Max.
19	Safety valve set pressure	120 Kg/cm²
20	Pump Type	Gear
21	Volume of oil receiver	5 Lit
22	No of Cylinder	2 No for Dock & 01 Nos for Lip

International Business Partners

ALBANY ASSA ABLOY MEGADOOR ASSA ABLOY Crawford ASSA ABLOY ACO Teckentrup

3) Sectional Door

Sr. No	Description	Specification
1	Size	(W) 4000 mm X (H) 4000 mm
2	Vision Windows	2 Nos at central panel
3	Opening Direction & Mounting	Vertical (For Quantity 7 Nos)
4	Opening Direction & Mounting	Low lift (For Quantity 1 No)
5	Opening/Closing Speed	CDM9 0,28 m/s
6	Door Material	GI Steel
7	Panel Thickness	42 mm Square Grid, steel sheet
8	Filling	CFC-free polyurethane
9	Panel colour	RAL 9002 Grey White Powder coated
10	Door sealent	All door sealants made of EPDM rubber, temperature resistant -30/+70
11	Panel Flame Retardent standrad	Flame retardant polyurethane foam according DIN4102-class B2.
12	Water Penetration	EN 12425 class 3
13	Air Permealibity	EN12426 class 3
14	Wind Load	EN21424 class 3
15	Thermal Transittance	EN 12428 1.10W /m2K
16	Bottom sealing	Bottom of the door to be equiped with three lip sealing made of oil resistant EPDM rubber
17	Door saftey	Doors equiped with spring break device
18	Incase of Power failuer	Doors to be equiped with quick release fuction
19	Operator power conumption	Operator to have a maximum power consumption of 0,37kW and a standby consumption of Maximum 15W
20	Drive Unit & Mounting Type	Single phase 230V direct drive on shaft
21	Emergency Operation	by Disengagement rope manual
22	Operating Switch	Up/Down Keypad + stopbutton
23	Locks : Lock bolt	The Lock bolt locks the door from the inside, without the use of a key. The Lock bolt is not visible from the outside.
24	Environmental Green Product Declaration Certification	As per ISO 14025 and EN 15804

International Business Partners

ALBANY ASSA ABLOY MEGADOOR ASSA ABLOY Crawford ASSA ABLOY ACO Teckentrup

4) High Speed Door

Sr. No	Description	Specifications
1	Sizes	(W) 4000 X (H) 4000 mm
2	Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking
3	Security Features	EN 13241-1
3	Opening Speed up to	Opening 1.5 m/s.
	Closing Speed	0.8 m/s.
4	Control Panel	4 Push Button operated
5	Resistance to wind load	EN 12424 upto Class 2
6	Curtain stabilisation / Wind load	Aluminium anodized windbars
7	Curtain	Fabric -0.9 to 1.5 mm Transparent PVC section -2.0 mm
8	Curtain colour	Standard blue RAL 5010
9	Guide Material / Surface	Aluminium anodized
10	Hood Cover	galvanized steel
11	Motor Cover	galvanized steel
12	Operator & Control	European Make Motor
13	Connecting Voltage	220 V ~ / 50 - 60 Hz - 1 PH , N
14	Open-Stop-Close Button	Standard
15	Protection Category (Operator / Control)	IP 54 / IP 65
16	Power Consumption	0.75 kw Motor
17	Emergency Off Button	Standard
18	Closing Zone Monitoring	Optical Safety edge
19	External Route Monitoring	Photocell
20	Emergency Opening	Crank Handle

3) Sectional Door – Ref. Photograph





4) High Speed Door – Ref. Photograph





International Business Partners

ALBANY ASSA ABLOY

MEGADOOR ASSA ABLOY

Crawford ASSA ABLOY

ACO

Teckentrup

5) Dock Shelters





Sr. No	Description	Specification
1	Size	(W) 3450 mm x (H) 3600 mm
2	Quantity	4 Nos
3	Curtain colour	Black
4	Parking Guides	White, Yellow
5	Wall Fixings	Concrete, Sandwich light Concrete, Load house cavity, insulated panel
6	Top & Side Curtaiins	Double Layer High Quality Polyester
9	Continous Roof Cover	One layer high quality Polyester
10	Thickness	0.5 mm

International Business Partners

ALBANY ASSA ABLOY
MEGADOOR ASSA ABLOY
Crawford ASSA ABLOY
ACO
Teckentrup

6) Single Skinned Motorised Rolling Shutter





Sr. No	Description	Specification
1	Size	(W) 2500 mm x (H) 4000 mm (W) 4000 mm x (H) 4000 mm (perforated 600 mm)
2	Roller shutter curtain profile type	Flat Profile GI
3	Mounting Location area	Inside area / Outside area
4	Mounting Surface	Side Brackets: Optional = On Concrete /Steel & Side
5	Curtain Panel	The panel made of 1.0mm thick GI
6	Curtain panel size	75mm wide
7	Bottom Profile	M. S. Plate 100 mm x 2.5 mm thick with angle stiffener
8	Side Guide Profile	M.S." U" Shaped profile 65 mm -150 mm x 3 mm thick (as per the opening width dimension)
9	Roller Shaft	M.S. Tubular Pipe with Flange & machined shaft at the ends Pipe Día - 100 to 300 mm as per w x h
10	Side Brackets	MS Plate 3 mm to 10 mm thick, as per the opening dimension.
11	Hood Cover	Made of GI Sheet Thickness 0.9 mm
12	Surface finish	without paint (Powder coated)
13	Motor	Direct Drive European Make

International Business Partners

ALBANY ASSA ABLOY MEGADOOR ASSA ABLOY Crawford ASSA ABLOY ACO Teckentrup