Product:

High Performance Door

NIHVA RapidProtect™ 300 MP

Description:

Flexible High Performance Door, opening in vertical direction for use as a machine protection door.

Self-supporting side frames made of aluminium with integreated safety switches, all fittings galvanized.Front of side frame lifts of for generous access to safety limit switches and fixtures.

Door curtain made of RollTex® Plus – colour blue (similar RAL 5002), orange (similar RAL 2009), grey (similar RAL 7001).

Opening / closing speed: max 2.3/1.3 m/s (depending on size)

Wind protection: through wind tabs on the door curtain.

Wind resistance: class 1 (EN 12424).

Bottom profile: anodized aluminium.

Drive unit: hollow shaft gear motor, rotable in steps of 45°

Protection: IP 55

Control system: Frequency converter control system MCC^{VectorControl}, based on Vector control and including boost function at start-up. Can be upgraded with a graphic display and foil keypad for easy guided operation. Easy access to all important information for operation and service.

Control voltage 24 V DC

Supply voltage:

3L(N)/380/400/415/440/480V; 50/60 Hz.

Transformer necessary for 220/230/500V.

Safety devices:

- Electrical safety contact edge, only available with MCC control unit.
- No door line photocell

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com

- Cable chain integrated in side frame for evaluation of closing edge monitoring.
- Drop down protection integrated in gear box.
- Safety switches: Magnetic switch with evaluation unit for performance level e, acc. to EN ISO 13849-1, and SIL3, acc. to EN 62061, integrated in side frame.

Manual activation: by means of a crank.

Size max.: (DW x DH) 4000 x 3500 mm

Make: ALBANY RapidProtect™ 300 MP

Options

Cover

Top roll cover:made of anodized aluminum

Motor cover: steel sheet, powdercoated (similar RAL 9006)

Door curtain (alternatively):

- Curtain made of RollTex® Original – colour

  blue (similar RAL 5002),

  orange (similar RAL 2009) or

  grey (similar RAL 7001)
- Curtain made of NomaTex® – colour grey (similar RAL 7038)
- Window (DWxDH) 500x700mm (only for RollTex® or NomaTex®)
- Window (DWxDH) 700x500mm (only for RollTex® or NomaTex®)
- Anti UV bronze coloured window (only for RollTex® or NomaTex®)

- Curtain made of NomaTex® flame retardant without transparent stripes or windows - color grey (similar RAL 7045)

- Curtain made of transparent PVC with coloured coated fabric
- reinforcement sripes: ultramarine(similar RAL 5002), red (similar RAL 3002), beige (similar RAL 1014), yellow (similar RAL 1021), orange (similar RAL 2011), green (similar RAL 6018), white (similar RAL 9016) or grey (similar RAL 7035).
- PVC with silicone-free reinforcement stripes

Alternative control unit:

Contactor control ACS 50, electronic control system with mini contactors including main switch and open-stop-close switch, control voltage 24 V DC (open/close), max. 1.0 / 1,0 m/s

Supply voltage: 3L(N)PE/230/380/400/415V; 50Hz, transformer for 440/480/500V necessary

Safeguarding the main closing edge:

Self-monitoring electrical safety edge, additional door line photocell in the side frames, opening / closing speed: max. 2.3/1.3 m/s with MCC control unit

Safety switches (alternatively)

- 2 pcs Schmersal magnetic switches with control unit for safety class 4, Ple, SIL3, switches integrated in the side frames
- 2 pcs Telemecanique limit switches with control unit for safety class 3, PLd, SIL3, switches integrated in the side frames
- 1 pc Telemecanique limit switch on the drive side, no safety class
- 2 pcs Telemecanique limit switches, no safety class

Miscellaneous:

- Graphic display for MCC VectorControl unit
- Bottom plates in the side frames
- Braces for floor assembly
- Chain drive
- X-level extensions of the side frames from the lower closing edge to the floor
- Extended flexible seal
- Actuator
- Additional safety devices