NIHVA make – Motorized Sliding Gate

Door type	Motorized Sliding Gate
Clear Opening gate dimension	(W) 4950 mm X (H) 2700 mm
Quantity	1 No
Opening Direction	**Horizontal - from left to right or reverse**
Mounting Location area	Inside area
Design Pattern	Standard Tubular Design Pattern
Outer Frame Tube Sizes	100 X 4 mm
Internal Vertical Tube Sizes	49 x 2.9 mm
Gap Between Tubes	150 mm TYP
Bottom Rail on ground	dia 20 mm round bright bar with heavy duty support ISMB 100 X 50 Beams
Bottom Rollers	Heavy Duty Bottom Wheel With both side Bearings (chorme plated)
Full Height Column sizes	100 x 4 mm
Guide Rollers supporter during Gate movement	**Nylon Rollers with Bearings both side mounted on column for support smooth movement of gate**
Painting	Powder Coating
El motor make	BFT – Italy (100% imported)
Emergency Operation	Manual after turn the switch
Operating Switch	Push Button from inside
Safety	Photocells, Flashing Light
Metal Rack	Zinc plated metal rack
Installation Checks	need to be check = space requirements + substructure + Mounting access + Access in the event of power cut
Civil work	Client scope – client need to grout the I beam in concrete to create track for sliding gate