High Performance Door Rapid Roll® 500 (High Speed Door)



Door type	RR500	PL. indicate your requirement
Description	Flexible High Performance Door, opening in vertical direction, for interior and exterior use	
Side frames	Galvanized steel with cover panels made of anodized aluminum. Side frame consists of guide rail for intake of the curtain (zipper closure)	
Door curtain	Transparent PVC Curtain with vertical reinforcement stripes, blue (RAL 5002) or optional in red (RAL 3002)	
Wind protection	Through wind taps on the door curtain	
Wind resistance	Class 4 / Class 3 if DW > 6000 mm	
Bottom profile	Flexible PVC	
Drive unit	Elektrisch	
Protection	IP 55	
Control system	Frequency converter MCC	
Supply voltage	3/(N)/PE 380/400/415/440/460V 50/60 Hz +/- 10% (480V + 5%/-10%)	
Safety devices	Flexible bottom profile with electrical contact edge and wireless transmission to the control system, Safety photocell Transmitter / Receiver inside side frames.	
Manual activation	By releasing the brake at ground level. Opening speed up to 1,0 m/s, closing speed up to 0,5 m/s;	
Size max	(DW x DH) 8000 x 5500 mm	
Make	ALBANY Rapid Roll® 500	

Options		
Cover	➢ Top roll cover made of Aluminum anodized ➢ Steel, powder coated RAL 9006	
Door curtain (alternatively)	➢ PVC with coloured reinforcement stripes ➢ Blue 5002 ➢ Red 3002 ➢ Orange 2011 ➢ Grey 7035 ➢ Yellow 1021 ➢ Green 6018 ➢ Biege 1014 ➢ White 9016 ➢ NomaTex colour ➢ Blue 5005 ➢ Red 3000 ➢ Orange 2009 ➢ Grey 7038 ➢ Yellow 1023	
Control system (alternatively)	Frequency converter control system MCCVectorControl, based on vector control system including boost function for start-up, ➢ Opening speed up to 1,0 m/s, closing speed up to 0,5 m/s; ➢ 3/(N)/PE 380/400/415/440/460V 50/60 Hz +/- 10% (480V + 5%/-10%)	
Miscellaneous	➢ Knock out capability ➢ Chain drive ➢ Fall down protection (Within Gear Motor) ➢ Additional safety devices	

91 8551091333 ☎ +91 20 66304033

Email: marketing@nihva.com