ASSA ABLOY

AUFTRAGSBESTÄTIGUNG/ ORDER CONFIRMATION

ASSA ABLOY Entrance Systems - Am Mondschein 25 - D-59557 Lippstadt

NIHVA Technologies PVT LTD 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	**Auftrags-Nr./Order No**	30829674
	Datum/Date	2021-05-03
	Referenz/Reference	Mr. Gulagunji
	Verkäufer/Salesman	

Kunden-Nr./Customer No.	**Innendienst/Internal department**	**Versandart/Way of delivery**
1059669	Olga Ziebart +49.2941.766. x 746	Sea
Ihre Ust-ID Nr./Your TAX No	**Ihre Bestell-Nr./Your Order**	**Versandbedingungen/Terms of delivery**
	NVA-518	FCA / Stenovice incl.stand.packing / Forwarder (W)

Lieferadresse/Delivery address **Nr. Lieferadresse/Delivery address No.**	**Zahlungsbedingungen/Terms of payment**
NIHVA Technologies PVT LT1059669 27 8/1 Coromant Housing Society 411044 Pune, Nigdi Pradhikar India	Due Net 90

Pos. **item**	**Produkt** **Product**	**Beschreibung** **Description**	**Versanddatum** **Ship date**	**Anzahl** **QTY**	**Einheit** **Unit**	**Preis/Einh.** **Price/Unit**	**Preis** **Price**
10	**AD_RP300**	**ASSA ABLOY RP300**	**2021-05-25**	**1.000**	**ST**	**5,746.00**	**5,746.00**

Serien-Nr. 2620007711

Door type	High-speed roller door RapidProtect 300
Daylight width	1.800 mm
Daylight height	2.200 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Right
Motor Position	Right
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Plus
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.200 mm

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Display delivered separately, not mounted
Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	2800X580X470
Dimension packing 2 LxWxH	1000X800X770

20	**AD_RP300**	**ASSA ABLOY RP300**	**2021-05-25**	**1.000**	**ST**	**5,746.00**	**5,746.00**

Serien-Nr. 2620007712

Door type	High-speed roller door RapidProtect 300
Daylight width	1.800 mm
Daylight height	2.200 mm
Door control system	MCC VectorControl - frequency converter control system for a dynamic, smooth door movement, located close to the drive unit
Max. Opening Speed	2,3 m/s
Max. Closing Speed	1,7 m/s
Control box position	Mounted next to the drive unit
Control system position	Left
Motor Position	Left
Wind class	1
Side frame version	Aluminium
Bottom plate	Delivered without bottom plates
Bottom profile	Aluminium
Safety contact edge	Pre running photocell at the bottom profile
Photocell	With photocell
Crank	With crank for manual operation
Top roll material	Aluminum
Door curtain	RollTex Plus
Door curtain colour	Orange, similar to RAL 2009
Silicone free	Silicone free
Window type	Window 700X500 mm, type anti UV
Window Quantity	1
Height:bott.edge to bott.prof.	1.200 mm
Motor cover	Motor cover powder coated standard
Top roll cover	Top roll cover made of aluminium
MCC type	Standard version
MCC display type	Display delivered separately, not mounted

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm

Pos. item	Produkt Product	Beschreibung Description	Versanddatum Ship date	Anzahl QTY	Einheit Unit	Preis/Einh. Price/Unit	Preis Price

Power supply	400 V, 3-phase
Frequency	50 Hz
Main switch	With main switch
Interface cable length	3.000 mm
Mains connection cable length	3.000 mm
Dry contact	Dry contacts for signal door open / closed and door in operation
Interface card	Interface card delivered separately, installation on site in the customer control box
Safety limit switch (MP)	Schmersal on 1 side with relay for cat. 4
Cable marking	Including cable and component marking
Documentation language	English
Documenation door	English
Documentation control system	English
Wiring plan	English
MCC display language	English
CE - Sign	Yes
Packing	Box, heat treated
Warranty	1 Year
Dimension packing 1 LxWxH	2800X580X470
Dimension packing 2 LxWxH	1000X800X770

Warenwert/Value of goods **11,492.00**

Summe/Total **EUR** **11,492.00**

Wir danken für Ihren Auftrag Thank you for the order
Mit freundlichen Grüßen Best regards
Albany Door Systems GmbH

(Automatisch erstellt, daher ohne Unterschrift gültig
Written automatically, valid without signature)

Dem Auftrag liegen unsere allgemeinen, zur Zeit gültigen Verkaufsbedingungen zugrunde, die auch für alle weiteren Verträge Gültigkeit haben.
The order is based on our current general terms of sales, which will as well be applicable for all further contracts.

Die gesetzlichen durch die DSGVO geforderten Informationen zum Umgang mit Ihren personenbezogenen Daten erhalten Sie unter dem folgenden Link: https://goo.gl/qGzSw5

Sollten Sie keinen Zugang zum Internet haben, senden wir Ihnen gerne die Informationen postalisch zu. Bitte sprechen Sie uns ggf. unter Telefon: 02941/766-622 darauf an.

ASSA ABLOY Entrance Systems

Albany Door Systems GmbH
Am Mondschein 25
DE-59557 Lippstadt
www.assaabloyentrance.com

Phone:+49 (0) 2941/766-0
Fax: +49 (0) 2941/766-294
Service: +49(0) 2941/766555
verkauf.de.albany@assaabloy.com

Bank details
Commerzbank AG
Bank code: 200 400 00
Account: 0402 4014 00

VAT No.: CZ 682 534 558
SWIFT:COBADEFFXXX
IBAN-No: DE 09 2004 0000 0402 4014 00
Reg court Paderborn: HR B 61 06

Management:
Christopher Norbye
Marina Lindholm