AEGIS INFRASOLUTIONS (INDIA) PVT LTD		
Dock Levellers _Technical Specification		
Sr. No.	**Description**	**Specifications**
1	**Capacity**	**9 ton Capacity**
2	**Dock operation mode**	**AC power pack hydraulically operated**
3	**Lip operation mode**	**Hydraulic**
4	**Operation control**	**Through panel**
5	**Loading platform height from road**	**1200 mm**
6	**Travel above & below dock level**	**(+) 300 / (-) 200 mm**
8	**Platform Size (W x L)**	**2500 mm x 3000 mm**
9	**Lip size (W x L)**	**2500 x 400 mm**
10	**Shut Height**	**560 mm**
11	**Maximum slope can be achieved**	**10%**
13	**Clear Pit dimensions (W x L x D)**	**(W) 2525mm x (L)3025 mm x (D)565 mm**
14	**Hydraulic power pack**	**Standard**
15	**Driver type**	**Direct by electric Motor**
16	**Motor Ratings**	**1 H.P Motor & Control Panel - Flame proof**
17	**Pump design flow**	**2.5 LPM**
18	**Pump pressure**	**120 bar Operating 200 bar Max.**
19	**Safety valve set pressure**	**120 Kg/cm^2**
20	**Pump Type**	**Gear**
21	**Volume of oil receiver**	**7 Lit**
22	**No Of Deck cylinder**	**2 No**
23	**Lip Cylinder**	**1 No**
24	**Dock Bumper**	**1 Pair included**

1	**1. HYDROPACK AND PANEL SHOULD BE MOUNTED SEPARATELY NEAR THE DOCKLEVELLER (NOT BELOW)** **2..PLEASE NOTE THAT THE CAPACITY OF DOCK LEVELER CONSIDERED IS THE CAPACITYAFTER THE LIP IS RESTED ON THE VEHICLE.** **3.CYLINDERS PROVIDED ARE INTENDENT TO BE USED ONLY FOR LIFTING OF BARE DOCK & CAN NOT LIFT OTHER LOADS.**
2	**Motor - Flameproof - Crompton Greaves make**
3	**Control Panel - Flame proof**