Ultrasonic Thickness Gauges High-precision Model No. : 1600



Ultrasonic Thickness Gauges are designed to improve safety and ensure reliability of material subject to corrosion or erosion.

Corrosion gauges with their dual-element transducers are the primary inspection tool used to measure the remaining walls of components such as pipelines, pressure vessels, storagetanks, and numerous other applications.

Precision gauges use single-element transducers to provide the thinnest range and highest degree of accuracy possible. Common applications include metals and a variety of non-metals (i.e. glass, ceramic, plastic, etc.)

Measuring Range	**0.65 mm – 400mm (upto 500mm) (in steel)**
Sound Velocity	1000~9999 m/s
Resolution	**0.01mm/0.1mm or 0.001/0.01" selectable**
Units	mm/inch (selectable)
Memory	**Upto 2000 Groups (up to 99 Values for each file)**
Accuracy	± (0.5%Thickness+0.04) mm
Alarm	preset upper and lower limit
Work voltage	3V(2 AA alkaline battaries)
Work mode	Single point and scan
Interface port	**USB**
Dimensions	136 x 72 x 20mm
Weight	177 g
Display	3.5 digit LCD with EL backlight
Continuous working period	280 hours (with EL backlight off)
Probe	**6mm and 10 mm**

99 INSTRUMENTS

Lower Limit of Pipe Thickness Measurement :- Φ 15mm × 1.0mm (Φ 6mm probe)

Probe Type :- 1) 7.5M,Φ6mm :- (0.65～25mm) measure
2) 5M,Φ10mm :- (0.7～400mm) measure

• **Standard Delivery :** Main Unit, TWO test Probes, Data Cable, Software, Coupling oil, Battery, Operation Manual

A PRODUCTS BY : 99 INSTRUMENTS
204, Gayatri shopping center, opp. GPCB, near telephone exchange, GIDC, Vapi-396195,
Tel : 0260-6536699 Mo: 07778808981 Email : Sales@99instruments.co.in