SKB STORAGE INDUSTRIES SDN. BHD. (557922-U)
(A Subsidiary of SKB Shutters Corporation Berhad)
Lot 22 Jalan Teknologi, Taman Sains Selangor, Kota Damansara, 47810 Petaling Jaya, Selangor, Malaysia.
Tel : (60) 3-6157 2277 (12 lines) Fax : (60) 3-6157 2211
website : www.skb-shutters.com
Reg. Trademark No. 85/B03843
ISO 9001-2008 CERTIFIED

Quotation

Quotation Ref: SKB-2011-838
Date : 9-Nov-20
Quote Validity: 30 days
Delivery : 30 Days after drawing approved and payment.
Payment Term : 30% Down payment upon order confirmation.
70% Full payment prior to collection of goods.
(All down payment made are non-refundable)
Price : Supply Ex-Work in USD
(Collected by Container Bases (FCL) OR LCL)

Attn: Mr.Smita Khare
To : NIHVA Technologies Pvt Ltd
Add : 187, G-Block, Thermax Chowk, MIDC, Chichwad, Pune-411019, India.
Tel : 00963 799 1333
Project : Supply Only

Supply For: **SKB High Quality 2 Hrs Fire Shutters (BS476)**
Shutter Slats : Zinc Coated Steel Solid Slats
Powder coated to RAL colour manufacturer std
Slat Thickness: **1.0mm thick**
Shutter Design : SKB -A7
Shutter Guide : Galvanise Steel G65, 3mm thick
Bottom Bar : SKB T-120
Weather Seal : Excluded
Safety Sensor : Excluded
Push Button Switch: SKB standard
Operated By : Motorise 230Volt 1P 50Hz with Manual override chain
Fire Mode : Fire Shutter will auto close via 71 C degrees Thermal Fusible Link
Fire Shutter will auto close by gravity force when received 24V DC fire signal from control room.
Fire Signal of 24VDC 400mA are required

Standard Specifications:
Box Covers of Zinc Coated Steel Finish
Box Frame Standard, Single powder coated.
Standard Installation - Behind R.C. Beam.

For Motor Operated Unit:
Motor comes with one unit push button switch & manual overide.

***WITHOUT MOTOR COVER & SPROCKET COVER**

No.	Width (mm)	Height (mm)	Qty (Units)	Operated By	Unit Price (USD)	Total Price (USD)
1	4000	4000	6	SKB 500 Motor, 1 Phase + ERA + TFL	1,755	10,530
2	3400	1710	1	SKB 400 Motor, 1 Phase + ERA + TFL	1,088	1,088
3	4000	2200	8	SKB 400 Motor, 1 Phase + ERA + TFL	1,210	9,680
		Total Units	15	**Total Ex-Factory Price (USD)**		**$ 21,298**

Terms and Conditions :

(2) Remote Control and bottom safety air sensor are **Excluded** / **Optional Upon Request**.
(3) Steel Crate USD150/unit below 6 meter; USD250 above 6 meters for LCL Collection.
(4) Without Windlock, maximum windload is 20 ¬ 30km/hours ; pressure is 6¬9kgs/m2.
(5) SKB Standard Colour, Outdoor: RAL9010 (White), RAL7025 (Grey) Only
Shutter shall powder coated minimum 50 micron, and, minimum 20 micron to 50 micron for shutter box.
Non standard RAL Powder are chargeable as additional cost with minimum requirement of 200kg by supplier
(6) Shop Drawing supply within 7 days after received Firm Purchase Order.
(7) Buyer is requested to sign and approve the drawing submitted in order to commence fabrications.
(8) All roller shutter offers shall be supplied with Galvanized Steel Guide Rails as standard unless mentioned otherwise in this quotation.
(9) All motorized roller shutters is designed with Open & Close travel speed of approximately 50mm to 70mm per second as standard.
(10) All power point with Terminal or Isolater Switch to be provided by buyer to each motor position, 300mm from motor.
(11) The roller shutters offered with Standard Operation Design. Any extra safety features such as Automatic Reset Device, TFL. **Delay Timer Closing, Infra-Red Safety Sensor, Shutter Safety Brake Arrester, Powerless Assisted Lift Up System, PVC Fir** at Guide Rail, Anti Wind Locking System, DC Power Back Up Motor, Wireless Remote Control System are charged separately upo
(12) All Shutter box Covers shall be of Galvanized surface treated as standard unless indicated separately in writing, signed and approv in the quotation.
(13) All Roller Shutter's Box Cover includes Back & Bottom Galvanised Finishing 0.8mm Thick Steel Covers as standard.
(14) All Roller Shutter are designed for installation Behind Wall or Face Fixed Type as standard. For Between-wall design opening and Hanging Steel Angle Installation under floor slab, additional charges is applicable.
(15) Items requested and quoted for powder coating finishing are applicable to slat, bottom bar & shutter box only.
(16) Fabrications is solely based on Approved Shop Drawings Only. No site measurement will be taken. All amendments and modificati on items which had commenced fabrication shall be chargeable and written notice is required for the alteration and modification.
(17) All SKB Roller Shutters includes a warranty of **12 months against manufacturing defects on Mechanical part and 12 months against manufacturing defect on Electrical parts from date of Shipment** . Defect arrising from negligence or vandalism is not under warranty claims and are chargeable to recover its condition. The Warranty does not cover for any parts replacement and no extension of warranty period shall be allowed to the being replace.
(18) Product Warranty is Void if any modification is carried out by buyer and it does not include any Lightning Strike or act of God dama to the electrical system of the controls.
(19) Once production commenced, any changes by buyer shall treat as variation order and must inform SKB by written instruction from buyer with company letter head or personal order with IC No. and Name with signature.
(20) This quotation is subject to the terms & conditions as specified above
(21) Delivery Date shall be given only after buyer signed and approved the submitted drawing for Production.
(22) Container size and changes are subject to change depend upon space.
(23) Compensation clause (Quotation) -Please note that in the Events the buyer cancels and order after order is confirm to us, it is binding to the buyer to pay a compensation of 30% of the order value

Marilyn
For NIHVA Technologies Pvt Ltd

SKB Storage Industries Sdn Bhd
Marilyn Lai
email:marilyn@skb.com.my
Overseas Sales Department

Buyer's Signature & Date