Technical Specifications Against PO NO NVA 641		
Sr. No	**Description**	**Albany make Machine Protection Door RP300**
1	**Door version:**	Vertical Rapid Roller Door for machine protection.
2	**Side Frames:**	Aluminum anodized two parts, to have easy access to switches and service.
3	**Door blade:**	Rolltex Plus Curtain
4	**Bottom beam**	Aluminium anodized.
5	**Drive unit:**	Drive unit IP 55, RH as an option, with control cable (standard length = height of door)
6	**Opening / closing speed:**	Approx. max. 2,4 / 1,7 m/s
7	**Control system:**	MCC Frequency converterVector Control for opening/closing speed up to 2,4 / 1,4 m/s for door with safety
8	**Power suppy:**	3L(N)PE 380/400/415/440/460 and 480 V, 50/60 Hz
9	**Safety features:**	Safety edge with cable chain integrated in side frames, door line photocell (Transmitter / Receiver) inside side
10	**Safety limit switch:**	1 Schmersal safety limit switch PL e EN ISO 13849-1, SIL 3 EN 62061 on drive side integrated in the side frame to
11	**Window Type**	700 x 500 mm Anti UV Type
12	**Display**	Display "Up-Stop-Down"
13	**Motor Position**	Right Hand Side
14	**Interface Card**	MCC without display unit, with combibox in plastic (175x250x150 mm) with interface card and main switch
15	**Pre - running Photocell**	Bottom beam with pre-running photocell (without contact edge) with cable chain inside side frames (only
16	**Accessories**	Top Cover & Motor Cover