

| Type | Dock Levelers | PL. indicate your requirement |
|---|---|---|
| Make | NIHVA | |
| Capacity in KG | 6000/9000/10000/12000/15000 | |
| Platform Width in MM | 2000 | |
| Platform Length in MM | 2500 | |
| Lip Width in MM | 2000 | |
| Lip Length in MM | 400 | |
| Working Length (Including Lip) in MM | Direct by electric Motor | |
| Overall Length in MM | 2900 | |
| Overall Width in MM | 2000 | |
| Shut Height in MM | 480 | |
| Working Range UP/Down in MM | (+) 300 / (-) 150 | |
| Loading Platform Height from Road in MM | 1250 | |
| Dock Operation Mode | AC Power Pack Hydraulically Operated | |
| Lip Operation Mode | Hydraulically Operated | |
| Operation Control | Through Panel | |
| Power Pack | Hydraulic | |
| Drive Type | Direct by electric Motor | |
| Motor Ratings HP | 1HP | |
| Pump Design Flow (LPM) | 2.5 | |
| Pump Type | Gear | |
| Safety Valve Set Pressure (Kg/Sq. Cm) | 120 | |
| Volume of Oil Receiver (Liter) | 7 | |
| No. Of Deck Cylinder | 2 | |
| No. Of Lip Cylinder | 1 | |
| Power Supply | 3 Phase | |
| Maximum Gradient | 1:10 | |
| Clear Pit Dimensions (W x L x D) MM | 2050 X 2550 X 485 | |
| Service Weight in Kg (Approx.) | 900 | |