Preventive Maintenance Manufacturer's Specification

ASSA ABLOY Entrance Systems

Enhance the durability of your High Performance Door Albany RR500

Key benefit

Safety

Cost-Savings

Just as a car's tires and oil must be changed regularly, your Albany High Performance Doors have key components that periodically need replacing. Whether it's a spring or a sprocket, changing them before they break is an integral part of Pro-Active Care.

We at ASSA ABLOY Entrance Systems believe in Pro-Active Care. Letting us replace components before they fail keeps your warranty valid and your equipment compliant with regulations. Even more importantly, it ensures the safety and functionality of your equipment, so that you can avoid accidents and losses in productivity.



Instructions for table usage:

Qualified person
The manufacturer's recommendation for exchange of components is subject to the findings of a qualified person. We strongly recommend that inspections are performed by a qualified person within the recommended service intervals (according to the user manual of the door).

Recommendations for exchange
The manufacturer's recommendations are based on a door with average size, installed under regular environmental conditions. Doors dimensioned close to maximum size of the door type or doors installed in harsh environmental conditions, need particular observation by a qualified person as the recommended intervals might be shorter.

Components specified as wear and tear related do not have a recommended exchange interval, indications for exchange or wear can be derived from the corresponding fact sheets.

Subject to technical modifications without notice. Errors and omissions excepted.

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization

Preventive Maintenance
Manufacturer's Specification

ASSA ABLOY

Albany RR500

Product group	Description	100.000 cycles or 2 years	250.000 cycles	250.000 cycles or 3 years	300.000 cycles or 5 years	500.000 cycles or 5 years	500.000 cycles	1.000.000 cycles	1 year	10 years	wear / tear related
Actuators	Photocell receiver + 20 m cable									●	
	Photocell transmitter + 20 m cable									●	
Safety	Wireless safety system receiver					●					
Counterbalancing	Belt counterweight 7000mm (only non-drive side)		●								
Curtain tension	Springs mounting kit	●									
Curtain	Curtain PVC with safety edge										●
	Curtain NomaTex with safety edge										●
Bottom profile	Battery for wireless safety system								●		
	Rubber profile complete RR500				●						
Sliding/Guiding	Set plastic guiding headplate right / left	●									
	Sliding rail plastic, length 5600mm			●							
	Sliding rail plastic, length 150mm			●							
	Lubricant cartridge (300 ml)								●		
Drive unit	limit switch block, 6 contacts incl. Cams									●	
	Gear motor with MCC encoder (DW≤5000 mm)							●			
	Gear motor with MCC encoder (DW>5000 mm)							●			
Brake	Brake - frequency converter							●			
Encoder	Encoder									●	
Damper	Torque arm						●				

Technical data subject to change without notice

© ASSA ABLOY Entrance Systems AB PL.MAN/Albany RR500/DEU.EN-1.1/1606 / 64 100 703

ASSA ABLOY ENTRANCE SYSTEMS
Maintenance & Modernization