

Subspace Designs and Error-Correcting Codes

Sayak Chakrabarti

Subspace Designs

Definition (Subspace Designs [GK16, GX13])

Subspace designs are defined as collections of subspaces $\{H_1, H_2, \dots, H_M\}$, where $H_i \subseteq \mathbb{F}_q^m \forall i \in [M]$, with the property that any "low dimensional" subspace W will have less number of intersecting points with H_i 's

Error-Correcting Codes


Definition (Error-Correcting Codes)

An error-correcting code, for a distance $\delta \in [0, 1]$, is a function $E : \{0, 1\}^n \mapsto \{0, 1\}^m$ such that $\forall x \neq y, x, y \in \{0, 1\}^n$, $\Delta(E(x), E(y)) \geq \delta$.

Error-Correcting Codes

Definition (Error-Correcting Codes)

An error-correcting code, for a distance $\delta \in [0, 1]$, is a function $E : \{0, 1\}^n \mapsto \{0, 1\}^m$ such that $\forall x \neq y, x, y \in \{0, 1\}^n$, $\Delta(E(x), E(y)) \geq \delta$.



Relation to Computational Complexity Theory

- Subspace designs relate to error-correcting codes [GK16, GX13].

Relation to Computational Complexity Theory

- Subspace designs relate to error-correcting codes [GK16, GX13].
- Error-Correcting codes: Hardness of Approximations (Reducing Hardness) [AB09].

Relation to Computational Complexity Theory

- Subspace designs relate to error-correcting codes [GK16, GX13].
- Error-Correcting codes: Hardness of Approximations (Reducing Hardness) [AB09].
- Hardness of Approximations: Pseudorandomness [NW94]

Relation to Computational Complexity Theory

- Subspace designs relate to error-correcting codes [GK16, GX13].
- Error-Correcting codes: Hardness of Approximations (Reducing Hardness) [AB09].
- Hardness of Approximations: Pseudorandomness [NW94]




Figure 1: Relation between Hardness and Derandomization using ECC [AB09]

Error-Correcting Codes: Reed-Solomon Codes

Definition (Reed-Solomon Codes [WB99])

For a finite field \mathbb{F} , and integers $k \leq n \leq |\mathbb{F}|$, Reed-Solomon code is defined as a function $RS : \mathbb{F}^k \rightarrow \mathbb{F}^n$, such that on input $\bar{a} = (a_0, a_1, \dots, a_{k-1}) \in \mathbb{F}^k$, it outputs $RS(\bar{a}) = (z_0, z_1, \dots, z_{n-1})$, where $z_j = \sum_{i=0}^{k-1} a_i f_j^i$, for distinct $f_j \in \mathbb{F}$.

Error-Correcting Codes: Reed-Solomon Codes

Definition (Reed-Solomon Codes [WB99])

For a finite field \mathbb{F} , and integers $k \leq n \leq |\mathbb{F}|$, Reed-Solomon code is defined as a function $RS : \mathbb{F}^k \rightarrow \mathbb{F}^n$, such that on input $\bar{a} = (a_0, a_1, \dots, a_{k-1}) \in \mathbb{F}^k$, it outputs $RS(\bar{a}) = (z_0, z_1, \dots, z_{n-1})$, where $z_j = \sum_{i=0}^{k-1} a_i f_j^i$, for distinct $f_j \in \mathbb{F}$.

a_0	a_1	a_2	\dots	a_{n-1}
-------	-------	-------	---------	-----------

Error-Correcting Codes: Reed-Solomon Codes

Definition (Reed-Solomon Codes [WB99])

For a finite field \mathbb{F} , and integers $k \leq n \leq |\mathbb{F}|$, Reed-Solomon code is defined as a function $RS : \mathbb{F}^k \rightarrow \mathbb{F}^n$, such that on input $\bar{a} = (a_0, a_1, \dots, a_{k-1}) \in \mathbb{F}^k$, it outputs $RS(\bar{a}) = (z_0, z_1, \dots, z_{n-1})$, where $z_j = \sum_{i=0}^{k-1} a_i f_j^i$, for distinct $f_j \in \mathbb{F}$.

a_0	a_1	a_2	\dots	a_{n-1}
-------	-------	-------	---------	-----------

- Efficient Decoding [WB86]: Error locator polynomial

$$Q(x) = \prod_{j=1}^t (x - e_{i_j})$$

Error-Correcting Codes: Reed-Solomon Codes

Definition (Reed-Solomon Codes [WB99])

For a finite field \mathbb{F} , and integers $k \leq n \leq |\mathbb{F}|$, Reed-Solomon code is defined as a function $RS : \mathbb{F}^k \rightarrow \mathbb{F}^n$, such that on input $\bar{a} = (a_0, a_1, \dots, a_{k-1}) \in \mathbb{F}^k$, it outputs $RS(\bar{a}) = (z_0, z_1, \dots, z_{n-1})$, where $z_j = \sum_{i=0}^{k-1} a_i f_j^i$, for distinct $f_j \in \mathbb{F}$.

a_0	a_1	a_2	\dots	a_{n-1}
-------	-------	-------	---------	-----------

- Efficient Decoding [WB86]: Error locator polynomial

$$Q(x) = \prod_{j=1}^t (x - e_j)$$

- $P(e_j)Q(e_j) = c'_j Q(e_j)$

Error-Correcting Codes: Reed-Solomon Codes

Definition (Reed-Solomon Codes [WB99])

For a finite field \mathbb{F} , and integers $k \leq n \leq |\mathbb{F}|$, Reed-Solomon code is defined as a function $RS : \mathbb{F}^k \rightarrow \mathbb{F}^n$, such that on input $\bar{a} = (a_0, a_1, \dots, a_{k-1}) \in \mathbb{F}^k$, it outputs $RS(\bar{a}) = (z_0, z_1, \dots, z_{n-1})$, where $z_j = \sum_{i=0}^{k-1} a_i f_j^i$, for distinct $f_j \in \mathbb{F}$.

a_0	a_1	a_2	\dots	a_{n-1}
-------	-------	-------	---------	-----------

- Efficient Decoding [WB86]: Error locator polynomial
 $Q(x) = \prod_{j=1}^t (x - e_j)$
- $P(e_j)Q(e_j) = c_j'Q(e_j)$
- Error: $< 50\%$

Error-Correcting Codes: List Decoding

- **List Decoding:** Crossing the 50% barrier [[Sud97](#)].

Error-Correcting Codes: List Decoding

- **List Decoding:** Crossing the 50% barrier [Sud97].
- Bivariate error locator polynomial $Q(x, y)$ such that $Q(e_j, c'_j) = 0$
 $\forall 0 \leq j \leq n - 1$.
- Linear equation solving such that $R(x) = Q(x, P(x)) = 0$ [Sud96].

Error-Correcting Codes: Algebraic Geometric Codes

Definition (AG Codes [Gop82, Chu04])

Given a non-singular projective curve \mathbf{X} over \mathbb{F}_q^m , let $\mathcal{P} = \{P_1, P_2, \dots, P_n\} \subset \mathbf{X}(\mathbb{F}_q)$ be a collection of points. Let a divisor D be such that $\mathcal{P} \cap \text{supp}(D) = \emptyset$.

Error-Correcting Codes: Algebraic Geometric Codes

Definition (AG Codes [Gop82, Chu04])

Given a non-singular projective curve \mathbf{X} over \mathbb{F}_q^m , let $\mathcal{P} = \{P_1, P_2, \dots, P_n\} \subset \mathbf{X}(\mathbb{F}_q)$ be a collection of points. Let a divisor D be such that $\mathcal{P} \cap \text{supp}(D) = \emptyset$. Riemann-Roch Theorem gives a unique vector space $L(D)$.

Error-Correcting Codes: Algebraic Geometric Codes

Definition (AG Codes [Gop82, Chu04])

Given a non-singular projective curve \mathbf{X} over \mathbb{F}_q , let $\mathcal{P} = \{P_1, P_2, \dots, P_n\} \subset \mathbf{X}(\mathbb{F}_q)$ be a collection of points. Let a divisor D be such that $\mathcal{P} \cap \text{supp}(D) = \emptyset$. Riemann-Roch Theorem gives a unique vector space $L(D)$.

$$C(X, \mathcal{P}, D) = \{(f(P_1), f(P_2), \dots, f(P_n)) \mid f \in L(D)\} \subset \mathbb{F}_q^n.$$

Subspace Designs

- Collection of subspaces $\mathcal{H} = \{H_1, H_2, \dots, H_M\} \subset \mathbb{F}_q^m$.

Subspace Designs

- Collection of subspaces $\mathcal{H} = \{H_1, H_2, \dots, H_M\} \subset \mathbb{F}_q^m$.
- (s, A) -subspace: Every s -dimensional subspace $W \subset \mathbb{F}_q^m$ intersects with at most A -many H_i 's non-trivially.

Subspace Designs

- Collection of subspaces $\mathcal{H} = \{H_1, H_2, \dots, H_M\} \subset \mathbb{F}_q^m$.
- (s, A) -subspace: Every s -dimensional subspace $W \subset \mathbb{F}_q^m$ intersects with at most A -many H_i 's non-trivially.
- "Well Spread-out property" [GK16]: random collection of good subspaces \rightarrow good subspaces.

Subspace Designs: Motivation

- Output size in list-decoding algorithms of RS and AG codes.

Subspace Designs: Motivation

- Output size in list-decoding algorithms of RS and AG codes.
- [GX13]: List decoding solutions of RS code f evaluated at $\mathbb{F}_q \mapsto$ pinned to a linear subspace.

Subspace Designs: Motivation

- Output size in list-decoding algorithms of RS and AG codes.
- [GX13]: List decoding solutions of RS code f evaluated at $\mathbb{F}_q \mapsto$ pinned to a linear subspace.
 - Solution polynomials: $f(x) = f_0 + f_1x + \cdots + f_{k-1}x^{k-1}$
 - $f_i \in W + A_i(f_0, \dots, f_{i-1}), \forall i \in 0, 1, \dots, k-1$.

Subspace Designs: Motivation

- Output size in list-decoding algorithms of RS and AG codes.
- [GX13]: List decoding solutions of RS code f evaluated at $\mathbb{F}_q \mapsto$ pinned to a linear subspace.
 - Solution polynomials: $f(x) = f_0 + f_1x + \cdots + f_{k-1}x^{k-1}$
 - $f_i \in W + A_i(f_0, \dots, f_{i-1}), \forall i \in 0, 1, \dots, k-1.$
 - Radius $\frac{s}{s+1}(n-k), \dim(W) = s-1.$

Subspace Designs: Motivation

- Output size in list-decoding algorithms of RS and AG codes.
- [GX13]: List decoding solutions of RS code f evaluated at $\mathbb{F}_q \mapsto$ pinned to a linear subspace.
 - Solution polynomials: $f(x) = f_0 + f_1x + \cdots + f_{k-1}x^{k-1}$
 - $f_i \in W + A_i(f_0, \dots, f_{i-1}), \forall i \in 0, 1, \dots, k-1.$
 - Radius $\frac{s}{s+1}(n-k), \dim(W) = s-1.$
- Also gave a family of AG codes whose list decoded solutions are pinned down to a linear subspace.

Subspace Designs: Motivation

- Messages $f_i \in H_i$, H_i 's are \mathbb{F}_q subspaces of \mathbb{F}_{q^m} .

Subspace Designs: Motivation

- Messages $f_i \in H_i$, H_i 's are \mathbb{F}_q subspaces of \mathbb{F}_{q^m} .
- Dimensions of solutions to f_i 's of given form: $\sum_{i=0}^{k-1} \dim(W \cap H_i)$.

Subspace Designs: Motivation

- Messages $f_i \in H_i$, H_i 's are \mathbb{F}_q subspaces of \mathbb{F}_{q^m} .
- Dimensions of solutions to f_i 's of given form: $\sum_{i=0}^{k-1} \dim(W \cap H_i)$.

Theorem ([GK16])

For every $R \in (0, 1)$, we can construct a family of ECCs of rate R on an alphabet set of size $(1/\epsilon)^{\mathcal{O}(1/\epsilon^2)}$. This can be list decoded in $n^{\mathcal{O}(1)}$ time with $(1 - R - \epsilon)$ errors, which outputs a list of size at most $\exp_{1/\epsilon}(\exp_{1/\epsilon}(\exp(\mathcal{O}(\log^ n))))$.*

Subspace Designs

Definition (Weak Subspace Designs [GK16])

A collection of subspaces $\mathcal{H} \subset \mathbb{F}_q^m$ is called an (s, A) -weak subspace design if, for every linear subspace $W \subset \mathbb{F}_q^m$ of dimension s , we have

$$|\{i \in [M] \mid \dim_{\mathbb{F}_q}(W \cap H_i) > 0\}| \leq A \quad (1)$$

Subspace Designs

Definition (Weak Subspace Designs [GK16])

A collection of subspaces $\mathcal{H} \subset \mathbb{F}_q^m$ is called an (s, A) -weak subspace design if, for every linear subspace $W \subset \mathbb{F}_q^m$ of dimension s , we have

$$|\{i \in [M] \mid \dim_{\mathbb{F}_q}(W \cap H_i) > 0\}| \leq A \quad (1)$$

Definition (Strong Subspace Designs [GK16])

Similarly, a collection of subspaces \mathcal{H} is called an (s, A) -weak subspace design if, for every linear subspace $W \subseteq \mathbb{F}_q^m$ of dimension s , we have

$$\sum_{i=1}^M \dim_{\mathbb{F}_q}(W \cap H_i) \leq A \quad (2)$$

- (s, A) -strong subspace $\rightarrow (s, A)$ -weak subspace.

Subspace Designs

Definition (Weak Subspace Designs [GK16])

A collection of subspaces $\mathcal{H} \subset \mathbb{F}_q^m$ is called an (s, A) -weak subspace design if, for every linear subspace $W \subset \mathbb{F}_q^m$ of dimension s , we have

$$|\{i \in [M] \mid \dim_{\mathbb{F}_q}(W \cap H_i) > 0\}| \leq A \quad (1)$$

Definition (Strong Subspace Designs [GK16])

Similarly, a collection of subspaces \mathcal{H} is called an (s, A) -weak subspace design if, for every linear subspace $W \subseteq \mathbb{F}_q^m$ of dimension s , we have

$$\sum_{i=1}^M \dim_{\mathbb{F}_q}(W \cap H_i) \leq A \quad (2)$$

- (s, A) -strong subspace $\rightarrow (s, A)$ -weak subspace.
- (s, A) -weak subspace $\rightarrow (s, sA)$ -strong subspace.

Subspace Designs

Example

- $\alpha_1, \alpha_2, \dots, \alpha_M \in \mathbb{F}_q$
- $v_{\alpha_i} = (1, \alpha_i, \alpha_i^2, \dots, \alpha_i^{m-1}) \in \mathbb{F}_q^m$
- $H_i = \{x \in \mathbb{F}_q^m \mid \langle x, v_{\alpha_i} \rangle = 0\}$

Subspace Designs

Example

- $\alpha_1, \alpha_2, \dots, \alpha_M \in \mathbb{F}_q$
- $v_{\alpha_i} = (1, \alpha_i, \alpha_i^2, \dots, \alpha_i^{m-1}) \in \mathbb{F}_q^m$
- $H_i = \{x \in \mathbb{F}_q^m \mid \langle x, v_{\alpha_i} \rangle = 0\}$
- (s, m) -strong subspace.

Subspace Designs

Goal: Explicit construction of subspaces using folded RS codes and multiplicity codes [KRZSW18].

Subspace Designs

Goal: Explicit construction of subspaces using folded RS codes and multiplicity codes [KRZSW18].

Definition (Folded Reed-Solomon Codes)

Folded Reed-Solomon codes are a variant of Reed-Solomon Codes. The polynomial f is formed as before, and the ECC outputs

$$f(x) \mapsto (f(1), f(\gamma), f(\gamma^2), \dots, f(\gamma^{n-1})),$$

a generator γ of \mathbb{F}_q^* .

Subspace Designs

Goal: Explicit construction of subspaces using folded RS codes and multiplicity codes [KRZSW18].

Definition (Folded Reed-Solomon Codes)

Folded Reed-Solomon codes are a variant of Reed-Solomon Codes. The polynomial f is formed as before, and the ECC outputs

$$f(x) \mapsto (f(1), f(\gamma), f(\gamma^2), \dots, f(\gamma^{n-1})),$$

a generator γ of \mathbb{F}_q^* .

Definition (Multiplicity Codes [KSY14])

It is an ECC similar to Reed-Muller codes where the output is $(f(\bar{a}), \frac{\partial f(\bar{a})}{\partial x}, \frac{\partial f(\bar{a})}{\partial y})$, for $\bar{a} \in \mathbb{F}_q^2$.

Wronskian: A nice algebraic tool

Definition (Classical Wronskian)

Given polynomials $f_1(x), f_2(x), \dots, f_s(x) \in \mathbb{F}[x]$, the Wronskian $W(f_1, f_2, \dots, f_s)$ is defined as:

$$\begin{bmatrix} f_1(x) & \dots & f_s(x) \\ f_1^{(1)}(x) & \dots & f_s^{(1)}(x) \\ \vdots & & \vdots \\ f_1^{(s-1)}(x) & \dots & f_s^{(s-1)}(x) \end{bmatrix}.$$

Wronskian: A nice algebraic tool

Definition (Classical Wronskian)

Given polynomials $f_1(x), f_2(x), \dots, f_s(x) \in \mathbb{F}[x]$, the Wronskian $W(f_1, f_2, \dots, f_s)$ is defined as:

$$\begin{bmatrix} f_1(x) & \dots & f_s(x) \\ f_1^{(1)}(x) & \dots & f_s^{(1)}(x) \\ \vdots & & \vdots \\ f_1^{(s-1)}(x) & \dots & f_s^{(s-1)}(x) \end{bmatrix}.$$

f_1, \dots, f_s are linearly independent over $\mathbb{F} \iff \det(W(f_1, \dots, f_s)) \neq 0$.

Wronskian: A nice algebraic tool

Definition (Folded Wronskian)

Given polynomials $f_1(x), f_2(x), \dots, f_s(x) \in \mathbb{F}[x]$ and $\gamma \in \mathbb{F}^*$, the folded Wronskian $W_\gamma(f_1, f_2, \dots, f_s)$ is defined as:

$$\begin{bmatrix} f_1(x) & \dots & f_s(x) \\ f_1(\gamma x) & \dots & f_s(\gamma x) \\ \vdots & & \vdots \\ f_1(\gamma^{s-1}x) & \dots & f_s(\gamma^{s-1}x) \end{bmatrix}.$$

Wronskian: A nice algebraic tool

Definition (Folded Wronskian)

Given polynomials $f_1(x), f_2(x), \dots, f_s(x) \in \mathbb{F}[x]$ and $\gamma \in \mathbb{F}^*$, the folded Wronskian $W_\gamma(f_1, f_2, \dots, f_s)$ is defined as:

$$\begin{bmatrix} f_1(x) & \dots & f_s(x) \\ f_1(\gamma x) & \dots & f_s(\gamma x) \\ \vdots & & \vdots \\ f_1(\gamma^{s-1}x) & \dots & f_s(\gamma^{s-1}x) \end{bmatrix}.$$

f_1, \dots, f_s are linearly independent over $\mathbb{F} \iff$
 $\det(W_\gamma(f_1, \dots, f_s)) \neq 0.$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Weak Subspace Construction [GK16]

For a generator γ of \mathbb{F}_q^* and some t such that $s \leq t \leq m < q$, define the set $\mathcal{F} = \{\gamma^{jt} | j \in \{0, 1, \dots, q/t\}\}$. Now, $\forall \alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]_{<m} | P(\alpha\gamma^i) = 0, \forall i \in \{0, 1, \dots, t-1\}\}$$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Weak Subspace Construction [GK16]

For a generator γ of \mathbb{F}_q^* and some t such that $s \leq t \leq m < q$, define the set $\mathcal{F} = \{\gamma^{jt} | j \in \{0, 1, \dots, q/t\}\}$. Now, $\forall \alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]_{<m} | P(\alpha\gamma^i) = 0, \forall i \in \{0, 1, \dots, t-1\}\}$$

Codimension of \mathcal{H}_α is t .

Explicit Subspace Designs: Folded Reed-Solomon Codes

Weak Subspace Construction [GK16]

For a generator γ of \mathbb{F}_q^* and some t such that $s \leq t \leq m < q$, define the set $\mathcal{F} = \{\gamma^{jt} | j \in \{0, 1, \dots, q/t\}\}$. Now, $\forall \alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]_{<m} | P(\alpha\gamma^i) = 0, \forall i \in \{0, 1, \dots, t-1\}\}$$

Codimension of \mathcal{H}_α is t .

Theorem ([GK16])

The collection of subspaces given by $\{\mathcal{H}_\alpha | \alpha \in \mathcal{F}\}$ is an $\left(s, \frac{(m-1)s}{t-s+1}\right)$ -weak subspace design.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Consider folded Wronskian of basis of W as a polynomial $L(x)$.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Consider folded Wronskian of basis of W as a polynomial $L(x)$.
- $\dim_{\mathbb{F}_q}(W \cap \mathcal{H}_\alpha) > 0 \implies L(\alpha.\gamma^i) = 0, 0 \leq i \leq t - s.$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Consider folded Wronskian of basis of W as a polynomial $L(x)$.
- $\dim_{\mathbb{F}_q}(W \cap \mathcal{H}_\alpha) > 0 \implies L(\alpha.\gamma^i) = 0, 0 \leq i \leq t - s.$
- $\deg(L) = (m - 1)s, (t - s + 1)$ -many roots.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < q$. Given a generator γ of \mathbb{F}_q^* and an $\alpha \in \mathbb{F}_{q^r}$, define

$$S_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t\} \subseteq \mathbb{F}_{q^r},$$

and

$$S'_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t - s + 1\}.$$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < q$. Given a generator γ of \mathbb{F}_q^* and an $\alpha \in \mathbb{F}_{q^r}$, define

$$S_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t\} \subseteq \mathbb{F}_{q^r},$$

and

$$S'_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t - s + 1\}.$$

Define \mathcal{F} such that

- $\mathcal{F} = \{\alpha \in \mathbb{F}_{q^r} \mid \mathbb{F}_q[\alpha] = \mathbb{F}_q\} \subset \mathbb{F}_{q^r},$
- $\alpha, \beta \in \mathcal{F}, \alpha \neq \beta \implies S_\alpha \cap S_\beta = \emptyset,$
- $|S_\alpha| = rt.$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < q$. Given a generator γ of \mathbb{F}_q^* and an $\alpha \in \mathbb{F}_{q^r}$, define

$$S_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t\} \subseteq \mathbb{F}_{q^r},$$

and

$$S'_\alpha = \{\alpha^{q^j} \gamma^i \mid 0 \leq j < r, 0 \leq i < t - s + 1\}.$$

Define \mathcal{F} such that

- $\mathcal{F} = \{\alpha \in \mathbb{F}_{q^r} \mid \mathbb{F}_q[\alpha] = \mathbb{F}_q\} \subset \mathbb{F}_{q^r},$
- $\alpha, \beta \in \mathcal{F}, \alpha \neq \beta \implies S_\alpha \cap S_\beta = \emptyset,$
- $|S_\alpha| = rt.$

We take $|\mathcal{F}| = \Omega(\frac{q^r}{rt})$. Also, $|S_\alpha| = r(t - s + 1)$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Strong Subspace Construction [GK16]

For every $\alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) \mid P(\alpha \cdot \gamma^j) \equiv 0 \ \forall j \in \{0, 1, \dots, t-1\}\}.$$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Strong Subspace Construction [GK16]

For every $\alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) | P(\alpha \cdot \gamma^j) \equiv 0 \ \forall j \in \{0, 1, \dots, t-1\}\}.$$

\mathcal{H}_α has codimension rt .

Explicit Subspace Designs: Folded Reed-Solomon Codes

Strong Subspace Construction [GK16]

For every $\alpha \in \mathcal{F}$, define the subspaces

$$\mathcal{H}_\alpha = \{P(x) \mid P(\alpha \cdot \gamma^j) \equiv 0 \ \forall j \in \{0, 1, \dots, t-1\}\}.$$

\mathcal{H}_α has codimension rt .

Theorem ([GK16])

The collection $(\mathcal{H}_\alpha)_{\alpha \in \mathcal{F}}$ is an $\left(s, \frac{(m-1)s}{r(t-s+1)}\right)$ -strong subspace.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its folded Wronskian $M(x)$.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its folded Wronskian $M(x)$.
- The matrix $M(\alpha) \in \mathbb{F}_{q^r}^{t \times s}$ satisfies $\text{rank}(M(\alpha)) \leq s - \dim_{\mathbb{F}_q}(W \cap \mathcal{H}_\alpha)$.

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its folded Wronskian $M(x)$.
- The matrix $M(\alpha) \in \mathbb{F}_{q^r}^{t \times s}$ satisfies $\text{rank}(M(\alpha)) \leq s - \dim_{\mathbb{F}_q}(W \cap \mathcal{H}_\alpha)$.
- For each $\beta \in S'_\alpha$, we have $\dim(W \cap H_\alpha) \leq \text{mult}(L, \beta) \leq s(m-1)$

Explicit Subspace Designs: Folded Reed-Solomon Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its folded Wronskian $M(x)$.
- The matrix $M(\alpha) \in \mathbb{F}_{q^r}^{t \times s}$ satisfies $\text{rank}(M(\alpha)) \leq s - \dim_{\mathbb{F}_q}(W \cap \mathcal{H}_\alpha)$.
- For each $\beta \in S'_\alpha$, we have $\dim(W \cap H_\alpha) \leq \text{mult}(L, \beta) \leq s(m-1)$
- Sum over all α and β .

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathbb{F}_q$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathbb{F}_q$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

\mathcal{H}_α has codimension t .

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathbb{F}_q$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

\mathcal{H}_α has codimension t .

Theorem ([GK16])

The collection $(\mathcal{H}_\alpha)_{\alpha \in \mathbb{F}}$ is an $\left(s, \frac{(m-1)s}{(t-s+1)}\right)$ -strong subspace.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.
- $\text{rank}(M(\alpha)) = s - \dim(W \cap \mathcal{H}_\alpha)$.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.
- $\text{rank}(M(\alpha)) = s - \dim(W \cap \mathcal{H}_\alpha)$.
- $\text{mult}(L, \alpha) \geq (t - s + 1) \cdot \dim(W \cap \mathcal{H}_\alpha)$.

Explicit Subspace Designs: Multiplicity Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < \text{char}(\mathbb{F}_q)$.

- Again, we form $\mathcal{F}_0 \subseteq \mathbb{F}_{q^r}$ s.t. $\mathbb{F}_q[\alpha] = \mathbb{F}_{q^r}$.

Explicit Subspace Designs: Multiplicity Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < \text{char}(\mathbb{F}_q)$.

- Again, we form $\mathcal{F}_0 \subseteq \mathbb{F}_{q^r}$ s.t. $\mathbb{F}_q[\alpha] = \mathbb{F}_{q^r}$.
- We have $|\mathcal{F}_0| = q^r(1 - o(1))$. Partition \mathcal{F}_0 into r sets such that they are mutual conjugates over \mathbb{F}_q .

Explicit Subspace Designs: Multiplicity Codes

Improving the Construction

s, t, r, q, m are parameters such that $s \leq t \leq m < \text{char}(\mathbb{F}_q)$.

- Again, we form $\mathcal{F}_0 \subseteq \mathbb{F}_{q^r}$ s.t. $\mathbb{F}_q[\alpha] = \mathbb{F}_{q^r}$.
- We have $|\mathcal{F}_0| = q^r(1 - o(1))$. Partition \mathcal{F}_0 into r sets such that they are mutual conjugates over \mathbb{F}_q .
- Choose one element from each of these sets to form \mathcal{F} with $|\mathcal{F}| \approx q^r/r$

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathcal{F}$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathcal{F}$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

\mathcal{H}_α has codimension t .

Explicit Subspace Designs: Multiplicity Codes

Strong Subspace Construction [GK16]

For each $\alpha \in \mathcal{F}$, consider the subspaces

$$\mathcal{H}_\alpha = \{P(x) \in \mathbb{F}_q[x]^{<m} \mid \text{mult}(P, \alpha) \geq t\}$$

\mathcal{H}_α has codimension t .

Theorem ([GK16])

The collection $(\mathcal{H}_\alpha)_{\alpha \in \mathcal{F}}$ is an $\left(s, \frac{(m-1)s}{r(t-s+1)}\right)$ -strong subspace.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.
- $\text{rank}(M(\alpha)) \leq s - \dim(W \cap \mathcal{H}_\alpha)$.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.
- $\text{rank}(M(\alpha)) \leq s - \dim(W \cap \mathcal{H}_\alpha)$.
- $\text{mult}(L, \alpha) \geq (t - s + 1) \cdot \dim(W \cap \mathcal{H}_\alpha)$.

Explicit Subspace Designs: Multiplicity Codes

Proof Idea:

- Given basis P_1, \dots, P_s of W , form its Wronskian $M(x)$.
- $W \cap \mathcal{H}_\alpha$ is nontrivial $\implies M(\alpha)$ is singular matrix.
- $\text{rank}(M(\alpha)) \leq s - \dim(W \cap \mathcal{H}_\alpha)$.
- $\text{mult}(L, \alpha) \geq (t - s + 1) \cdot \dim(W \cap \mathcal{H}_\alpha)$.
- $(m - 1) \cdot s \geq \sum_{\alpha \in \mathcal{F}_0} \text{mult}(L, \alpha) = \sum_{\alpha \in \mathcal{F}} r \cdot \text{mult}(L, \alpha) \geq r \cdot (t - s + 1) \sum_{\alpha \in \mathcal{F}} \dim(W \cap \mathcal{H}_\alpha)$.

Consequences of List Decoding

- Pick subcodes of codes using subspaces to reduce list size.

Consequences of List Decoding

- Pick subcodes of codes using subspaces to reduce list size.
- In RS, coefficients of polynomials are restricted to subspaces \mathcal{H} that form (s, A) -strong subspace designs.
- Error: $\frac{s}{s+1}(q - k)$; $\dim(H_i) = (1 - \epsilon)m$; Rate: $\frac{(1-\epsilon)k}{q}$.

Consequences of List Decoding

- Pick subcodes of codes using subspaces to reduce list size.
- In RS, coefficients of polynomials are restricted to subspaces \mathcal{H} that form (s, A) -strong subspace designs.
- Error: $\frac{s}{s+1}(q - k)$; $\dim(H_i) = (1 - \epsilon)m$; Rate: $\frac{(1-\epsilon)k}{q}$.
- Pick $s = \mathcal{O}(1/\epsilon)$, $m = \Omega(s/\epsilon)$.

Consequences of List Decoding

- Pick subcodes of codes using subspaces to reduce list size.
- In RS, coefficients of polynomials are restricted to subspaces \mathcal{H} that form (s, A) -strong subspace designs.
- Error: $\frac{s}{s+1}(q - k)$; $\dim(H_i) = (1 - \epsilon)m$; Rate: $\frac{(1-\epsilon)k}{q}$.
- Pick $s = \mathcal{O}(1/\epsilon)$, $m = \Omega(s/\epsilon)$.
- AG codes: Do in blocks [GX13, GK16].



Sanjeev Arora and Boaz Barak.

Computational complexity: a modern approach.

Cambridge University Press, 2009.



Key One Chung.

Goppa codes, December 2004.

Department of Mathematics, Iowa State University.



Venkatesan Guruswami and Swastik Kopparty.

Explicit subspace designs.

Combinatorica, 36(2):161–185, 2016.



Valerii Denisovich Goppa.

Algebraico-geometric codes.

Izvestiya Rossiiskoi Akademii Nauk. Seriya Matematicheskaya,
46(4):762–781, 1982.



Venkatesan Guruswami and Chaoping Xing.

List decoding reed-solomon, algebraic-geometric, and gabidulin subcodes up to the singleton bound.

In Proceedings of the forty-fifth annual ACM symposium on Theory of computing, pages 843–852, 2013.



Swastik Kopparty, Noga Ron-Zewi, Shubhangi Saraf, and Mary Wootters.

Improved decoding of folded reed-solomon and multiplicity codes.

In 2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS), pages 212–223. IEEE, 2018.



Swastik Kopparty, Shubhangi Saraf, and Sergey Yekhanin.

High-rate codes with sublinear-time decoding.

Journal of the ACM (JACM), 61(5):1–20, 2014.



Noam Nisan and Avi Wigderson.

Hardness vs randomness.

Journal of computer and System Sciences, 49(2):149–167, 1994.



Madhu Sudan.

Maximum likelihood decoding of reed solomon codes.

In Proceedings of 37th Conference on Foundations of Computer Science, pages 164–172. IEEE, 1996.



Madhu Sudan.

Decoding of reed solomon codes beyond the error-correction bound.

Journal of complexity, 13(1):180–193, 1997.



Lloyd R Welch and Elwyn R Berlekamp.

Error correction for algebraic block codes, December 30 1986.

US Patent 4,633,470.



Stephen B Wicker and Vijay K Bhargava.

Reed-Solomon codes and their applications.

John Wiley & Sons, 1999.

Thank You!