



University of Colorado
Boulder

Introduction to Virtual Reality

Depth Perception

Professor **Dan Szafir**

*Computer Science & ATLAS Institute
University of Colorado Boulder*

Depth Perception

Lots of research!

Still not entirely understood

Visual Cliff: Gibson and Walk (1960) – Learned or innate?

Binocular and Monocular cues



Depth Perception

Binocular Cues  Innate

Stereopsis (Disparity,
Binocular Parallax)

Convergence

Monocular Cues 

Size

Interposition

Grain / Texture

Motion parallax

Linear perspective

Aerial perspective

Light and shade

Relative Height

Accommodation

Learned?


Binocular Cues

Stereopsis

(retinal / binocular disparity)

Brain fuses images from both eyes

As horizontal distance between eyes is fixed, can triangulate to determine distance




Stereopsis (cont.)

Correspondence points vs retinal disparity

Panum's Fusional area: area on retina that corresponds to binocular fusion

Diplopia: images fall far apart causing double vision


Horopter: plot of correspondence points for given distance



Convergence

Muscles and nerves send signals as object is tracked

Inward turn of ocular muscles indicates object is close



Monocular Cues

Relative Size

Objects that cast a smaller retinal image tend to be perceived as farther away (if relatively the same size)



BaMbuti Pygmies

1950's and 1960's study by Colin Turnbull

Pygmies environment did not require relative size depth cues and thus they were not able to utilize relative size to determine depth

Demonstrated certain depth cues are learned

Interposition / Overlap / Occlusion

Objects that block out the view of another object are perceived to be nearer



Grain / Texture Gradient

The clearer the texture of an object is the closer we perceive it to be


As textures blend together, we perceive the object to be further away



Relative Motion / Motion Parallax


As we move forward, nearby objects appear to move out of our field of vision more quickly

Objects that move slower or appear to move with us are perceived to be further away



Linear Perspective

As assumed parallel edges (e.g., road, railroad tracks) appear to get closer together they are perceived to be farther away from us



Aerial Perspective / Atmospheric Perspective



Objects that appear less clear are perceived as being farther away (environmental effect)

Farther away objects have less saturated colors and shift towards the background color




Light and Shading

Objects that are seen as brighter are perceived as nearer



Relative Height / Elevation



Objects that appear higher in our field of vision are perceived to be farther away (below vs above horizon)




Accommodation

Process of how the eye controls the focus to see an object at different distances by changing the shape of the eye lens


Ciliary muscles: contract = near, relaxed = far




Far:




lens viewed from back




Near:




lens viewed from back



Accommodation-vergence conflict










Fig. 1. Schema of effective ranges of the different depth cues (based on Cutting and Vishton [1995]).

Egocentric Depth Estimation in MR

“Subjectively perceived distance from a human observer to an object”

Measured via:

Blind walking

Blind reaching

Alignment tasks

Consensus: depth in VR is underestimated compared with the real world

i.e., objects appear smaller and farther away than they should





Figure 2: The experimental apparatus.



Figure 3: Perceptual matching and blind reaching tasks.

Visual Illusions











University of Colorado
Boulder

THANKS!

Professor **Dan Szafir**

*Computer Science & ATLAS Institute
University of Colorado Boulder*