

School of Computer Science and Artificial Intelligence

Lab Assignment # 11.2

Program	: B. Tech (CSE)
Specialization	: -
Course Title	: AI Assisted Coding
Course Code	: 23CS002PC304
Semester	: II
Academic Session	: 2025-2026
Name of Student	: Mohammed Hashir Sayam Hussain
Enrollment No.	: 2403A51L27
Batch No.	: 51
Date	: 17/02/26

Submission Starts here**Screenshots:****Task Description #1 – Stack Implementation**

Task: Use AI to generate a Stack class with push, pop, peek, and is_empty methods.

Sample code:

```
class Stack:  
    Pass
```

Prompt:

generate a Stack class with push, pop, peek, and is_empty
Methods and code.

Code:

```

1 class Stack:
2     def __init__(self):
3         """Initialize an empty stack."""
4         self.items = []
5
6     def push(self, item):
7         """Add an item to the top of the stack.
8
9         Args:
10             item: The item to be added to the stack.
11         """
12         self.items.append(item)
13
14     def pop(self):
15         """Remove and return the top item from the stack.
16
17         Returns:
18             The top item from the stack.
19
20         Raises:
21             IndexError: If the stack is empty.
22         """
23         if self.is_empty():
24             raise IndexError("Cannot pop from an empty stack")
25         return self.items.pop()
26
27     def peek(self):
28         """Return the top item from the stack without removing it.
29
30         Returns:
31             The top item from the stack.
32
33         Raises:
34             IndexError: If the stack is empty.
35         """
36         if self.is_empty():
37             raise IndexError("Cannot peek at an empty stack")
38         return self.items[-1]
39
40     def is_empty(self):
41         """Check if the stack is empty.
42
43         Returns:
44             True if the stack is empty, False otherwise.
45         """
46         return len(self.items) == 0
47
48     def size(self):
49         """Return the number of items in the stack.
50
51         Returns:
52             The number of items in the stack.
53         """
54         return len(self.items)
55
56     def __str__(self):
57         """Return a string representation of the stack.
58
59         Returns:
60             A string representation of the stack.
61         """
62         return f"Stack({self.items})"

```

```

63
64
65 # Example usage and testing
66 if __name__ == "__main__":
67     # Create a new stack
68     stack = Stack()
69
70     # Test is_empty on empty stack
71     print(f"Is stack empty? {stack.is_empty()}")
72     print(f"Stack size: {stack.size()}")
73     print()
74
75     # Push items onto the stack
76     print("Pushing items: 10, 20, 30")
77     stack.push(10)
78     stack.push(20)
79     stack.push(30)
80     print(f"Stack: {stack}")
81     print(f"Is stack empty? {stack.is_empty()}")
82     print(f"Stack size: {stack.size()}")
83     print()
84
85     # Peek at the top item
86     print(f"Peek at top: {stack.peak()}")
87     print(f"Stack after peek: {stack}")
88     print()
89
90     # Pop items from the stack
91     print("Popping items:")
92     print(f"Popped: {stack.pop()}")
93     print(f"Stack: {stack}")
94     print(f"Popped: {stack.pop()}")
95     print(f"Stack: {stack}")
96     print(f"Popped: {stack.pop()}")
97     print(f"Stack: {stack}")
98     print()
99
100     # Test is_empty after popping all items
101     print(f"Is stack empty? {stack.is_empty()}")
102     print(f"Stack size: {stack.size()}")

```

Output:

```

Is stack empty? True
Stack size: 0

Pushing items: 10, 20, 30
Stack: Stack([10, 20, 30])
Is stack empty? False
Stack size: 3

Peek at top: 30
Stack after peek: Stack([10, 20, 30])

Popping items:
Popped: 30
Stack: Stack([10, 20])
Popped: 20
Stack: Stack([10])
Popped: 10
Stack: Stack([])

Is stack empty? True
Stack size: 0

```

Task Description #2 – Queue Implementation

Task: Use AI to implement a Queue using Python lists.

Sample Input Code:

```
class Queue:
```

Pass

Prompt:

complete the queue class with enqueue, dequeue, peek, and size methods and code

Code:

```

1  class Queue:
2      def __init__(self):
3          """Initialize an empty queue."""
4          self.items = []
5
6      def enqueue(self, item):
7          """Add an item to the rear of the queue.
8
9          Args:
10             item: The item to add to the queue
11          """
12          self.items.append(item)
13
14      def dequeue(self):
15          """Remove and return the front item from the queue.
16
17          Returns:
18             The front item of the queue
19
20          Raises:
21             IndexError: If the queue is empty
22          """
23          if self.is_empty():
24              raise IndexError("Cannot dequeue from an empty queue")
25          return self.items.pop(0)
26
27      def peek(self):
28          """Return the front item of the queue without removing it.
29
30          Returns:
31             The front item of the queue
32
33          Raises:
34             IndexError: If the queue is empty
35          """
36          if self.is_empty():
37              raise IndexError("Cannot peek at an empty queue")
38          return self.items[0]
39
40      def size(self):
41          """Return the number of items in the queue.
42
43          Returns:
44             The number of items in the queue
45          """
46          return len(self.items)
47
48      def is_empty(self):
49          """Check if the queue is empty.
50
51          Returns:
52             True if the queue is empty, False otherwise
53          """
54          return len(self.items) == 0
55
56
57 # Example usage and testing
58 if __name__ == "__main__":
59     # Create a new queue
60     q = Queue()
61
62     # Click to check, Ctrl+K to generate
63     # Test enqueue
64     print("Enqueueing items: 1, 2, 3, 4, 5")
65     q.enqueue(1)
66     q.enqueue(2)
67     q.enqueue(3)
68     q.enqueue(4)
69     q.enqueue(5)
70
71     # Test size
72     print(f"Queue size: {q.size()}")
73
74     # Test peek
75     print(f"Peek at front: {q.peek()}")
76
77     # Test dequeue
78     print("\nDequeuing items:")
79     while not q.is_empty():
80         print(f"  Dequeued: {q.dequeue()}, Remaining size: {q.size()}")
81
82     # Test empty queue
83     print(f"\nQueue is empty: {q.is_empty()}")
84
85     # Test error handling
86     try:
87         q.dequeue()
88     except IndexError as e:
89         print(f"Error caught: {e}")
90
91     try:
92         q.peek()
93     except IndexError as e:
94         print(f"Error caught: {e}")

```

Output:

```

Enqueueing items: 1, 2, 3, 4, 5
Queue size: 5
Peek at front: 1

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Enqueueing items: 1, 2, 3, 4, 5
Queue size: 5
Peek at front: 1
0
Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Peek at front: 1

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeued: 5, Remaining size: 0

Queue is empty: True
Error caught: Cannot dequeue from an empty queue
Error caught: Cannot peek at an empty queue

```

Task Description #3 – Linked List

Task: Use AI to generate a Singly Linked List with insert and display methods.

Sample Input Code:

class Node:

Pass

Prompt:

generate a Singly Linked List with insert and display methods with code

Code:

```

1 class Node:
2     """Node class to represent a single node in the linked list"""
3     def __init__(self, data):
4         self.data = data # Data stored in the node
5         self.next = None # Reference to the next node
6
7
8 class SinglyLinkedList:
9     """Singly Linked List implementation with insert and display methods"""
10
11     def __init__(self):
12         self.head = None # Head pointer pointing to the first node
13
14     def insert(self, data):
15         """
16         Insert a new node at the end of the linked list
17
18         Args:
19             data: The data to be inserted into the linked list
20         """
21         new_node = Node(data)
22
23         # If the list is empty, make the new node the head
24         if self.head is None:
25             self.head = new_node
26         else:
27             # Traverse to the end of the list
28             current = self.head
29             while current.next is not None:
30                 current = current.next
31             # Insert the new node at the end
32             current.next = new_node
33
34     def insert_at_beginning(self, data):
35         """
36         Insert a new node at the beginning of the linked list
37
38         Args:
39             data: The data to be inserted into the linked list
40         """
41         new_node = Node(data)
42         new_node.next = self.head
43         self.head = new_node
44
45     def display(self):
46         """
47         Display all elements in the linked list
48         """
49         if self.head is None:
50             print("Linked List is empty")
51             return
52
53         current = self.head
54         elements = []
55         while current is not None:
56             elements.append(str(current.data))
57             current = current.next
58
59         # Display in format: data1 -> data2 -> data3 -> None
60         print(" -> ".join(elements) + " -> None")
61
62
63 # Example usage
64 if __name__ == "__main__":
65     # Create a new linked list
66     ll = SinglyLinkedList()
67
68     # Insert some elements
69     print("Inserting elements into the linked list...")
70     ll.insert(10)
71     ll.insert(20)
72     ll.insert(30)
73     ll.insert(40)
74
75     # Display the linked list
76     print("\nLinked List contents:")
77     ll.display()
78
79     # Insert at beginning
80     print("\nInserting 5 at the beginning...")
81     ll.insert_at_beginning(5)
82     ll.display()
83
84     # Create an empty list
85     print("\nCreating an empty linked list:")
86     empty_ll = SinglyLinkedList()
87     empty_ll.display()

```

Output:

```
Inserting elements into the linked list...
Inserting elements into the linked list...
```

```
Linked List contents:
```

```
Linked List contents:
```

```
Linked List contents:
```

```
10 -> 20 -> 30 -> 40 -> None
```

```
10 -> 20 -> 30 -> 40 -> None
```

```
Inserting 5 at the beginning...
```

```
Inserting 5 at the beginning...
```

```
5 -> 10 -> 20 -> 30 -> 40 -> None
```

```
5 -> 10 -> 20 -> 30 -> 40 -> None
```

```
Creating an empty linked list:
```

```
Linked List is empty
```

```
Linked List is empty
```

Task Description #4 – Binary Search Tree (BST)

Task: Use AI to create a BST with insert and in-order traversal methods.

Sample Input Code:

```
class BST:
    pass
```

Prompt:

create a BST with insert and in-order traversal methods and code

Code:

```

1 class Node:
2     def __init__(self, key: int):
3         self.key = key
4         self.left: "Node | None" = None
5         self.right: "Node | None" = None
6
7
8 class BST:
9     def __init__(self):
10        self.root: Node | None = None
11
12    def insert(self, key: int) -> None:
13        """Insert key into the BST (duplicates go to the right)."""
14        if self.root is None:
15            self.root = Node(key)
16            return
17
18        cur = self.root
19        while True:
20            if key < cur.key:
21                if cur.left is None:
22                    cur.left = Node(key)
23                    return
24                cur = cur.left
25            else:
26                if cur.right is None:
27                    cur.right = Node(key)
28                    return
29                cur = cur.right
30
31    def inorder(self) -> list[int]:
32        """Return keys in in-order (sorted) order."""
33        result: list[int] = []
34
35        def dfs(n: Node | None) -> None:
36            if n is None:
37                return
38            dfs(n.left)
39            result.append(n.key)
40            dfs(n.right)
41
42        dfs(self.root)
43        return result
44
45    if __name__ == "__main__":
46        bst = BST()
47        for x in [7, 3, 9, 1, 5, 8, 10]:
48            bst.insert(x)
49        print("In-order:", bst.inorder())
50

```

Output:

```
In-order: [1, 3, 5, 7, 8, 9, 10]
```

Task Description #5 – Hash Table

Task: Use AI to implement a hash table with basic insert, search, and delete methods.

Sample Input Code:

```
class HashTable:
    pass
```

Prompt:

implement a hash table with basic insert, search, and delete methods with code

Code:


```

1 class HashTable:
2     """
3     Hash table using separate chaining (list of buckets).
4
5     Methods:
6     - insert(key, value): add/update a key
7     - search(key): return value or None if not found
8     - delete(key): remove key, return True if removed else False
9     """
10
11     def __init__(self, capacity: int = 8) -> None:
12         if capacity < 1:
13             raise ValueError("capacity must be >= 1")
14         self._capacity = capacity
15         self._buckets = [[] for _ in range(self._capacity)] # List[List[tuple[key, value]]]
16         self._size = 0
17
18     def _index(self, key) -> int:
19         return hash(key) % self._capacity
20
21     def _rehash(self, new_capacity: int) -> None:
22         old_items = []
23         for bucket in self._buckets:
24             old_items.extend(bucket)
25
26         self._capacity = new_capacity
27         self._buckets = [[] for _ in range(self._capacity)]
28         self._size = 0
29
30         for k, v in old_items:
31             self.insert(k, v)
32
33     def insert(self, key, value) -> None:
34         # Resize when load factor gets too high (simple rule-of-thumb)
35         if (self._size + 1) / self._capacity > 0.75:
36             self._rehash(self._capacity * 2)
37
38         idx = self._index(key)
39         bucket = self._buckets[idx]
40
41         for i, (k, _) in enumerate[Any](bucket):
42             if k == key:
43                 bucket[i] = (key, value) # update existing
44                 return
45
46         bucket.append((key, value))
47         self._size += 1
48
49     def search(self, key):
50         idx = self._index(key)
51         bucket = self._buckets[idx]
52         for k, v in bucket:
53             if k == key:
54                 return v
55         return None
56
57     def delete(self, key) -> bool:
58         idx = self._index(key)
59         bucket = self._buckets[idx]
60
61         for i, (k, _) in enumerate[Any](bucket):
62             if k == key:
63                 bucket.pop(i)
64                 self._size -= 1
65                 return True
66
67         return False
68
69     def __len__(self) -> int:
70         return self._size
71
72     def __contains__(self, key) -> bool:
73         return self.search(key) is not None
74
75     def __repr__(self) -> str:
76         return f"HashTable(size={self._size}, capacity={self._capacity})"
77
78
79 if __name__ == "__main__":
80     ht = HashTable()
81     ht.insert("name", "Alice")
82     ht.insert("age", 20)
83     ht.insert("age", 21) # update
84
85     print(ht) # HashTable(...)
86     print(ht.search("name")) # Alice
87     print(ht.search("age")) # 21
88     print(ht.search("x")) # None
89
90     print(ht.delete("age")) # True
91     print(ht.delete("age")) # False
92     print(len(ht)) # 1

```

Output:

```
HashTable(size=2, capacity=8)
Alice
21
None
HashTable(size=2, capacity=8)
Alice
21
None
21
None
True
False
1
True
False
1
False
1
```

Task Description #6 – Graph Representation

Task: Use AI to implement a graph using an adjacency list.

Sample Input Code:

```
class Graph:
    pass
```

Prompt:

implement a graph using an adjacency list with code

Code:

```

1 class Graph:
2     """
3     Graph implemented using an adjacency list.
4
5     - By default the graph is undirected.
6     - Set directed=True for a directed graph.
7     """
8
9     def __init__(self, directed: bool = False):
10         self.directed = directed
11         # adjacency list: vertex -> set of neighbor vertices
12         self.adj: dict[object, set[object]] = {}
13
14     def add_vertex(self, v: object) -> None:
15         """Add a vertex if it doesn't already exist."""
16         if v not in self.adj:
17             self.adj[v] = set[object]()
18
19     def add_edge(self, u: object, v: object) -> None:
20         """Add an edge u -> v (and v -> u if undirected)."""
21         self.add_vertex(u)
22         self.add_vertex(v)
23         self.adj[u].add(v)
24         if not self.directed:
25             self.adj[v].add(u)
26
27     def remove_edge(self, u: object, v: object) -> None:
28         """Remove an edge u -> v (and v -> u if undirected), if present."""
29         if u in self.adj:
30             self.adj[u].discard(v)
31         if not self.directed and v in self.adj:
32             self.adj[v].discard(u)
33
34     def remove_vertex(self, v: object) -> None:
35         """Remove a vertex and all edges incident to it."""
36         if v not in self.adj:
37             return
38
39         # Remove edges from neighbors to v
40         for n in list[object](self.adj[v]):
41             self.remove_edge(v, n)
42
43         # In directed graphs, also remove incoming edges to v
44         if self.directed:
45             for u in self.adj:
46                 self.adj[u].discard(v)
47
48         del self.adj[v]
49
50     def neighbors(self, v: object) -> list[object]:
51         """Return neighbors of v as a sorted list when possible."""
52         if v not in self.adj:
53             return []
54         try:
55             return sorted(self.adj[v])
56         except TypeError:
57             return list[object](self.adj[v])
58
59     def bfs(self, start: object) -> list[object]:
60         """Breadth-first traversal order starting from start."""
61         if start not in self.adj:
62             return []
63
64         visited = {start}
65         queue = [start]
66         order: list[object] = []
67
68         while queue:
69             v = queue.pop(0)
70             order.append(v)
71             for n in self.neighbors(v):
72                 if n not in visited:
73                     visited.add(n)
74                     queue.append(n)
75
76         return order
77
78     def dfs(self, start: object) -> list[object]:
79         """Depth-first traversal order starting from start."""
80         if start not in self.adj:
81             return []
82
83         visited: set[object] = set[object]()
84         order: list[object] = []
85
86         def _visit(v: object) -> None:
87             visited.add(v)
88             order.append(v)
89             for n in self.neighbors(v):
90                 if n not in visited:
91                     _visit(n)
92
93         _visit(start)
94         return order
95
96     def __str__(self) -> str:
97         lines = []
98         for v in self.adj:
99             lines.append(f"{v} -> {self.neighbors(v)}")
100         return "\n".join(lines)
101
102
103 if __name__ == "__main__":
104     g = Graph(directed=False) # change to True for a directed graph
105     g.add_edge("A", "B")
106     g.add_edge("A", "C")
107     g.add_edge("B", "D")
108     g.add_edge("C", "D")
109     g.add_edge("D", "E")
110
111     print("Adjacency list:")
112     print(g)
113     print()
114     print("BFS from A:", g.bfs("A"))
115     print("DFS from A:", g.dfs("A"))

```

Output:

```
Adjacency list:
A -> ['B', 'C']
B -> ['A', 'D']
Adjacency list:
A -> ['B', 'C']
B -> ['A', 'D']
A -> ['B', 'C']
B -> ['A', 'D']
B -> ['A', 'D']
C -> ['A', 'D']
D -> ['B', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
D -> ['B', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
```

Task Description #7 – Priority Queue

Task: Use AI to implement a priority queue using Python's heapq module.

Sample Input Code:

```
class PriorityQueue:
    pass
```

Prompt:

implement a priority queue using Python's heapq module with code

Code:

```

1 import heapq
2 from itertools import count
3
4 class PriorityQueue:
5     """
6     Min-priority queue by default (smaller priority value = served first).
7     For max-priority behavior, push with -priority.
8     """
9     def __init__(self):
10         self._heap = []
11         self._seq = count(int)() # tie-breaker for equal priorities (FIFO)
12
13     def push(self, item, priority: int):
14         heapq.heappush(self._heap, (priority, next(self._seq), item))
15
16     def pop(self):
17         if not self._heap:
18             raise IndexError("pop from empty PriorityQueue")
19         priority, _, item = heapq.heappop(self._heap)
20         return item, priority
21
22     def peek(self):
23         if not self._heap:
24             raise IndexError("peek from empty PriorityQueue")
25         priority, _, item = self._heap[0]
26         return item, priority
27
28     def __len__(self):
29         return len(self._heap)
30
31     def empty(self):
32         return len(self._heap) == 0
33
34
35 if __name__ == "__main__":
36     pq = PriorityQueue()
37     pq.push("low", 5)
38     pq.push("urgent", 1)
39     pq.push("medium", 3)
40     pq.push("also urgent (arrives later)", 1)
41
42     while not pq.empty():
43         item, pr = pq.pop()
44         print(pr, item)
45
46     # Max-priority example (bigger number = served first):
47     maxpq = PriorityQueue()
48     for item, pr in [("A", 10), ("B", 2), ("C", 10)]:
49         maxpq.push(item, -pr) # negate priority
50
51     print("max first:", maxpq.pop()) # returns (item, neg priority)

```

Output:

```

1 urgent
1 also urgent (arrives later)
3 medium
5 low
max first: ('A', -10)

```

Task Description #8 – Deque

Task: Use AI to implement a double-ended queue using `collections.deque`.

Sample Input Code:

```

class DequeDS:
    pass

```

Prompt:

implement a double-ended queue using `collections.deque` with code

Code:

```

1  from __future__ import annotations
2
3  from collections import deque
4  from typing import Deque, Generic, Iterator, Optional, TypeVar
5
6  T = TypeVar("T")
7
8
9  class DequeDS(Generic[T]):
10     """
11     Double-ended queue (deque) implemented using collections.deque.
12     Supports O(1) append/pop operations on both ends.
13     """
14
15     def __init__(self, items: Optional[Iterator[T]] = None) -> None:
16         self._dq: Deque[T] = deque[T](items or [])
17
18     # --- Add operations ---
19     def add_front(self, item: T) -> None:
20         """Insert item at the front (left)."""
21         self._dq.appendleft(item)
22
23     def add_rear(self, item: T) -> None:
24         """Insert item at the rear (right)."""
25         self._dq.append(item)
26
27     # --- Remove operations ---
28     def remove_front(self) -> T:
29         """Remove and return the front (left) item."""
30         if self.is_empty():
31             raise IndexError("remove_front from empty deque")
32         return self._dq.popleft()
33
34     def remove_rear(self) -> T:
35         """Remove and return the rear (right) item."""
36         if self.is_empty():
37             raise IndexError("remove_rear from empty deque")
38         return self._dq.pop()
39
40     # --- Peek operations ---
41     def peek_front(self) -> T:
42         """Return the front (left) item without removing it."""
43         if self.is_empty():
44             raise IndexError("peek_front from empty deque")
45         return self._dq[0]
46
47     def peek_rear(self) -> T:
48         """Return the rear (right) item without removing it."""
49         if self.is_empty():
50             raise IndexError("peek_rear from empty deque")
51         return self._dq[-1]
52
53     # --- Utility ---
54     def is_empty(self) -> bool:
55         return len(self._dq) == 0
56
57     def size(self) -> int:
58         return len(self._dq)
59
60     def clear(self) -> None:
61         self._dq.clear()
62
63     def __len__(self) -> int:
64         return len(self._dq)
65
66     def __iter__(self) -> Iterator[T]:
67         return iter(self._dq)
68
69     def __repr__(self) -> str:
70         return f"DequeDS({list[T](self._dq)!r})"
71
72
73 if __name__ == "__main__":
74     d = DequeDS[int]()
75     d.add_front(10)    # [10]
76     d.add_rear(20)    # [10, 20]
77     d.add_front(5)    # [5, 10, 20]
78     print("Deque:", d)
79     print("Front:", d.peek_front())
80     print("Rear:", d.peek_rear())
81     print("Remove front:", d.remove_front()) # 5
82     print("Remove rear:", d.remove_rear())   # 20
83     print("Deque now:", d)

```

Output:

```
Deque: DequeDS([5, 10, 20])
Front: 5
Rear: 20
Remove front: 5
Remove rear: 20
Deque now: DequeDS([10])
```

Task Description #9 Real-Time Application Challenge – Choose the Right Data Structure

Prompt:

Solve this clearly and concisely.

Design a Campus Resource Management System code with:

1. Student Attendance Tracking
2. Event Registration System
3. Library Book Borrowing
4. Bus Scheduling System
5. Cafeteria Order Queue

Choose the best data structure for each feature from:

Stack, Queue, Priority Queue, Linked List, BST, Graph, Hash Table, Deque

Output as a table:

Feature | Data Structure | 2–3 sentence justification

Code:


```

1 from __future__ import annotations
2
3 from dataclasses import dataclass
4 from collections import deque
5 import heapq
6 import itertools
7 from typing import Deque, Dict, List, Optional, Set, Tuple
8
9
10 # =====
11 # 1) Student Attendance Tracking (Hash Table)
12 # =====
13
14 class AttendanceTracker:
15     """
16     Data structure: Hash Table (Python dict)
17     student_id -> (date_str -> present_bool)
18     """
19
20     def __init__(self) -> None:
21         self._records: Dict[str, Dict[str, bool]] = {}
22
23     def mark(self, student_id: str, date: str, present: bool) -> None:
24         self._records.setdefault(student_id, {})
25         self._records[student_id][date] = present
26
27     def is_present(self, student_id: str, date: str) -> Optional[bool]:
28         return self._records.get(student_id, {}).get(date)
29
30     def attendance_records(self, student_id: str) -> Dict:
31         days = self._records.get(student_id, {})
32         if not days:
33             return {}
34         present_count = sum(1 for v in days.values() if v)
35         return {present_count / len(days): 100.0}
36
37 # =====
38 # 2) Food Registration System (Queue)
39 # =====
40
41 class FoodRegistrationSystem:
42     """
43     Data structure: Queue (collections.deque)
44     . FIFO registration requests = FIFO queue.
45     """
46
47     @dataclass(frozen=True)
48     class Event:
49         event_id: str
50         name: str
51         capacity: int
52
53     def __init__(self) -> None:
54         self._events: Dict[str, FoodRegistrationSystem.Event] = {}
55         self._confirmed: Dict[str, List[str]] = {} # event_id -> list(student_id)
56         self._requests: Dict[str, Deque[str]] = {} # event_id -> deque(student_id)
57         self._waitlist: Dict[str, Deque[str]] = {} # event_id -> deque(student_id)
58
59     def create_event(self, event_id: str, name: str, capacity: int) -> None:
60         if capacity < 0:
61             raise ValueError("Capacity must be >= 0")
62         self._events[event_id] = self.Event(event_id, name, capacity)
63         self._confirmed.setdefault(event_id, [])
64         self._requests.setdefault(event_id, deque())
65         self._waitlist.setdefault(event_id, deque())
66
67     def request_registration(self, event_id: str, student_id: str) -> None:
68         self._request_event(event_id)
69         if student_id in self._confirmed[event_id]:
70             return
71         if student_id in self._requests[event_id] or student_id in self._waitlist[event_id]:
72             self._requests[event_id].append(student_id)
73
74     def process_next_request(self, event_id: str) -> Optional[str]:
75         """
76         Processes the pending request in FIFO order.
77         Returns the student_id that got confirmed (or None if no request).
78         """
79         self._process_event(event_id)
80         q = self._requests[event_id]
81         if not q:
82             return None
83         student_id = q.popleft()
84         if len(self._confirmed[event_id]) < self._events[event_id].capacity:
85             self._confirmed[event_id].append(student_id)
86             return student_id
87         self._waitlist[event_id].append(student_id)
88         return None
89
90     def cancel_registration(self, event_id: str, student_id: str) -> None:
91         self._request_event(event_id)
92         if student_id in self._confirmed[event_id]:
93             self._confirmed[event_id].remove(student_id)
94             self._process_from_waitlist(event_id)
95             return
96         if student_id in self._requests[event_id]:
97             self._requests[event_id].remove(student_id)
98             self._process_from_waitlist(event_id)
99             return
100         if student_id in self._waitlist[event_id]:
101             self._waitlist[event_id].remove(student_id)
102
103     def confirm_event(self, event_id: str) -> List[str]:
104         self._process_event(event_id)
105         return sorted(self._confirmed[event_id])
106
107     def waitlist_list(self, event_id: str) -> List[str]:
108         self._process_event(event_id)
109         return list(self._waitlist[event_id])
110
111     def process_waitlist(self, event_id: str) -> None:
112         if len(self._confirmed[event_id]) == self._events[event_id].capacity:
113             return
114         w = self._waitlist[event_id]
115         while w and len(self._confirmed[event_id]) < self._events[event_id].capacity:
116             self._confirmed[event_id].append(w.popleft())
117
118     def remove_from_queue(self, q: Deque[str], student_id: str) -> None:
119         # queue doesn't support fast middle removal, rebuild for clarity.
120         if not q:
121             return
122         new_q = deque()
123         for x in q:
124             if x != student_id:
125                 new_q.append(x)
126         q.clear()
127         q.extend(new_q)
128
129     def remove_event(self, event_id: str) -> None:
130         if event_id not in self._events:
131             raise KeyError(f"Unknown event_id: {event_id}")
132
133 # =====
134 # 3) Library Book Borrowing (BST)
135 # =====
136
137 # Dataclass
138 class Book:
139     isbn: str
140     title: str
141     total_copies: int
142     available_copies: int
143
144 class BookSTNode:
145     def __init__(self, key: str, val: Book) -> None:
146         self.key = key
147         self.val = val
148         self.left: Optional[BookSTNode] = None
149         self.right: Optional[BookSTNode] = None
150
151 class LibrarySystem:
152     """
153     Data structure: BST (By ISBN) for catalog/inventory search and ordered traversal.
154     Borrowing increments available copies, returning increments.
155     """
156
157     def __init__(self) -> None:
158         self._root: Optional[BookSTNode] = None
159         self._isbn_to_book: Dict[str, Book] = {} # (student_id, isbn) -> current borrowed
160
161     def add_book(self, isbn: str, title: str, copies: int) -> None:
162         if copies <= 0:
163             raise ValueError("copies must be > 0")
164         existing = self.find(isbn)
165         if existing:
166             existing.total_copies += copies
167             existing.available_copies += copies
168             return
169         book = Book(isbn=isbn, title=title, total_copies=copies, available_copies=copies)
170         self._root = self._insert(self._root, isbn, book)
171
172     def find(self, isbn: str) -> Optional[Book]:
173         node = self._root
174         while node:
175             if isbn < node.key:
176                 node = node.left
177             elif isbn > node.key:
178                 node = node.right
179             else:
180                 return node
181         return None
182
183     def borrow(self, student_id: str, isbn: str) -> bool:
184         book = self.find(isbn)
185         if not book or book.available_copies <= 0:
186             return False
187         book.available_copies -= 1
188         self._isbn_to_book[(student_id, isbn)] = self._root.get(student_id, isbn), 0 + 1
189         return True
190
191     def return_book(self, student_id: str, isbn: str) -> bool:
192         key = (student_id, isbn)
193         if key in self._isbn_to_book:
194             return True
195         return False

```



```

100     book = self.find(book)
101     if not book:
102         return False
103     self.available_copies -= 1
104     return True
105
106 def catalog_in_order(self) -> list(Book):
107     out_list[book] = []
108     self.catalog_in_order_recursive(out_list, None)
109     return out_list
110
111 def insert(self, node: Optional(BookNode), left: str, book: Book) -> BookNode:
112     if node is None:
113         return BookNode(left, book)
114     if left < node.left:
115         node.left = self.insert(node.left, left, book)
116     else:
117         node.right = self.insert(node.right, left, book)
118     return node
119
120 def in_order(self, node: Optional(BookNode), out_list[Book]) -> None:
121     if node is None:
122         return
123     self.in_order(node.left, out_list)
124     out_list.append(book)
125     self.in_order(node.right, out_list)
126
127 # =====
128 # 4) Bus Scheduling System (Graph)
129 # =====
130
131 class BusNetwork:
132     """
133     Data structure: Graph (adjacency list)
134     stop -> list of (neighbor_stop, travel_minutes)
135     - shortest path uses Dijkstra (non-negative weights).
136     """
137
138     def __init__(self) -> None:
139         self.adj: dict[str, list[tuple[str, int]]] = {}
140
141     def add_stop(self, stop: str) -> None:
142         self.adj.setdefault(stop, [])
143
144     def add_route(self, s: str, t: str, minutes: int, bidirectional: bool = True) -> None:
145         if minutes < 0:
146             raise ValueError("minutes must be non-negative")
147         self.add_route(s, t, minutes)
148         if bidirectional:
149             self.add_route(t, s, minutes)
150
151     def shortest_path(self, start: str, end: str) -> tuple[list[str], int]:
152         if start not in self.adj or end not in self.adj:
153             raise ValueError("start/end stop not found")
154
155         dist: dict[str, int] = {start: 0}
156         prev: dict[str, Optional[str]] = {start: None}
157         pq: list[tuple[int, str]] = [(0, start)]
158
159         while pq:
160             d, u = heapq.heappop(pq)
161             if d != dist.get(u, 10**18):
162                 continue
163             if u == end:
164                 break
165             for v, w in self.adj[u]:
166                 nd = d + w
167                 if nd < dist.get(v, 10**18):
168                     dist[v] = nd
169                     prev[v] = u
170                     heapq.heappush(pq, (nd, v))
171
172         if end not in dist:
173             return (10**18, [])
174
175         # Reconstruct path
176         path: list[str] = []
177         cur: Optional[str] = end
178         while cur is not None:
179             path.append(cur)
180             cur = prev.get(cur)
181         path.reverse()
182         return dist[end], path
183
184 # =====
185 # 5) Cafeteria Order Queue (Priority Queue)
186 # =====
187
188 @dataclass(frozen=True)
189 class CafeteriaOrder:
190     order_id: int
191     student_id: str
192     item: str
193     priority: int # Higher number == Higher priority
194
195 class CafeteriaOrderSystem:
196     """
197     Data structure: Priority Queue (heap)
198     - Serve highest priority first; tie-break by arrival order.
199     """
200
201     def __init__(self) -> None:
202         self.heap: list[tuple[int, CafeteriaOrder]] = []
203         self.counter = itertools.count()
204
205     def place_order(self, student_id: str, item: str, priority: int = 0) -> CafeteriaOrder:
206         order_id = next(self.counter)
207         order = CafeteriaOrder(order_id, student_id, item, item, priority)
208         # Push to heap, insert priority on-heap priority order first
209         heapq.heappush(self.heap, (-priority, order_id, order))
210         return order
211
212     def serve_next(self) -> Optional[CafeteriaOrder]:
213         if not self.heap:
214             return None
215         _, order_id, order = heapq.heappop(self.heap)
216         return order
217
218     def pending_count(self) -> int:
219         return len(self.heap)
220
221 # =====
222 # Demo (optional)
223 # =====
224
225 def main() -> None:
226     # Attends
227     att = AttendanceTracker()
228     att.mark("S1", "2024-03-17", True)
229     att.mark("S1", "2024-03-18", False)
230     print(f"Attendance S1: {att.attendance_percent('S1', 2)}")
231
232     # Events
233     events = EventRegistrationSystem()
234     events.create_event("T100", "AI Workshop", capacity=2)
235     for sid in ["S1", "S2", "S3"]:
236         events.request_registration("T100", sid)
237     events.process_next_request("T100")
238     print(f"Confirmed S1: {events.confirmed_list('T100')}")
239     print(f"Waitlist T100: {events.waitlist_list('T100')}")
240     events.cancel_registration("T100", "S2")
241     print(f"After cancel S2 confirmed: {events.confirmed_list('T100')}")
242
243     # Library (BFS)
244     lib = LibrarySystem()
245     lib.add_book("9781492051208", "Effective Java", copies=2)
246     lib.add_book("9781492051167", "Fluent Python", copies=1)
247     print(f"Borrow fluent Python: {lib.borrow('S1', '9781492051167')}")
248     print(f"Borrow fluent Python again: {lib.borrow('S2', '9781492051167')}")
249     print(f"Catalog in order: {lib.catalog_in_order()}")
250
251     # Bus network (Graph)
252     buses = BusNetwork()
253     buses.add_route("Hostel", "Gate", 8)
254     buses.add_route("Gate", "Library", 4)
255     buses.add_route("Hostel", "Cafeteria", 5)
256     buses.add_route("Cafeteria", "Library", 4)
257     minutes, path = buses.shortest_path("Hostel", "Library")
258     print(f"Shortest bus path Hostel->Library: {path}, {minutes} minutes")
259
260     # Cafeteria (Priority Queue)
261     cafe = CafeteriaOrderSystem()
262     cafe.place_order("S1", "Sandwich", priority=0)
263     cafe.place_order("S2", "Coffee", priority=2)
264     cafe.place_order("S3", "Burger", priority=1)
265     print("Serve order:", cafe.serve_next())
266     print("Serve order:", cafe.serve_next())
267
268     if __name__ == "__main__":
269         main()
270

```

Output:

```
Attendance S1 %: 50.0
Confirmed E100: ['S1', 'S2']
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Attendance S1 %: 50.0
Confirmed E100: ['S1', 'S2']
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Serve order: CafeteriaOrder(order_id=3, student_id='S3', item='Burger', priority=1)
Serve order: CafeteriaOrder(order_id=3, student_id='S3', item='Burger', priority=1)
```

Task Description #10: Smart E-Commerce Platform – Data Structure

Prompt:

Solve this clearly and concisely.

Design a Smart E-Commerce Platform with:

Shopping Cart Management – Add/remove products dynamically

Order Processing System – Process orders in placement order

Top-Selling Products Tracker – Rank products by sales count

Product Search Engine – Fast lookup using product ID

Delivery Route Planning – Connect warehouses and delivery locations

Choose the most appropriate data structure for each feature from:

Stack, Queue, Priority Queue, Linked List, BST, Graph, Hash Table, Deque

Output as a table:

Feature | Data Structure | 2–3 sentence justification

Code:

```

1 from collections import deque
2 import heapq
3 from typing import Dict, List, Tuple, Optional
4
5
6 # -----
7 # Product model
8 # -----
9
10 class Product:
11     def __init__(self, product_id: int, name: str, price: float):
12         self.id = product_id
13         self.name = name
14         self.price = price
15
16     def __repr__(self):
17         return f"Product(id={self.id}, name='{self.name}', price={self.price})"
18
19 # -----
20 # Product Search Engine (Hash Table)
21 # -----
22
23 class ProductSearchEngine:
24     def __init__(self):
25         # Hash Tables: product_id -> Product
26         self.products: Dict[int, Product] = {}
27
28     def add_product(self, product: Product):
29         self.products[product.id] = product
30
31     def get_product(self, product_id: int) -> Optional[Product]:
32         return self.products.get(product_id)
33
34     def remove_product(self, product_id: int):
35         self.products.pop(product_id, None)
36
37 # -----
38 # Shopping Cart (linked list)
39 # -----
40
41 class CartNode:
42     def __init__(self, product: Product, quantity: int):
43         self.product = product
44         self.quantity = quantity
45         self.next: Optional[CartNode] = None
46
47
48 class ShoppingCart:
49     def __init__(self):
50         self.head: Optional[CartNode] = None
51
52     def add_product(self, product: Product, quantity: int = 1):
53         """
54         If product already exists in the list, increase quantity.
55         Otherwise, add new node at the front (O(1) insertion).
56         """
57         node = self.head
58         while node:
59             if node.product.id == product.id:
60                 node.quantity += quantity
61                 return
62             node = node.next
63
64         new_node = CartNode(product, quantity)
65         new_node.next = self.head
66         self.head = new_node
67
68     def remove_product(self, product_id: int, quantity: int = None):
69         """
70         Remove some or all quantity of a product.
71         If quantity is None or reaches 0, remove the node.
72         """
73         prev = None
74         node = self.head
75
76         while node:
77             if node.product.id == product_id:
78                 if quantity is None or node.quantity <= quantity:
79                     # delete the node
80                     if prev:
81                         prev.next = node.next
82                     else:
83                         self.head = node.next
84                 else:
85                     node.quantity -= quantity
86                     return
87                 prev = node
88                 node = node.next
89
90     def list_items(self) -> List[Tuple[Product, int]]:
91         result = []
92         node = self.head
93         while node:
94             result.append((node.product, node.quantity))
95             node = node.next
96         return result
97
98     def total_price(self) -> float:
99         return sum(node.product.price * node.quantity
100                    for node in self._iter_nodes())
101
102     def _iter_nodes(self):
103         node = self.head
104         while node:
105             yield node
106             node = node.next
107
108 # -----
109 # Order Processing System (Queue)
110 # -----
111
112 class Order:
113     __next_id = 1
114
115     def __init__(self, cart_snapshot: List[Tuple[Product, int]]):
116         self.id = Order.__next_id
117         Order.__next_id += 1
118         self.items = cart_snapshot # list of (Product, quantity)
119
120     def __repr__(self):
121         return f"Order(id={self.id}, items=[{(p.id, q) for p, q in self.items}])"
122
123
124 class OrderProcessingSystem:
125     def __init__(self):
126         # Queue of orders (FIFO)
127         self.queue: deque[Order] = deque[Order]()
128
129     def place_order(self, cart: ShoppingCart) -> Order:
130         order = Order(cart.list_items())
131         self.queue.append(order)
132         return order
133
134     def process_next_order(self) -> Optional[Order]:
135         if not self.queue:
136             return None
137         return self.queue.popleft()
138
139     def pending_orders(self) -> int:
140         return len(self.queue)
141
142 # -----
143 # Top-Selling Products Tracker (Priority Queue / Max-Heap)
144 # -----
145
146 class TopSellingProductsTracker:
147     def __init__(self):
148         # product_id -> sales_count
149         self.sales: Dict[int, int] = {}
150         # priority queue: entries < (sales_count, product_id)
151         self.heap: List[Tuple[int, int]] = []
152
153     def record_sale(self, product_id: int, quantity: int = 1):
154         self.sales[product_id] = self.sales.get(product_id, 0) + quantity
155         # Push new priority entry; lazy update (we'll verify against self.sales on pop)
156         heapq.heappush(self.heap, (-self.sales[product_id], product_id))
157
158     def top_k(self, k: int) -> List[Tuple[int, int]]:
159         """
160         Returns list of (product_id, sales_count) for top k products.
161         Uses lazy removal from the heap to keep it consistent.
162         """

```

```

162         result = []
163         seen = set()
164
165         while self.heap and len(result) < k:
166             neg_sales, pid = heapq.heappop(self.heap)
167             current_sales = self.sales.get(pid, 0)
168
169             if current_sales == -neg_sales and pid not in seen:
170                 result.append(pid, current_sales)
171                 seen.add(pid)
172
173             # push back the elements we popped that are still valid
174             for pid in seen:
175                 heapq.heappush(self.heap, (-self.sales[pid], pid))
176
177         return result
178
179
180 # =====
181 # Delivery Route Planning (Graph + Dijkstra)
182 # =====
183 class DeliveryRoutePlanner:
184     def __init__(self):
185         # Graph as adjacency list: node -> [(neighbor, distance)]
186         self.graph = Dict[str, List[Tuple[str, float]]] = {}
187
188     def add_location(self, name: str):
189         if name not in self.graph:
190             self.graph[name] = []
191
192     def add_route(self, from_loc: str, to_loc: str, distance: float, bidirectional: bool = True):
193         self.add_location(from_loc)
194         self.add_location(to_loc)
195         self.graph[from_loc].append((to_loc, distance))
196         if bidirectional:
197             self.graph[to_loc].append((from_loc, distance))
198
199     def shortest_path(self, start: str, end: str) -> Tuple[float, List[str]]:
200         # Dijkstra's algorithm: returns (distance, path).
201         # Distance is float('inf') if no path exists.
202         if start not in self.graph or end not in self.graph:
203             return float('inf'), []
204
205         # min-heap: (distance, node, path)
206         heap = [(0.0, start, [start])]
207         visited = set()
208
209         while heap:
210             dist, node, path = heapq.heappop(heap)
211             if node in visited:
212                 continue
213             visited.add(node)
214
215             if node == end:
216                 return dist, path
217
218             for neighbor, weight in self.graph[node]:
219                 if neighbor not in visited:
220                     heapq.heappush(heap, (dist + weight, neighbor, path + [neighbor]))
221
222         return float('inf'), []
223
224
225 # =====
226 # Example usage
227 # =====
228 if __name__ == "__main__":
229     # Product search engine
230     search_engine = ProductSearchEngine()
231     p1 = Product(1, "Laptop", 1000.0)
232     p2 = Product(2, "Phone", 500.0)
233     p3 = Product(3, "Headphones", 100.0)
234     for p in (p1, p2, p3):
235         search_engine.add_product(p)
236
237     # Shopping cart
238     cart = ShoppingCart()
239     cart.add_product(search_engine.get_product(1), 1)
240     cart.add_product(search_engine.get_product(2), 2)
241     cart.add_product(search_engine.get_product(3), 3)
242     cart.remove_product(1, 1) # remove 1 headphone
243
244     print("Cart items:", cart.list_items())
245     print("Total price:", cart.total_price())
246
247     # Order processing
248     ops = OrderProcessingSystem()
249     order1 = ops.place_order(cart)
250     print("Placed order:", order1)
251     print("Pending orders:", ops.pending_orders())
252     processed = ops.process_next_order()
253     print("Processed order:", processed)
254     print("Pending orders:", ops.pending_orders())
255
256     # Top-selling products
257     tracker = TopSellingProductsTracker()
258     tracker.record_sale(1, 10) # Laptop sold 10
259     tracker.record_sale(2, 5) # Phone sold 5
260     tracker.record_sale(3, 7) # Headphones sold 7
261     print("Top 2 products (id, sales):", tracker.top_k(2))
262
263     # Delivery route planner
264     planner = DeliveryRoutePlanner()
265     planner.add_route("WarehouseA", "City1", 10.0)
266     planner.add_route("WarehouseA", "City2", 20.0)
267     planner.add_route("City1", "City2", 5.0)
268     planner.add_route("City2", "City3", 7.0)
269
270     dist, path = planner.shortest_path("WarehouseA", "City3")
271     print("Shortest route WarehouseA -> City3: ", path, "distance:", dist)

```

Output:

```

Cart items: [(Product(id=3, name='Headphones', price=100.0), 2), (Product(id=2, name='Phone', price=500.0), 2), (Product(id=1, name='Laptop', price=1000.0), 1)]
Total price: 2200.0
Placed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 1
Processed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 0
Top 2 products (id, sales): [(1, 10), (3, 7)]
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0
PS C:\2403A51L03\3-2\AI_A_C\Cursor AI>

Total price: 2200.0
Placed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 1
Processed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 0
Top 2 products (id, sales): [(1, 10), (3, 7)]
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0

```