Manual test cases — ShopDesk

Status defaults to **Not run** until a student executes the case. Record Actual, Evidence and final Status during class. All cases assume a running API and app, unless specified.

ID	Risk	Steps / test data	Expected	Technique	Status
TC-AUTH-001	R-02	Register unique `ada1@example.test` / `Password123!`	HTTP 201, user and token, no password hash	EP	Not run
TC-AUTH-002	R-02	Repeat registration with same email	HTTP 409 `email_taken`	EP	Not run
TC-AUTH-003	R-06	Register with 7-character password	HTTP 400 `validation_error`	BVA	Not run
TC-AUTH-004	R-02	Log in with known valid account	HTTP 200, JWT	EP	Not run
TC-AUTH-005	R-02	Wrong password	HTTP 401	Negative	Not run
TC-PROD-001	R-04	GET `/api/products` after seed	10 items, each integer `price_kobo`	EP	Not run
TC-PROD-002	R-04	GET `/api/products?search=desk`	2 matching catalogue entries	EP	Not run
TC-PROD-003	R-04	Search unmatched nonsense	200 with `data:[]`	EP	Not run
TC-PROD-004	R-04	GET `/api/products/9999`	404, `not_found`	Negative	Not run
TC-CART-001	R-01	Add one hub	Cart shows ₦`25,000.00`	EP	Not run
TC-CART-002	R-01	On detail screen change quantity to 2	Total is 5,000,000 kobo	BVA	Not run
TC-CART-003	R-05	Remove last cart line	Empty cart shown	EP	Not run
TC-ORDER-001	R-01	Logged-in customer places order	HTTP 201, server total, cart clears	EP	Not run
TC-ORDER-002	R-03	POST order without token	HTTP 401, no order	Negative	Not run
TC-ORDER-003	R-07	Request quantity above stock	HTTP 409, stock unchanged	BVA	Not run
TC-ORDER-004	R-02	Customer A fetches customer B order ID	HTTP 403	Negative	Not run

Handbook caveat: The sample Week 1 manual catalogue includes shipping/99-quantity and stricter password constraints that do not exist in the earlier supplied storefront/API. Those should be flagged as requirement gaps or demonstrated only through `web/src/lib` practice functions, rather than marked as passing end-to-end features.