Question 1

1. 

2. 

3. 

4. Running nginx



5. Accessing the page

6. 

Question 2

1.



```
[ec2-user@ip-172-31-3-136 ~]$ sudo docker volume create student data
"docker volume create" requires at most 1 argument.
See 'docker volume create --help'.

Usage:  docker volume create [OPTIONS] [VOLUME]

Create a volume
[ec2-user@ip-172-31-3-136 ~]$ sudo docker volume create studentdata
studentdata
```

2.





```
[ec2-user@ip-172-31-3-136 ~]$ sudo docker volume create student data
"docker volume create" requires at most 1 argument.
See 'docker volume create --help'.

Usage:  docker volume create [OPTIONS] [VOLUME]

Create a volume
[ec2-user@ip-172-31-3-136 ~]$ sudo docker volume create studentdata
studentdata
[ec2-user@ip-172-31-3-136 ~]$ ls
[ec2-user@ip-172-31-3-136 ~]$ sudo docker run -it -v studentdata:/ubuntu bash
Unable to find image 'bash:latest' locally
latest: Pulling from library/bash
9b70e313681f: Pull complete
15249c1264b1: Pull complete
87abf3302012: Pull complete
Digest: sha256:27639cc1442e5d2ed9778c122a60effff06f73812c0320e55fa8e5e0ec1f4f26
Status: Downloaded newer image for bash:latest
bash-5.3#
```

3.



```
bash-5.3#  echo "name: jay narkhede, roll no. : 24104A0038" > /data/info.txt
bash-5.3#
```

4.





```
bash-5.3#  echo "name: jay narkhede, roll no. : 24104A0038" > /data/info.txt
bash-5.3# cat /data/info.txt
name: jay narkhede, roll no. : 24104A0038
bash-5.3#
```

Question 3



Bonus question

1. Docker images are read only template
   docker container is a mutable instance made form docker image. It is isolated.

2. Docker volumes are used to **persist data** outside the container’s lifecycle. Since containers data is deleted after removal of container. Volumes provide the storage.